Machine and Tool

BLUE BOOK

an interview with:


HENRY VISCARDI ABILITIES, INC.

"How disabled a man is isn't nearly as important as whether he wants to work or not."

see page 102



also: Charlie Wick Starts His Series on Chipless Machining



... unequaled holding power,
but... NO IMPACT... NO MAR
... NO NOISE... with exclusive...

So vibration-free a nickel balances easily right above air-hydraulic holddowns applying tons of pressure, that's the Lodge & Shipley Shear feature demonstrated by the "nickel trick". Sof-Loc Holddown gives positive holding power without damage to the most easily marred material.

Available in capacities from 10 gauge to % inch, Lodge & Shipley Shears are built for heavy duty and high production shearing with almost a score of features vital to economical operation. Almost all of these features are included in the low base price whereas they're "extras" on comparable machines. The many advantages of Lodge & Shipley Shears are described in a new 20-page catalog. Request Bulletin S-347 from The Lodge & Shipley Co., 3074 Colerain Ave., Cincinnati 25, Ohio.



for shear excellence, choose . . .

HYDRAULIC HOLDDOWN SYSTEM



Adjustable for pressure and speed, Sof-Loc Holddowns eliminate Impact and damage.

Lodge & Shipley

.PATENTED, TRADEMARK REGISTERED

The FREEST CUTTING
Counterbore on the market

Now-designed for new "1960 SERIES" socket head cap screw standards

OVER 40 YEARS OF LEADERSHIP SINCE 1918



- Ample chip room prevents breakage caused by clogging
- Fast helix of the two flutes results in improved cutting action
- Solid pilot without grooves will not ream or mar the hole
- Only two cutting lips to regrind, cuts tool room sharpening time



THE WELDON TOOL COMPANY

3000 Woodhill Road . Cleveland 4, Ohio

Weiden distributors throughout U. S. A. and Canada carry complete stocks to serve you.

Use postpaid cord. Circle No. 201

April, 1961

1872 1961

UadeLATHES have always met the standards of the times

There's a real plus-factor for the user, in the long life and business continuity of the builder of a machine tool. The tool always has the original manufacturer behind it . . . to fulfill a guarantee, to supply parts and accessories, to see that it continues to operate and make money for the owner.

If you're interested in knowing more about this well-designed, modern lathe, with more than 88 years of integrity behind it, write for our new brochure on the Wade No. 94 Lethe.



2

MOW NOW

SWAGE PARTS LIKE THESE

SIMPLY QUICKLY AT LOW COST

Requires no additional machining



provides lowest cost method for producing rectangular, tapered, and formed cross sections from entry rounds, squares, or rectangles.

A REAL BOON TO COST CONSCIOUS MANUFACTURERS

*Patents Pending

Another Great First by



Actual unretouched photo of swaged samples include from top to bottom: Harrow spike, auger bit shank, soldering iron tip, and screwdriver.



Fonn engineers welcome the opportunity to evaluate and make recommendations for application to your production requirements.



THE FENN MANUFACTURING COMPANY, FENN ROAD, NEWINGTON, CONN.

New ARMSTRONG Swivel Pad

Now Armstrading deep throat "C" Clamps have the new (Pat. apd. for) Armstrading Ball-joint Swivel Pad. This "C" Clamp pad, developed by Armstrading Engineers, is tougher than any on the market. Rigorous testing in our own plant first proved this fact, and field tests in factories throughout the country have confirmed our own test results.

Here's Why it's



joint Swivel Pad is undercut so that when the ball of the screw is inserted, and the lip is permanently forced down, a solid steel wall is formed, inside the pad cavity, completely encircling the ball. This wall of steel makes it impossible for the pad

This wall of steel makes it impossible for the pad to come off the screw during normal use. In fact, our tests have proved that it is virtually impossible to intentionally knock the pad off with a hammer—yet the pad is free to swivel through an arc of approximately 40°.





Your ARMSTRONG Distributor can offer delivery from stock on this "400-Series" deep throat, drop-forged "C" Clamp with the new Ball-joint Swivel Pad. He also carries in stock the other styles of clamps in the ARMSTRONG Line—the broadest line of drop forged "C" Clamps.

ARMSTRONG BROS. TOOL CO., 5208 W. ARMSTRONG AVE. CHICAGO 46, ILLINOIS

SEE US AT BOOTH 3906 ASTME SHOW, NEW YORK COLISEUM

W. F. Schleicher, Vice President and Editorial Director E. Altholz, Editor J. B. Pond, Managing Editor

D. J. Fairfield, Assistant Editor EDITORIAL ART DEPARTMENT

EDITORIAL ART DEPARTMENT
R. R. Hadley,
Executive Art Director

J. R. Erickson, R. M. Erickson
L. M. Schroeder
Associate Art Directors

l. H. Smith, Manager; M. C. Routa, iditor; M. E. Moffett, Editor.

iditorial Advisory Board: M. John hlstromer, as 1. factory mgr., Chiago Screw Co.; Ronnie Burritt, facory mgr., J. J. Tourek Mfg. Co.; di Fluskey, consulting eng., Revere lamera Co.; J. Kosinski, works manger, Scully-Jones & Co.; Richard W. andon, management consultant, resap, McCormick and Paget; Paul Yrikos, vice-pres., Prikos & Becker Tool Co.

Hitchock Editorial Board: E. Altholz; . A. Pearson; M. M. Patterson; l. I. Schram, Jr.; W. E. Poole; D. H. oyce; M. E. Heuertz; B. B. Howat;

V. F. Schleicher.

husiness Staff: R. C. Van Kampen, hairman of the Board; O. A. Feldon, resident; V. C. Hogren, Executive lice President & Treasurer; E. P. Madigan lice President & Secretary; O. S. epper, Business Manager; N. M. Hoover, Assistant Business Manager; L. A. Elliott, Promotional Manager; L. J. Sietsema, Director of Resarch; Poole, Librarian; E. W. West, irector of Reader Services; R. I. ipreckels, Director of Circulation, Vancy Alcorn, Circulation Mgr., S. Todd, Production Manager; L. L. Yonts, Advertising Production Manager;

litchcock's District Offices:

New York: 551 Fifth Ave., MUrray Hill 7-6310; Connecticut: S. Glaston-bury, MEdford 3-7083; Boston: Hing-am, Mass., 2 Juniper Rd., Riverview 1960; Cleveland: 3639 Lee Rd., Kyline 2-3715; Detroit: 10432 W. AcNichols, Dlamond 1-9525; Cininnati: 1410 Wynnburn Park Dr., BLackburn 1-2987; Las Angeles: 3723 Wilshire Blvd., DUnkirk 8-2981; San Francisco: 515 Market St. Bldg., Tukon 2-4280; Seattle 766 Dexter Iorton Bldg., MAin 2-4363; St. oseph, Mich.: 2100 Lake View, UJ 3-5444.

Other Hitchcock Publications:

Hitchcock's Wood Working Digest; Assembly and Fastener Engineering: l'ant Management and Engineering: Justing Tool Engineering; Grinding and Finishing; School Bus Transporation; Metropolitan Transportation; Hitchcock's Machine & Tool Direcory; Hitchcock's Woodworking Diectory; Hitchcock's Assembly & Jastener Directory.

Publishers of Business Magazines and Directories Since 1898.



Machine and Tool


BLUE BOOK

for the Men of Action in Metalworking

CONTENTS FOR APRIL, 1961 VOL. 56, NO.	4
Features In This Issue	99 101
FEATURE ARTICLES	
America's Amazing Abilities, an interview with Henry Viscardi, Jr	110 118
COLUMNISTS	
Chipless Machining	
Now Finish Milling With ThrowawaysR. Ruckel	
FIELD REPORTS	
Light Poles Made on Twin Press Brakes. Tapes Make Debut at Steel Fabricator's. Thread Rolling Combined With Tracer Turning Right-Angle Drive Mills Keyway. Unloader Tied To Press Ram. Drill Press With Hollow Mill Proves Faster Than Lathe. Tool Beauty Salon.	140 141 142 143 143 144 144
DEPARTMENTS	
Shop Hints Free Literature News of Industry What's New in Metalworking Products Index Index to Advertisers One Last Word: Is The U.S. Losing The Race?	155 164 181 261
W. F. Schleicher	271

Published monthly. © Copyright 1961 by Hitchcock Publishing Company, Wheaton, Illinois. Printed in the U.S.A. Subscription rate is \$5.00 per year in the U.S.A., \$6.00 per year elsewhere. Editorial and Executive offices located at Geneva Rd., Wheaton, Illinois. Telephone Montrose 5-1000-2-3-4. Cable: HITCHPUB.







Tolerance of .000050"



Put your Bokum tool in the Bokumicro-Dial Boring Head*. For set-up, bore a hole a few thousandths undersize. Measure the hole and move the dial indicator (which moves the tool) to the exact reading you wish—you can read directly 50 millionths of an inch! You get absolute accuracy on production runs or tool room work. It's Bokumagic! Write today!

BOKUM TOOL COMPANY, INC.




14775 WILDEMERE AVENUE DETROIT 38, MICHIGAN


PATENT PENDING



of Leadership, Quality and Acceptance.

- 1. FIELD SERVICE Coast to Coast
- 2. BEST PRICES IN U.S.A.
- 3. LARGEST MACHINE TOOL STOCK
 -NEW & USED
- 4. TERMS TO FIT
- 5. RENT-BUY-LEASE





IMPERIAL MULTI-MATIC #10 IRONWORKER

Stationary and portable types SHEARS — PUNCH — COPING — NOTCH and BAR CUTTER. \$2895.



IMPERIAL SLIDING BED GAP LATHE

from 30" ctrs. to 300" ctrs. MISSILE — T — SLIDING BED & SPECIAL LATHES TO ORDER. Flame hardened, ground bed ways. Heat-hardened gears throughout. Precision roller spindle bearings.

IMPERIAL-WESTBURY Model IS TURRET MILL

Complete \$2034.50
Model T-1 TURRET MILL

Compound "Knuckle Joint," 12" cross travel, 1½ H.P. 42" x 9" table. Power feed to table measuring and slotting attachments, accessories.

Complete \$2314.50

AARON MACHINERY CO., Inc. 45 CROSBY ST., N. Y. 12 . WA 5-8300

BRANCHES AT: MINEOLA, N. Y. OAKLAND, CAL. LOS ANGELES, CAL. HOUSTON, TEXAS


FILMATIC PLAIN GRINDER saves up to 35 hours

in grinding hard-surfaced mixing screw

AT THE RIGHT you see a rough, tough part. It's rough because it has been hard-surfaced by welding. It's tough because, until recently, it taxed the ingenuity of manufacturing engineers to machine it.

The part is a 16"OD mixing screw, manufactured by a prominent builder of food and chemical machinery. Their problem was to machine the OD of the flights to a smooth finish and at a reasonable cost. Turning operations on a lathe required 35 to 45 hours. Too expensive. Now, the OD is ground in 10 to 15 hours! A CINCINNATI FILMATIC 24" x 120" Plain Grinding Machine performs the operation, reducing cost by more than half. And, finish is of much higher quality than ever before.

All CINCINNATI Centertype Grinding Machines are built to operate at the highest standards of performance. Generously proportioned structural



Tops in grinding heavy, hard stock and large work. It's easy for this new CINCINNATI FILMATIC 24" x 120" Plain Grinder. Catalog G-709-1.

elements are one plus factor. Another is the dependable pressure lubricating system for the ways. And still another is the FILMATIC bearing mounting for the grinding wheel spindle... no adjustment ever required for extreme variables in stock removal. More information or CINCINNATI FILMATIC Plain and Rol Grinding Machines in the heavy duty sizes may be obtained by writing for Catalog G-709-1.



Photographs courtesy of Baker Perkins, Inc., Saginaw, Mich.



Huge savings in time are gained by replacing turning with grinding to remove hard, heavy stock on the OD of mixing screws. A CINCINNATI 24" x 120" Plain Grinder performs the operation, grinding the rough, interrupted surfaces to a high-quality finish.



ROLL . CHUCKING . CENTERLESS LAPPING



The second secon



Unlocked position *
in this position tools
are inserted or removed.



Locked position e Handle is moved upward as shown to lock tools securely. Desired locking pressure obtained by nose adjustment.



Working position •
Tool now securely held
in position—handle
removed.

TREE RAPID-LOK COLLET ADAPTER



TREE FEATURE


The Tree Rapid-Lok is a collet adapter designed to hold end mills, boring bars, and other tooling accurately, securely and with great rapidity on both horizontal and vertical mills, jig borers, boring bars and other machines.

It is an adaptation of an exclusive

It is an adaptation of an exclusive feature which has been proved in use on Tree milling machines over a period of years.



TREE TOOL & DIE WORKS
RACINE, WISCONSIN



MASTERLINE® 51B SUPERFINISHER

New—for parts not requiring traverse. Longitudinally adjustable platen supports reciprocating unit holding one or two quills. Add a second platen and you can handle up to four diameters at once—automatically.



A similar Model 52A offers longitudinal stone traverse. Call your Gisholt Representative or write for Catalog 1159-C.

Are you giving your competitors a decisive edge by using outdated surface-finishing methods?

If you need a controlled finish (1 microinch RMS to 80) Superfinish will cut your costs and improve quality.

You save on initial investment, grindingwheel costs, production time, work-handling, and floor space.

In many cases you can Superfinish® direct from a turned surface and eliminate grinding. On other parts you rough-grind, then Superfinish. Your finish is produced in seconds, automatically, piece after piece!




MACHINE COMPANY Medison 10, Wisconsin, U.S.A.

Turret Lathes . Automatic Lathes . Balancers . Superfinishers . Threading Lathes Factory-Rebuilt Machines with New-Machine Guarantee



PRODUCE 5 TIMES MORE PARTS BURGMASTER Automatic 6-Spindle Turret Drill



Shot pin fixture locator is shown projecting through table directly under the spindle. Color paths painted on template correspond to colors on spindle tooling as a visual aid for operation sequence.

Sequence of Operations

Spindle Number	Color Code	Tool	Speed
1	Red	Drill for #4-40 tap	1700
2	Black	Drill for #8-30 tap	1700
3	Green	Drill for #10-32 tap	1700
4	Red	Tap #4-40	900
5	Black	Top #8-30	900
6	Green	Tap #10-32	900

Power Feed and Power Indexed Turret Speed Machining

- Meridian Metalcraft, Whittier, California, use a Burgmaster Automatic 6spindle Turret Drill to machine several designs of Heat Exchangers for Instruments. In the setup shown, 60 holes in a range of three diameters are drilled and tapped in six minutes—five times faster than with former drill press methods. The simpler setup also saves 40% in tooling.
- * Special mounting of the Turret Head on a Riveter C-frame provides 45''' throat depth for widest utilization of this efficient setup. Bushings in the fixture bottom duplicate the hole pattern, and are sequentially engaged by an air-operated shot pin located in the table directly under the spindle. After hand shifting the fixture to approximate position $(\pm 1/6'')$ as indicated by the template, the operator presses a hand-held control button to seat the shot pin and bring the fixture to exact position. The safely seated shot pin automatically initiates the spindle power feed cycle.



WRITE FOR FREE LITERATURE on Burgmaster Bench Model Turret Drills and Rapid Positioning Table. \(\frac{4}{2}\)" drill and tap capacity in steel. Representatives in principal cities.




BURGMASTER CORPORATION

SMALL TOOL DIVISION - BURG TOOL MANUFACTURING CO., INC.

13001 S. Figueroe St., Box 311, Gardone, Calif. Phone: FAculty 1-3510-Phone, who or write Dept. OA
World's largest manufacturer of turret-type drilling and tapping machines.

basic reasons Lapping is now a standard



2. NEED: Quality control requirements for lapping to thousandths of an inch precision has become increasingly necessary. Literally any piece part produced of any material is quickly, accurately, economically lapped and/

3. COMPLETE LINE: from small bench type 6" roller lapping machines to 48"

or finished in small or high volume pro-

Write for free Spitfire Catalog.

TOOL & MACHINE CO 2931 N. Puloski Rd. Chicago 41, Illinois Phone: AVenue 6-1610

Use postpaid card. Circle No. 212

Machine



FASTER, accurate cut-off LONGER cut-off blade life SMOOTHER cut-off surfaces

WIDEST RANGE OF BLADE MATERIALS

- Empire cut-off blades are available in four grades of H.S. Steel (high-cobalt, high-vanadium). Range covers most any requirement for H.S. Steel tooling.
- Solid cast-alloy blades (non-ferrous, cobalt-chromiumtungsten) have high red-hardness, superior resistance to abrasion and are non-magnetic.
- Carbide tipped cut-off blades come in four grades of carbide
 -the best carbide for each job can be furnished.



- Paster Cutting precision grinding of all blade surfaces assures sharper cutting edges.
- Reduced Friction hollow-ground top causes chips to collapse, relieving friction against sidewall of cut.
- Cooler Cutting collapsed chips permit coolant to reach blade cutting edges.
- Greater Precision blades are precision ground on all surfaces, centrality of head to shank is held to close tolerances.
- Smoother Cut-Off Surfaces sharper cutting edges, collapsed chips, better coolant flow, and liberal side clearances add up to smoother cutting.
- Longer Blade Life wide selection of blade materials, finest blade design, resharpening on front face only, assures longer life on every cut-off job.

Made under license issued by John Milton Luers
Patents, Inc.

11501 LAMBS ROAD . MEMPHIS, MICHIGAN



The job illustrated is typical of work where large amounts of metal are removed. For example, one forging was reduced from 1850 lbs. as forged to 890 lbs. after machining. Material AISI-1045. Floor-to-floor time: 51/4 hours including setup and gaging.

AT CANN & SAUL STEEL COMPANY Royersford, Pa.



80 lbs. of metal turned from this forging in 3 minutes

Warner & Swasey 36" swing 5-A in progressive forge shop cuts metal full time at maximum rates yet provides fast handling for small lot production.

The 5-A turret lathe has the power and the rigidity to hog metal at this clip yet the same machine finishes work to .002" or less for Cann &




Rough forgings machined by the Cann & Saul Company include medium carbon steels, stainless, titanium and other alloys, and frequently are heat treated to 300 Brinell before machining. Eccentric and interrupted cuts are a stiff test of machine rigidity. Saul. Heavy metal removal plus the ability to handle one to four-piece lots at low cost on a battery of Warner & Swasey's are but two reasons why Cann & Saul remains a leader in the competitive custom machined forging field. They make good use of the power built into the 5-A Extra Heavy Duty Warner & Swasey turret lathe by taking cuts up to 1" deep at 300 SFPM and .025" feed. The machine's 36" swing and 12½" hole through the spindle accommodates a wide variety of forging shapes.

The hydraulic speed shifts and easy handling tool carriages help the operator to handle small lots efficiently... and the work is within easy reach for rapid gaging, an extremely important factor on a big machine like the 5-A.

For more information contact your resident Warner & Swasey Field Engineer, or Warner & Swasey Company, Cleveland 3, Ohio.

YOU CAN TURN IT BETTER, FASTER, FOR LESS...WITH A WARNER & SWASEY





Famous Perfection Grinding Live Center H.S.S. and Carbide Accurate Detachable Points Expansion Compensating Lathe Centers

ANNOUNCING THE FIRST COMPLETE LINE OF PRECISION-BUILT LIVE CENTERS

INCLUDING 5 TYPES OF EXPANSION COMPENSATING CENTERS

- · the only complete line
- the only guaranteed self-adjusting live center

INTRODUCING J & S Tool Company's complete new line of live centers with accuracy better than .0001", with these features:

- · Guaranteed one year.
- · Self-adjusting bearing take-up.
- RPM speeds up to capacity of present-day machines.
- · Correct capacity rating.
- Hardened and ground throughout.

Write today for a free copy of the J & S Live Center Catalog.

J&S TOOL CO., INC.

882 DORSA AVE., LIVINGSTON, N. J.

WYman 2-3181



Send for

Your local supply house carries Dayton Rogers', Layout Fluid.

Applicable to all metal. One merely wipes the surface clean and then brushes on the Layout Fluid.

Dries Instantly. No waste. Scribed lines are pronounced and contrast to the dark blue background, thus relieving eyestrain.

Assures greater accuracy and speeds up work. You will save time and money on all layout jobs.

A sample is waiting for you. Send for it today.

MINNEAPOLIS 7, MINNESOTA



REDUCE MANUAL HANDLING OF PARTS TO A MINIMUM



Transfer & Storage

PARTS FEEDERS

Relieve production lag between primary and secondary operations


Syntron Transfer & Storage Parts Feeders are designed to receive parts at one level, store prior to usage and discharge in an oriented position at another level. They provide an automatic, instantly adjustable method of distributing parts from one process operation to another; eliminating slow, manual parts handling.

The powerful electromagnetic drive unit produces 3600 instantly controllable vibrations per minute. Simplicity of design means dependability of operation, longer service life, and lower maintenance.

If you have an operation to operation parts handling problem, Syntron Transfer & Storage Parts Feeders will help reduce costs and speed production.



Call your Syntron Representative or write for a Syntron Parts Feeder Catalog Section.



61PF4

SYNTRON

SYNTRON COMPANY

300 Levington Avenue Homer City, Pa

INSPECTION PROJECTOR MAGNIFIES FOR (R) QUALITY...

Our inspection projector magnifies cutting edges to eliminate the minute angular deflection that could cause you castly production losses . . . just one of many inspections that account for Circle R quality.

CIRCLE R saws, slitters and combination center drills must submit to constant exhaustive inspection to work their way to you. They've got to prove they can ensure you correct cutting angles, long service, and minimal downtime.

Consult these CIRCLE R Specialists . .

CONSULT THE BURBANK Production Mach. Sales lat. CEDAR RAPIDS McMool Tool & Supply Corp. CHICAGO Bund Rabethan E Co. CLEVELAND Production Tool Co. DAYYOM

ho Eston Company
NESS AN APPOLES
BARRISH RICHIES
MEMPHIS
Estonich Bermin
Tool Specialists
MILWAUKEE
ord Tool Company
MONTEEAL
umphray B. Molton
W HYDE PARK
he Ecton Company

NEW YORK CITY

1. Y. Crumonin (Expert)
PHILADELPHIA
Suneral Tool Sales Co.
PHOCENIX
Disagenia York Contur
PITTSBURGH
Relph Expecto & Co.
PROVINGENCY

PROVIDENCE Fred S. McMillan BOCHESTER James C. Huma

CIRCULAR TOOL CO., INC.

PROVIDENCE 5, RHODE ISLAND
Specialists in Circular Cutting Tools Since 1923

METAL SLITTING SAWS · GEPPER SLITTING SAWS · STEER SLETTING SAWS · CENUMENTATION SLITTING SAWS · CHECKLES' SLOTTING SAWS · CHT OFF SAWS · CHCKLAR MINVES & DOTARY STEER BLADES · CIRCOLOY STEEL SAWS · SHALE & THPYER THRUSTER MARKET SAWS · COMMINED BRILLS & COUNTERSINES · CENTER BEAMERS



you want to control
and improve the quality of your product
with measurements displayed
on a dial ... in an air column
or in signal lights ... in a chart

there'll be **no** in the results when you measure with Sheffield gages



A subsidiary of The Bendix Corporation

Inspection Gages, Dimensional Control Instruments, Machine Controls, Automatic Gaging & Assembly Systems, Measuray® X-Ray Thickness Measuring, Crushtrue® & Multiform® Grinders, Cavitron® Ultrasonic Machine Tools, Press-Pacer® Transfer Units, Large Dies, Tooling. Contract Manufacturing.



UTILITY MODEL 1612-U

offers 16" throat and 12" thickness capacity.

A larger Model 2012-U has 30° and 12° thickness capacity. Both machines have all-welded box frame construction. No. 10 but welder; high-speed insertage guides for band widths from ½ to ½°, and other top-quality features. Both are guaranteed by DoALL, world's leader in band sewing machines and band

USES THIS NEW DART* BLADE


onstration.

Service store today for a dem-

The Utility machine is capable of using the new Dart blade, which is guaranteed to outperform any make of carbon steel saw band. Specialized heat-treatment gives it a spring-tempered back and full, hard cutting edge. Custom-welded to length with DoALL's exclusive process—guarantees strongest weld made and perfectly matched teeth. Set is guaranteed to within ± .002"

See if at ASTME Show, Booth 2222 New York Coliseum - May





FAST!

Your hack sawing machines will produce faster cutting-off on all types of work when they are equipped with unbreakable Marvel High-Speed-Edge Hack Saw Blades.

Why? Because these are the blades specifically designed to take the high speeds and heavier feed pressures demanded by today's production schedules.

What's more, your operators know—or will soon learn—they can increase speed and pressure without endangering themselves or the machine, because these are unbreakable Marvel High-Speed-Edge Blades . . . the blades that have set the standard for all other blades to match—if they can.


Ask for Marvel High-Speed-Edge Hack Saw Blades by name and you can be sure you're getting the unbreakable blades designed to give you maximum accuracy and speed in your cutting-off operations. Leading Industrial Distributors have Marvel Blades in stock.

Write for the latest Cutting Tool Bulletin and the name of your nearest Marvel Distributor.

MARVEL Metal Cutting SAWS

BETTER MACHINES
BETTER BLADES

ARMSTRONG-BLUM MANUFACTURING CO. 5700 Bloomingdale Avenue · Chicago 39, Illinois



FAST, True-Square Setups With The Robbins 90° Indicator Gage!

- Checks squareness instantly
- Registers angular errors to plus or minus .0001"
- Dial indicator for easy, visual measurement
- Designed for toolroom, inspection or production use
- Includes Master Square accurate to .0001"

Magna-Sine or non-magnetic Sine Plates, it quickly checks accuracy of angles other than 90 degrees.

The Robbins 90° Indicator Gage is furnished complete with Dial Gage, Master Square accurate to .0001", and fitted hardwood box. Contact your Robbins Representative, or write direct for price and application data on this moneysaving shortcut to true-square inspection and machining.

With the Robbins 90° Indicator Gage, inspection and setups are faster, easier, more accurate. No special skills are needed to use it, no shimming or complicated build-ups are needed to check squareness.

A dial indicator visually reads 90° angles with accuracy to plus or minus .0001" on surfaces from $1\frac{1}{2}$ " to $17\frac{3}{4}$ " long. The Robbins Indicator Gage also checks relative position of parts or fixture components, and, when used with Robbins

61-28





Use it in the plant. Use it outdoors. Use it with remote control. You'll like MagnaLift features such as these: Power pack an entirely separate unit from magnet—power pack can be placed on magnet or placed elsewhere for remote control by extension cable—OFF-ON switch located on top of unit for maximum convenience—built-in charging indicator and plug-in receptacle for battery power pack. You'll like the way MagnaLift makes lifting jobs easier, safer, faster. Send for complete details about MagnaLift, the new and different lift magnet. Write Dept. BB-461.

Model LM4, \$385.00 F.O.B. Big Rapids, Mich.

3 Power Packs

12-VOLT BATTERY


12-VOLT BATTERY— VARIABLE HOLDING POWER

110-VOLT A.C.— BUILT-IN D.C. RECTIFIER

Hanchett MAGNA-LOCK CORPORATION BIG RAPIDS, MICHIGAN, U.S.A.

ALL SET for more and better cuts per dollar!





"Job Tempered" Hack Saw Blades







High Speed "M"-HAX 12"-14T All Hard



UNAPOEARTY PAYS OFF Uniform set gives the teeth of every Heller-blade the clearance needed for straight, fast cutting. Uniform shape, spacing and height of teeth distribute wear evenly and lengthen life. Uniform temper over the full length of every blade adds extra resistance against stresses and strains.


TEST THEM YOURSELF! You'll find that Heller's certified uniformity within each blade and from blade to blade adds up to superior cutting at lower costs. Your nearby Heller distributor has a complete line of Heller Hack Saw Blades . . . 3 types for power use . . . 3 types for hand use . . . in all standard specifications. So, he can help you select the right blade for any job.

HELLER TOOL CO.



America's Oldest File Manufacturer NEWCOMERSTOWN, OHIO

Branch Offices and Warehouses, Newerk, N. J. . Detroit . Chicago . Shrevepast . Les Angeles . Portland, Oregon Use postpaid card. Circle No. 224



ADJUSTABLE DIES

For Perforating and Notching Materials up thru 1/4" Mild Steel

save thousands \$\$\$ in tooling costs

Interchangeable punch and die parts are readily arranged on Tee-Slot die sets. The same parts can be used again and again in different groupings. You profit in numerous ways:

- Even new workers can quickly learn to make pattern changes.
- · Tooling costs cut to rock bottom.
- · Precise accuracy assured.
- Punches and dies stocked in .001" increments from .100" to .500" diameters. Larger sizes in stock up to 3"

S. 746	GET THE TIME		
Adjustable Die Catalog	Magna-Die Catalog	Custom Die Bulletin	ON WHISTLES PRODUCTS:
COMPANY			magnetic dies
CITY	ZONE	STATE	adjustable die

POSITIVE DIE PROTECTION

AT 350 STROKES/MIN.

Jobs diverted from \$15,000 press to \$3,000 KENCO

ELECTRO-SAFE PRESS

A Los Angeles manufacturer of precision stampings produces burr-less parts at 350 strokes per minute in a Kenco 15-ton Electro-Safe Press. Due to critical die closure tolerances required to blank material as thin as .001", built-in die guidance formerly required heavy die set construction and the die capacity of a \$15,000 straight side press. The \$3,000 Electro-Safe and less expensive sub-press die represent major savings while offering positive die protection.

The advantages of Electro-Safe construction in high speed automatic operation lies in its fast-stopping capability—there is no clutch or high energy flywheel. Unique controls permit most effective monitoring by safety detectors that will stop the press in less than ½ stroke at high speed should a "fault" signal occur.

WRITE FOR ELECTRO-SAFE BULLETIN




-complete specifications and dimensions: 5, 8, 12, 15, 18, 23 and 26 tons.






THE MOST COMPLETE LINE OF SMALE PURCH PRESSES IN THE WORLD



20" CLAUSING
HEAVY-DUTY
DRILL PRESS

POSITIVE-POWER VARIABLE or STEP PULLEY 5 or 10 SPEED

COUNTERSHAFT DRIVES



- SPEED RANGES —
 150 to 2000 RPM

 Dial speeds with variable drive model.
- PRODUCTION RATED

Dia, hole in cast iron 1%"
Dia, hele in steel %"

- GEAR DRIVEN POWER FEED or HAND FEED
- MACHINED and BALANCED
 PULLEYS
- 19½" x 22" PRECISION GROUND TABLE—4" COLUMN with ½" WALL — MASSIVE, GROUND BASE
- READY-TO-RUN MOTOR and SWITCH INSTALLED — WIRED — FACTORY TESTED

Clausing drills out-perform — on continuous production, in the tool room, maintenance shop — every application — because they are built better. Ask your dealer to prove it! And write for literature on the new 20" and 15" models.

CLAUSING

ATLAS PRESS COMPANY

OUTSTANDING VALUES IN PRECISION MACHINES



Hours in tool rooms and die shops with CONTOUR SAWING AND FILING

You can save real time and money in the production of parts for jigs and fixtures, dies, gages, templates and special machine production by using an Oliver of Adrian contour sawing and filing machine.

The Oliver is so simple to operate that all sawing, filing and lapping can be handled by an ordinary mechanic—saving a skilled die maker's costly time. Parts can be shaped to dimension faster, more accurately with no hand filing or semi-finishing operations. Available in five types — bench or pedestal. Write today.

OLIVER of ADRIAN OLIVER INSTRUMENT COMPANY 1408 E Maumee St. • Adrian, Michigan



Use postpaid card. Circle No. 228

Save

REPRINTS NOW AVAILABLE ON THESE BLUE BOOK ARTICLES OF LASTING INTEREST

- Reducing Production Cost With Pneumatic Devices
- When-And How Much-Should You Invest In Tooling?
- ☐ Pneumation Of Machines
- How Douglas Got The DC-8 Airborne
- The Best Of Dennis Jones
- Saw Blade Series

For your FREE copies, check this page, tear out and mail in-or just drop us a line stating which articles you want.

MACHINE and TOOL BLUE BOOK

WHEATON

ILLINOIS

DOVETAIL TOOLS

COST LESS WHEN MADE FROM

SOMMA BLANKS

If you make your own dovetail tools for automatic machines, you can get two fold savings with Somma Blanks.

- · Costly machine and toolmakers' time preparing blanks is eliminated.
- · Volume purchasing of steel by Somma keeps material, costs down.

Prompt delivery in either M-2 or T-5 H.S.S. Write for prices and name of representative in your area.



STANDARD SIZE HARDENED DOVETAIL FORM TOOL and SHAVE TOOL BLANKS



TOOL CO., INC. 118 SCOTT ROAD, WATERBURY, CONN.

West Coast Worehouse: 576 N. Frarie, Hawthorne, Cal.



 KEEP YOUR OPERATING COSTS WHERE THEY SHOULD BE!

You Make Your Own Engraved Nameplates!

PORTABLE 40-POUND BENCH MODEL 106

Here is a speedy, economical 2 or 3-dimensional engraver used by thousands of dollar-conscious companies. It features 5 positive, accurate pantographic ratios; ball bearing spindle with 3 speeds up to 14,000 rpm. Is supplied with one copy carrier that accepts all standard master type sizes. Will ectually work up to 10" by any width. Height of pantograph and position of cutter are continuously adjustable.

MODEL D-2 HEAVY-DUTY 2-DIMENSIONAL

Pantograph for milling, drilling and engraving.

Vertical adjustment of copy table automatic with Pantograph. Features: unobstructed on 3 sides to take large work; micrometer adjustment for depth of cut; ball bearing construction throughout; spindle speeds up to 26,000 rpm for engraving or machining; vertical range over 10"; ratios 2-to 1 to infinity — master copy area 26" x 10"

Write or call for full.





NEW MODEL D2-201 PNEUMATIC ATTACHMENT

for use with Model D2 Pantograph Engraver to rapidly drill holes in printed circuits by tracing templates. Drills as many as 100 holes per minute. Equipped with foot switch; spindle air cylinder; regulating valve and pressure gauge; filter and oiler. It's ready to use as soon as it's attached to an air compressor.

GREEN INSTRUMENT COMPANY, INC.

Dept. 386, 295 Vasser St., Cambridge 39, Mass. Tel. Ellot 4-2989

SIMONDS
MEANS
SAVINGS
WHATEVER
YOU
CUT



Now Change from



"Red Tang" Files

For faster, easier filing, Simonds "Red Tang" Files are sharper to start with, hog off more metal per stroke. More wear-resistant, too, they keep on cutting long after other files have turned dull and useless.



Simonds Circular Saws

Tops for fast, straight cutting, Simonds Saws are designed and made to stay on the job longer. Available in 5 types: Solid Tooth, Hard Rim, Inserted Tooth, Segmental and Carbide Tipped—for lowest cost cutting of all kinds of metal.



Simonds Band Saw Bla

Our new "Super" High Speed Steel Bane you up to 3 times better performance other high speed steel blade you're no It's a stertling new advance that can tially reduce your cutting costs.



Hacking to Cutting...

with Simonds "Red End" Hacksaw Blades

Important Cutting Fact! Simonds big "Red End" Hacksaw Blades cut curled chips like the cutting tool on a lathe.

Result? You cut faster, you cut straighter — get more work done in far less time.

What's more, Simonds blades are made from tough, cross-rolled steel . . . steel that stays sharp longer, resists breakage, gives you many more cuts per blade!

But don't take our word for it. Test a box of 10 Simonds "Red End" Blades against any 10 others. See for yourself how Simonds will up your cutoff production, lower your blade costs.

Simonds "Red End" Power Blades come in All-Hard

and Shatterproof types in all standard lengths, thicknesses and tooth spacing . . . a "right" blade for every job.

Three types of Hand Blades are also furnished in all standard specifications for easier cutting, longer life and lower costs. Call your local Simonds Distributor for prompt delivery or further details.



Buy through your local Simonds Distributor for

- Local Stocks - Local Speed - Local Skill

Factory Branches in Union, N. J., Chicago, Shreveport, La., Los Angales, San Francisco, Portland, Ore. • Canadian Factory in Granby, Que. • Simonds Divisions: Simonds Steel Mill, Lockport, N. Y.; Heller Tool Co., Newcomerstown, Ohio; Simonds Abrasive Co., Philadelphia, Pa. and Arvida, Que., Can.



So gentle it won't chip china, yet powerful enough to bend steel tubing as if it were a soda straw. In a nutshell, this demonstrates the almost unbelievable degree of control built into Logan air-draulic devices.

The controlled accuracy gives this equipment a versatility and flexibility that makes it adaptable to all kinds of jobs, ranging from precision laboratory assignments to actual production line work.

If you would like additional information about air-draulic devices or other Logan products, merely fill in the coupon below.



Check the Items you want, fill in your name and address, tear out and mail to:

Logansport I	Machine	Co., Inc	C. *	750	Center	Avenue,	Logansport, Indiana	Ř.
--------------	---------	----------	------	-----	--------	---------	---------------------	----

- 100-1 AIR CYLINDERS
- 100-2 MILL-TYPE AIR CYLS.
- 100-3 AIR-DRAULIC CYLS.
- 100-4 AIR VALVES
- 100-5 LOGANSQUARE CYLS.
- 100-6 ULTRAMATION CYLS.
- 100-7 SUB-PLATE AIR VALVE
- 300-1 CHUCKS 300-2 PRESSES
- 200-1 HYD. POWER UNITS
- 200-2 ROTOCAST HYD. CYLS.
- .200-3 750 SERIES HYD, CYLS.
- 200-4 and 200-7 HYD. VALVES
- 200-6 SUPER-MATIC CYLS.
- ABC BOOKLET
- CIRCUIT RIDER
- CALCULATOR
- FACTS OF LIFE

- Please send copy of catalog
- NAME
- TITLE.
- COMPANY
- ADDRESS

Use postpaid card. Circle No. 235



CIMCOOL
Cutting Fluids

FOR 100% OF ALL METAL CUTTING JOBS

Production-proved products of The Cincinnati Milling Machine Co.

CIMCOOL 52 Concentrate — The pink fluid which covers 85% of all metal cutting jobs.
CIMPERIAL * — Newest in the famous, industry-proven line of Ciscool.* Cutting Fluids.
CIMPLUS — The transparent grinding fluid which provides exceptional rust control.
CIMCUT Concentrates (AA, NC, SS) — For every job requiring an oil-base cutting fluid.
ALSO — CIMCOOL Tapping Compound — CIMCOOL Backing Closes.

For full information on the complete family of CIMCOOL Cutting Fluids, call your CIMCOOL Distributor. Or contact Cincinnati Milling Products Division, Cincinnati 9, Ohio.

*Treede March Rep. U. 8. Pat. On.



Give your products <u>all</u> the high-production, high precision advantages of Fellows Gear Shaper performance by tooling up with Fellows cutters.

The <u>better</u> design of Fellows cutters is the result of advanced engineering techniques, including the use of a high-speed computer for solving design and application problems. Their <u>better</u> quality is the result of constant advances in metallurgy and manufacturing methods. And, proof of their <u>better</u> performance are the thousands of Fellows cutters in use on modern gear production lines.

Fellows cutters on Fellows machines lower costs and speed production on external and internal, spur and helical



THE FELLOWS GEAR SHAPER COMPANY 78 River Street, Springfield, Vermont, U.S.A. Branch Offices:

THE PRECISION

FEllows

1048 North Woodward Ave., Royal Oak, Mich. 150 West Pleasant Ave., Maywood, N. J. 5835 West North Avenue, Chicago 39 6214 West Manchester Ave., Los Angeles 45

Gear Production Equipment

ELECTRO-MAGNETIC TYPE

Exclusive laminated top plate. Circular locking take-up on hinge rolls for continuous accuracy. All-steel, moisture-proof. Uniformly distributed holding power.

PERMANENT MAGNET TYPE

Low height, light weight, positive holding power.

HARDENED STEEL SINE PLATES

Completely stabilized. Circular locking take-up. Tapped holes for clamping work.

Compound Annie Sine Chuck




		MODEL	(SINE) A	(SINE) B	C	D	E	F	G	PRICE
				EL	ECTRO-	MAGN	ETIC			
انت		DA-5	5.000	5.000	61/2	6	511/4	714	61/5	\$ 495.00
		DA-10	10.000	5.000	111%	6	5196	1254	614	650.00
		DA-1010	10.000	10.000	111/5	10	513%	1256	101/2	1,300.00
	8 -8-	DA-20	20.000	5.000	2115	6	5136	2214	61/6	1,750.00
-	21122			FER	MANEN	T MAI	GNET			
	-0-	DP-5	5.000	5.000	6	6	51/a	714	614	495,00
		DP-10	10.000	5.000	12	6	51/4	1254	614	650.00
	Single Angle Sin	e Chuck	200							
	ample reages and	MODEL	(SINE) A	c	D				G	PRICE
			10000711		ECTRO-					
		SA-5	5.000	61/2	A	41/		734	61/2	\$ 340,00
	-	SA-10	10.000	1139	6	436		256	61/2	430.00
		SA-1010	10.000	1136	10	436		234	1014	850.00
1		SA-1010	20.000	2135	10	436		214	61/2	1,250.00
-	A STATE OF THE STA	3A-20	20.000					274	072	1,200.00
-	p-6				MANEN	-	GNET			
		SP-5	5.000	6	6	3		714	61/2	340.00
-		SP-10	10.000	12	6	3	% 1	214	61/2	430.00
	Compound Angle	Sine Pic	rte in	THE OWNER OF THE OWNER,		1 18	1820	2000		
8 .										
	compound Angle	MODEL	(SINE) A	(SINE) 8	C	D	E	F	G	PRICE
	~-Q	DA-SP	5.000	5.000	61/5	61/2	3%	734	61/5	\$ 430.00
			5.000	5.000 5.000	61/5 111/5	_	3% 3%	734 1234		\$ 430.00 595.00
		DA-SP	5.000	5.000 5.000 10.000	635 1135 1135	61/2	3% 3% 3%	734 1234 1234	61/2 61/2	\$ 430.00 595.00 1,050.00
T.M.		DA-SP DA-10P	5.000	5.000 5.000	61/5 111/5	61/2	3% 3%	734 1234	61/2	\$ 430.00 595.00
MAN	Single Angle Sin	DA-5P DA-10P DA-1010P DA-20P	5.000 10.000 10.000	5.000 5.000 10.000	635 1135 1135	61/2	3% 3% 3%	734 1234 1234	61/2 61/2	\$ 430.00 595.00 1,050.00
T IMA		DA-5P DA-10P DA-1010P DA-20P	5.000 10.000 10.000	5.000 5.000 10,000 5.000	635 1135 1135	61/2	3% 3% 3%	734 1234 1234	61/2 61/2	\$ 430.00 595.00 1,050.00
The last		DA-SP DA-10P DA-1010P DA-20P	5.000 10.000 10.000 20.000	5.000 5.000 10.000 5.000	61/5 111/5 111/5 211/5 D	61/2	3% 3% 3% 3% 3%	714 1214 1214 2214 7	61/2 61/2 11 101/2 G	\$ 430.00 595.00 1,050.00 1,350.00
1		DA-SP DA-10P DA-1010P DA-20P Plate MODEL	5.000 10,000 10,000 20,000	5.000 5.000 10.000 5.000	61/2 111/2 111/2 211/2 D	6 1/2 6 1/2 11 6 1/2	3% 3% 3% 3% 3%	714 1214 1214 2214 F 714 714	61/2 61/2 11 101/2 G	\$ 430.00 595.00 1,050.00 1,350.00 PRICE \$280.00 380.00
		DA-SP DA-10P DA-1010P DA-20P Plate MODEL SA-SP	5.000 10.000 10.000 20.000 (SINE) A	5.000 5.000 10.000 5.000 C 61/2 111/2	61/5 111/5 111/5 211/5 D	6 1/2 6 1/2 11 6 1/2	3% 3% 3% 3% 3% 1	714 1214 1214 2214 7	61/2 61/2 11 101/2 G	\$ 430.00 595.00 1,050.00 1,350.00 PRICE \$280.00

Order now for prompt delivery

MAGNA-LOCK, INCORPORATED

BIG RAPIDS, MICHIGAN, U.S.A.



new tools for new horizons...

Today at the threshold of a new era, when new worlds are opening up at an ever-increasing speed, new tools must be created to meet the requirements of our new technology. Rotary files are increasingly used in thousands of operations for metal removal and finishing, on all kinds of metals, trigher speeds and new materials present special problems and old problems, such as chip removal, assume even greater proportions.

To meet these new requirements, the Grobel File Company of America has developed entirely new types of Rotary files such as the Facet Tooths and Bi-Dexis Tungsten Carbide Rotary Files. These major advancements reduce chatter, facilitate the removal of chips and greatly increase speed, ease and efficiency of operation.


Ask your distributor for detailed information or write directly to

GROBET FILE COMPANY OF AMERICA, INC.

Offices and Warehouses Chicago 311 North Desplaines St.—CE.ite 6 1489.
Atlanta 1475 Spring St., N.W.—TRinity 6 1064

Los Angeles: 3314 Fruitland Avenue - Ulriow B.1778
New York: 129 Larayette St. - Würth 6.0030

Use postpoid cord. Circle No. 241



PUNCH COMPLICATED PATTERNS FAST



With the new improved STRIPPIT 15-A Fabricator, complicated patterns of round and shaped holes can be produced quickly and accurately in sheet material. A high speed punch press that enables you to produce finished pieces directly from drawings, the versatile STRIPPIT 15-A eliminates slow "in-between" tool designing and die making... saves you days or even weeks of valuable time.

The STRIPPIT 15A features a unique multiple-stop gauging system for positioning work to exact layout specifications. Punches and diss... within easy reach in built-in file drawers...can be switched from one size to another in less than 20 seconds. Designed especially for prototype and short production runs, the STRIPPIT 15A is easily converted to a high speed production punching unit with the STRIPPIT Duplicator.

The STRIPPIT 15-A:

- PUNCHES any round or shaped hole up to 3½" diameter. Maximum material thickness is ¼".
- NOTCHES 90° corners—rectangular, radii, vee and special shape edge notches—up to ¼" capacity in mild steel.
- NIBBLES straight line or contour shearing up to 38" diameter circle, at 165 strokes a minute, 1/4" mild steel.

Send now for 15-A catalog. Free demonstration can be arranged right in your plant.


WALES STRIPPITING

204 Buell Road . Akron, New York

In Canada: Strippit Tool & Machine Company, Brampton, Ontario
In Continental Europe: Raskin, S. A., Lausanne, Switzerland In the British Isles: E. H. Jones (Machine Teols) Ltd., Hove, Sussex, England

Use postpaid card. Circle No. 239





You asked for it and Lees-Bradner has built it . . . after years of design planning and months of building and testing.

LEES-BRADNER

outlang and testing.

This rugged hobbing machine — known as the 12-HD 12" x 20" — will produce gears up to 8, 9, 10, even 12 inches in diameter at mass production speeds. A revolutionary innovation is the new variable speed A.C. drive, using stock — not special — stock A.C. motors!

Now truck, tractor and earthmoving equipment manufacturers can generate heavy-duty gears as efficiently as smaller ones have been made.

Write Lees-Bradner for all the details — or get in touch with our representative in your area.

SPECIFICATIONS

Rated capacity in steel 4 D.P.
Max. diameter capacity32" (with 5" hab)
Max. helix angle45"
Taper in work spindle nese 16 B & S
Floor space

IMPROVING GEARS FOR 50 YEARS

The USES-BRADNER Company

CLEVELAND 11, OHIO, U.S.A.


THE NEW 12" x 20" 12-HD

Designed to produce large, heavy-duty gears at highproduction speeds.

Can be equipped with lead differential, electric hob shifter and hydraulic controls.



U.S. Slide Feed produces at 620 strokes per minute ...tolerances to ±.001"



U.S. Slide Feed No. 22A, adapted for high speed production and U.S. Multi-Rell® Cradle No. ACC-19C at Triangle Tool Company.

Triangle Tool Company, Union, N. J., using U.S. Slide Feeds, runs continuous production at the rate of 620 strokes per minute. Coil stock, 1010 dead soft, .010" thick x 2" wide is fed into a 9-station all carbide progressive die. Feed length is 1.125". Tolerance is held to ± .001" without the aid of pilots. ■ Of all feeds tried by Triangle Tool Company, only the U.S. No. 22A Slide Feed proved capable of maintaining the required tolerance at this high speed. ■ The Feeds used are a variation of standard No. 22A U.S. Slide Feeds modified for high speed operation.

Bulletin #85-60-B describing U. S. Press Room Equipment will be sent upon request.



U.S. TOOL COMPANY, INC.


AMPERE (East Oranga) NEW JERSEY

II S. Madis-Stides® + II S. Madis-Millars® + II S. Automotic Press Boom Equipment + II S. Bie Sets and Accessories

Use postpaid card. Circle No. 242

MACHINE and TOOL BLUE BOOK





This low, complete price includes 26' numerically controlled drill with complete electrics, power feed, back gear, and Infispeed variable speed drive; 10" x 20" tape controlled, hydraulically operated positioning table; Cincinnati Acramatic control con-

sole with tape reader; complete installation and demonstration service.


This machine is readily adaptable for optional tape control of automatic feed cycle; depth selection from eix pre-set stops; tool change indicator.

CINCINNATI LATHE AND TOOL CO.


CINCINNATI B. OHIO


RYDRASHIFT Lathes / CINCINNATI Drilling Machines / SPIROPOINT Drill Sharpone CINTIMATIC Removicely Controlled Lathon and Drills





Delta Lathe Dealer and get a FREE CATALOG: Rockwell Manufacturing Company, Power Tool Division, 610D N. Lexington Avenue, Pittsburgh 8, Pa.





WHATEVER SHAPE YOU NEED IN A PUNCH OR DIE BUTTON. Richard Brothers can supply it

More than 10,000 sizes and types of standard punches and die buttons are immediately available from Richard Brothers' existing stock.

But that's just the beginning. Richard Brothers will also make any special-shaped punch or die button to your exact specifications . . . will fabricate them from special alloys, if you wish. All R-B punches and die buttons . . . standard and special . . . incorporate standardized R-B features which offer complete interchangeability.

Do business with the leader. Specify R-B punches and related metal-piercing tools. It pays . . . many ways.







INTERCHANGEABILITY



RELIABILITY



COMPLETE STOCK

RICHARD BROTHERS PUNCH DIVISION

ALLIED PRODUCTS CORPORATION DEFT. CS . 26800 CAPITOL AVENUE . DETROIT 10, MICHIGAN

Use postpaid card. Circle No. 245



PEMEMBER?



The blacksmith is one of the oldest metal fabricators. He served a long apprenticeship to learn how to accurately produce metal parts of almost any shape manually, employing little or no power equipment. Remember?

Metal fabricators frequently think along these lines and depend on skill and dexterity to produce accurate parts.

The "Wiedemann Method" employs mechanical work positioning equipment so simply that inexperienced menay become skilled operators in a very short period of time, often in a few days. Efficient, self trained Wiedemann operators and turret punch presses have replaced this slow costly hand work of metal fabricators.


Let Wiedemann Machine Company solve your hole positioning and punching problems. Learn how, merely by installing the "Wiedemann Method" you can realize 60% to 90% savings in your piercing operation. Drop us a line.



From the versatile 130 ton R-13 down to the hand operated R-2, there's a Wiedemann for your short run piercing requirements.

WIEDEMANN

WIEDEMANN MACHINE COMPANY Dept. MT4 Gulph Road • King of Prussle, Po.



HI-SPEED INLINE with integral pilet, 2 or 3-way, NO or NC, % to 11/4 in. NPT. Short poppet travel in Valvair's HI-SPEED INLINE provides maximum flow almost instantaneously. This shortens machine cycle time . . . lessens brake and clutch slip . . . provides more accurate cuts on high speed cut-offs . . . decreases set-up time . . . minimizes drift, for safer operation.

For increased production . . . lower costs . . . greater safety . . . specify Valvair HI-SPEED INLINE valves.

Write for free Bulletin HIN. Address: Bellows-Valvair, Akron 9, Ohio, Dept. MTB-461




Bellows-Valvair

DIVISION OF INTERNATIONAL BASIC ECONOMY CORPORATION (IBEC)

8140

Use postpaid card. Circle No. 247

49



Answer: Just one P.U.P.S.—and that's real economy!

Lower initial cost
Shelf stocking, no costly replacement delays


Cut inventory costs and wasted space by as much as 87%

Replaces 22 or more custom punch point sizes

Complete interchangeability, A.S.T.M.E. standard

Provides common set of punch standards to avoid confusion. Your Dayton Perforators Distributor has the inside moneysaving P.U.P.S. story. Contact him today, or write to:





The "Hidden Strengths and Values" of Minster O.B.I. presses...points of superiority that only Minster offers the O.B.I. user... are outlined in this new Bulletin 15. It will help you make comparisons when next you buy an O.B.I. May we send you a copy? Write or call...

The Minster Machine Company, Minster, Ohio



for speed and accuracy in production it pays to use UNIVERSAL DRILL BUSHINGS



UNIVERSAL ENGINEERING COMPANY . FRANKENMUTH 10, MICH.

214

JELNEWSLETTER-

the man who need a new machine fool is already paying for it

Actual memo from Production Control to Plant Manager in a large metalworking plant.

RE: NUMERICAL POSITIONING DRILLS

This memorandum is issued to call to your attention that not having a 2nd J & L Positioning Drill in Department 24 is costing us money. We are either sending overloads to the other divisions or running them on slower machines.

Last week, due to overloads on the Positioning Drill, it was necessary to run some rush work on another machine tool. Each order cost us extra time allowances. Two of the worst jobs were as follows:

- Part #12036, Operation #2. We had to give additional time of 1.80 minutes per piece. This is a 56% increase per piece and cost 5.3 extra hours for the entire lot.
- Part #12461, Operation #2. We had to give additional time of 2.00 minutes per piece. This is a 40% increase per piece and cost 2.5 extra hours for the entire lot.

I would also like to remind you that we have quoted on several rush subcontract jobs to be run on this machine. If overloads or a breakdown should occur, we would incur substantial losses from running them on slower machines. For example, on subcontract job \$XX-2912, we had 30 pieces to run on the Positioning Drill. The cycle time is 23.00 minutes. Because of the Positioning Drill overloads when we quoted on the job, we also computed the time to run on a radial drill. The cycle time came out the same but we would have to spend \$250 for the jig. As the jig cost was so much for a small lot, we also computed the cost on a Post Drill. Here our cost increased 23% per piece because of the additional cycle time and also because the labor grade was one higher.

There is also the possibility of incurring substantial increase in cost if this one machine is down or becomes overloaded because of having to run production orders on jig borers and boring machines. This is caused by lack of jigs on many new parts. As you know, we do not have to "jig up" like we used to because of having the Postioning Drill. For example:

- \$75513, Main Valve Bodies: Routed to the Positioning Drill and we saved about \$650 in jigs.
- 2. \$60342, Adapter: We saved about \$450 in jigs.
- \$775589, Lead Screw Bracket: Routed to Positioning Drill and we saved about \$350 in jigs.
- 4. \$700,090, Mounting Plate for Control Unit: We saved about \$250 in jigs.

Please let me know if there is anything I can do to expedite getting a second machine fast.


There's nothing we could add to this "voice of experience" — except, maybe, to tell you more about our positioning table. Write for further details.



... DOES TOUGH JOBS Dependably, Profitably

LEVELAND

Inclinable PRESSES WELDED-FRAME Open Back **COST-CUTTING**



Dies last longer with less downtime for die maintenance due to Cleveland's large box-type slide that results in greater production accuracy.

75 to 200-ton capacity, built for safer, more efficient operation with all gears and drive mechanism guarded.

Ruggedly built for many different press operations, material can be fed in from either side or from front to back.

Three different positions-vertical, 15° and 30°-to accommodate various types of dies and at the same time make use of gravity feed and discharge in automated production lines, or in operations using a single press.

You get better stampings for less with a CLEVELAND Press-the new welded-frame cost-cutting Cleveland OBI Press.

At the Middletown Manufacturing Co. in Middletown, Ky., this new welded-frame Cleveland OBI Press is blanking and piercing %
thick steel for reclining chair fixture parte and blanks for pressor cases. This Model 13-I has 150 ton capacity, 6 strake of slide, 4" slide adjustment, 30 x 45" bed area and operates at 35 strokes per minute.

Write Today for Cleveland's OBI Press Catalog OBI 3-60





Fabricating Tools Punching Tools & Dies

E. 40th and St. Clair Avenue, Cleveland 14, Ohio

AT'S A FACT !


You can tap 1/2" holes

with a light drill press and Supreme's

VersaTAPPER



Shaft of Model 6100 is held in drill press chuck. No. 6200 (above) has Tapered spi



VersaTAPPER is a compact precision-made tapping unit. Fits any drill press . . . features half-inch capacity range plus 4-time increase in torque. Easy to install. Simple and quick to r



Supreme Accutap Chuck is VersaTAPPER. Capacity 0-1/2"

VersaTAPPER... operates easily in any material ... with widest capacity range ... yet costs far less

The new VersaTAPPER has scored an instant success with production people everywhere. It has more versatility than other tapping devices. It has the widest capacity range-from 0 to 1/2', but depending on application, use of taps smaller than No. 10 is limited. It develops more power - makes the tapping of 1/2 "-13 holes a simpler matter, even with COMPLETE

light duty drill presses. VersaTAPPER is

simple to use-can be successfully operated by anyone in your shop. All of these features at the remarkably low price of \$63.00 complete marks VersaTAPPER as a product you must see at the first opportunity. It's available

at your local Supreme Chuck distributor. Call him soon.



CHICAGO 16. ILLINOIS

You get more from power tools with **Top Quality** Supreme Accessories



Supreme Brand Chucks

Noted for unmatched quality. The widest range of sizes and types...one for every machine in your shop. Exclusive Su-preme hardening means greater



Supreme Versamatic

Reversible speed reducer for portable drills. Fits all makes -permits their use for power screw driving, nut running and heavy duty drilling. 7 to 1 re-duction means high torque duction means hi



Supreme **Push-Pull Tapper**

Like the Versamatic, but made Like the Versanatic, out made for the single purpose of tap-ping with portable drills. Re-verses instantly for tap removal. Handles taps up to 5/16" diam-eter. Top quality. Simple to

SUPREME PRODUCTS ARE IN STOCK IN YOUR CITY. CALL YOUR DISTRIBUTOR

PRECISION ASE PRODUCTS

this coupon can save you money -- mail it today



COLUMBUS DIE-TOOL & MACHINE CO. P.O. BOX 750 • COLUMBUS, OHIO

Please send Brochure listing all your facilities, equipment and capacities.

NAME

COMPANY_

ADDRESS

CITY_

ZONE STATE

Precision made to your specifications — tools, jigs, fixtures, special machines and machine components. Hundreds of companies in every industry use our services. The high quality of our work, our fast delivery, our reasonable prices have earned us a high degree of acceptance. We can handle any size job. The Brochure you will receive by mailing in the coupon contains a comprehensive listing of our personnel, precision machine tools, facilities and capacity.

Serving all Industries anywhere in the U.S.A. since 1906,





P. O. BOX 750 . COLUMBUS, OHIO

Use postpoid card. Circle No. 253

SAVE UP TO \$350

on South Bend toolroom lathes with collets





Take advantage of this unmatched offer ... purchase any South Bend Precision Toolroom Lathe before May 1st and you will receive a set of South Bend Collets without extra charge. These are precision, milled thread, heat treated collets for round work.

Don't wait . . . mail the coupon now!

YOU SAVE -

LATHE	PRICES START AT	COLLET CAPACITY, MAX.	COLLETS IN SET	SIZE RANGE by 64ths	of COLLE
16" Toolroom	\$3230	11/6"	61	1/4" to 1"	\$350.75
14½" Toolroom	2760	136"	61	1/6" to 1"	350.75
13" Toolroom	2358	11/4"	61	1/4" to 1"	350.75
10" Toolroom	1783	136"	61	1/4" to 1"	350.75
10" Taoiroom	1590	13/4"	41	1/6" to 11/6"	196.80
10K Toolroom	815	%"	37	1/4" to 3/4"	173.90
9" Toolroom	725	1/4"	29	1/4" to 1/2"	130.50

eriess f.e.b. South Bend, Ind., Issu electricals

Special Offer Expires April 30, 1961

SOUTH BEND LATHE


A Subsidiary of American Steel Foundries

BUILDERS OF LATHES - MILLING MACHINES - SHAPERS DRILL PRESSES - PEDESTAL GRINDERS



SOUTH BEND LA	ATHE, INC., South Bo	nd 22, Indiana
Send us complete and Time Payment		i Toolroom Lathe affer
Nome		Title
Company		

WALKER CERAMAX



TURNING


Walker, for the first time in machine tool history, offers safe magnetic holding for lathes. Ceramic magnets in Walker Rotary CERAMAX chucks are not subject to electrical power failure and have three times greater coercive force than ordinary Alnico magnets. With uniform holding power over the entire face of the chuck, safe, accurate turning, facing or trepanning is accomplished in a single set-up.

For dependable, trouble free operation specify Walker CERAMAX Chucks.

GRINDING

Walker CERAMAX chucks provide all the holding power needed for standard grinding operations and with fine pole divisions are ideal for thin, small work as well as large, heavy pieces. All-steel top plate minimizes redressing to reduce non-productive machine time. Ceramic magnets retain magnetism permanently, eliminate constant recharging.

O.S. Walker Co., Inc.
ROCKDALE ST. - WORCESTER 6, MASS.
Original Designers and Builders of Magnetic Chucks



CLIP AND FILE

REAMING TIPS YOU CAN USE

SECONDARY CHAMFER



Grinding a secondary chamfer angle as illustrated (A) is aften recommended. It is useful in applications where a fine finish or clase tolerance is required. (8) is the regular chamfer.

KEEP IT SHARP



A chucking reamer is an end cutting tool. The cutting edges are produced by the chamfers at the ends of the lands. (A) To obtain maximum performance, the chamfers and clearance relief should be reground before excessive wear develops. Each chamfer should be ground exactly even or the tool may cut aversize.

OVERCOMING CHATTER

To end chatter in reaming, try Chicago-Latrobe's Duo-Spiral Reamer. The alternate left and right hand helixes tend to dampen cutting vibration; eliminate hogging; produce more accurate, better finished holes.

GOT A PROBLEM?


Arrange a consultation with a Chicago-Latrobe Sales or Service Engineer. His experience in hundreds of plants can lead to a auck solution of your problem.



CHICAGO-LATROBE

418 West Ontario Street

Chicago 10, Illinois




To self center cylindrical, square or hex stock for drilling

V for victory over a previously ticklish drilling job . . . new hardened ground Acme Industrial V bushing liners clamp over cylindrical (round bars, tubing, etc.), square or hex stocks . . . instantly, automatically locate dead center. Layout, jig boring eliminated . . . just center punch, drill and ream hole! Acting as a liner for removable bushings, Acme's "V" assures precision centered drilling always.

Available in 2 sets of 3 V bushing liners to accommodate slip bushings with O.D.'s of 3/16", 5/16" and 1/2" in a range from No. 80 drill to 11/32" in A.S.A. or Acme standard sizes. Acme V bushing liners . . . a must for every tool box.

* patent applied for

ACME IND	USTRIAL COMPANY Laflin Street/Chicago 7, Illinois
	Send me complete information on new V bushing liners Send me the complete Acme Industrial bushings catalog
Name	
Firm	
Address	
City	ZoneState



SEVEN OPERATIONS—SAME MACHINE

SAVES ON MAINTENANCE AND PRODUCTION

A BUFFALO Iron Worker can be the most useful, productive and cost-saving machine in your shop.

Without changing tools, it will do a variety of jobs — several at the same time.

It's compact, ruggedly-built, requires practically

no maintenance and is available in your choice of sizes and models.

Worth investigating, a BUFFALO U. I. W. pays its own way and returns dividends. Maybe you can't afford to be without one. Write for Bulletin 322 or . . . better still . . . call in your nearest BUFFALO representative.



MACHINE TOOL DIVISION BUFFALO FORGE COMPANY

number & Forms Co. 184 Elithaner Out.



'Buffalo' Air Mandling Equipment to move, heat, cool, dehumidit and class air and other asset.



Buffeld Machine Tools to o punch, shear, bend; slit, no and cape for production or plant maintenance.



'Buffalo' Contrifugal Pumpa to handle most liquids and slurries under a variety



Squiar Machinery to process super cane, coffee and rice. Special processing machinery for chamicals



Use postpaid card. Circle No. 259

SIX STYLES, THIRTY-THREE SIZES

LINGTHS FROM 4 TO 24 INCHES

J. H. WILLIAMS & CO.

MEETINGS AN

April 11-13, Annual Meeting, American Society of Lubrication Engineers, Bellevue-Stratford Hotel, Philadelphia, Pa., Information: ASLE, 5 N. Wabash Ave., Chicago 2, Illinois.

April 18-20 Welding Show, American Welding Society, New York Coliseum, New York, N.Y. Information: AWS, 33 W. 39th St., New York 18, New York.

April 24-26 Powder Metallurgy Show, Metal Powder Industries Federation, Hotel Sheraton-Cleveland, Cleveland, O. Information: MPIF, 60 E. 42nd St., N.Y. 17, N.Y.

May 1-2 Annual Meeting, American



Here is the same high quality design and manufacture as the famous Williams' Alloy Wrenches with the following industrial features. New, rust-resistant black oxide finish, chemically applied, lowers cost . . . will not chip or wear off. High lustre head and face the common features are important where wrench replacement rate is high. Made from strong, tough steel, carefully heat-treated. See your Williams Distributor.

33 PATTERNS-554 STYLES OPENINGS FROM 3/16" TO 7-5/8"

J. H. WILLIAMS . CO.

410 VULCAN ST., BUFFALO 7, M. V.



Use postpaid card. Circle No. 260



Made from tough, carefully selected steel, specially heat-treated to
increase strength and reduce liabiity of springing. Screws threaded
for rapid adjustment . . . thru-hardened for extra life. Swivels
designed for permanent retention on screws. Heavy Service

designed for permanent retention on screws. Heavy Service in 11 sizes up to 12½" cap, General Service in 9 sizes up to 18" cap. Deep Throat in 7 sizes up to 12" cap, Spatter-Resisting in 7 sizes up to 12" cap, Tool-Makers in 4 sizes up to 4½" cap. Also Machinists' Clamps, 4 sizes up to 4½" cap.

FIVE STYLES IN 38 SIZES SEE YOUR WILLIAMS DISTRIBUTOR

J. H. WILLIAMS . CO.

410 VULCAN ST., BUFFALO 7, N. V.



Use postpaid card, Circle No. 261

MACHINE and TOOL BLUE BOOK

ONVENTIONS

Zinc Institute, Drake Hotel, Chicago, Ill. Information: AZI, Inc., 60 E. 42nd St., N.Y. 17, N.Y.

May 8-12 Castings Show, American Foundrymen's Society, Brooks Hall, San Francisco, Calif. Information: AFS, Golf & Wolf Rds., Des Plaines, Illinois.


May 22-25 Design Engineering Show, Cobo Hall, Detroit, Mich. Information: Clapp & Poliak, Inc., 341 Madison Ave., N.Y. 17, N.Y.


May 22-26 Tool Exposition, American Society of Tool & Manufacturing Engineers, New York Coliseum, N.Y., N.Y. Information: ASTME, 10700 Puritan Ave., Detroit 38, Michigan.



Use postpaid card. Circle No. 263








Recent improvements in design and material make Williams Alloy and Carbon Steel Hooks the strongest, asfest to specify. Each is beat-treated for maximum toughness and high impact resistance. All are proof-tested to military standards to 50% beyond safe working loads. Available in eye and shank styles in regular and safety patternt. Safety latches feature non-corrosive snap springs with positive, safety action. Alloy steel capacities up to 70 tons. . . . carbon steel capacities up to 60 tons. Order from your Williams Distributor.

SIXTEEN STOCK SIZES
CAPACITIES UP TO 70 TONS
J. H. WILLIAMS & CO.

WILLIAMS

Use postpoid card. Circle No. 264



what kind of chips are these?

This photo shows chips — some as long as 6" — produced by

FULMER HONING MACHINES

. . . and prove the speed of the process that saves up to 96% in time alone over conventional bore-finishing processes!

In actual production, Fulmer Honing did a job in 40 minutes that formerly required 16 hours by grinding. Fulmer Honing is amazingly accurate as well as fast. It produces round and straight bores with maximum accuracy . . . to plus-or-minus .0001 limits.

LET US ESTIMATE . . . send prints or work-piece sample for free time and honing costs estimate. OR . . .

DO-IT-YOURSELF . . . write on company letterhead for FREE Honing Computer that figures honing time on any diameter bore, length and material, and gives other valuable information on stones, speeds, etc.

Write Today: C. Allen Fulmer Co., Dept. B, 107 E. Fourth St., Cincinnati 2, Ohio.



collets, pushers, details

accuracy is our



Allen's Burn Style

TAPER LOCK PUSHERS

When Specified

Automatic Adjustment Positive Feed Minimum Scratch SPECIAL DETAILS TO PRINT

Let Us Quote Your Details

We Will Duplicate COLLETS, COLLET TUBES,
PUSHERS and PUSHER TUBES



ALLEN COLLET MFG. CO., INC.

17720 CLARANN AVE. . MELVINDALE, MICHIGAN

Use postpaid card. Circle No. 266


to do small grinding jobs to MICRO-PRECISION FAST...

you need the SANFORD Model SG SURFACE GRINDER

This unrivalled small parts grinder can be depended upon for micro accuracy. It's easy to use too . . . every hand wheel and operating switch is at your finger tips.

Designed and built by engineers and tool makers of rare foresight for tool, die and gage work, it has been constantly preferred after these many years of proven worth.

Write for fully illustrated literature, replacement parts and special attachments data with price list.



PARTIAL SPECIFICATIONS-

Chuck Surface-3"x5" or 4"x6". Table travel-8", traverse 4". Vertical head movement-6". Work area under 4" wheel-6". with chuck-4". Standard grinding wheel-4"x3/4"x1/4". Spindle speed-approx. 5500 RPM. Motor, 1/6 HP, single or 3 ph., dynamically balanced.

Dimensions-23"x30"x27" high.

Net wt. approx. 160 lbs.

Representatives in major industrial areas

MANUFACTURING CORP. 1026 Commerce Ave., Union, N. J.

Use postpaid card. Circle No. 267

MAJOR AIRCRAFT MANUFACTURER MAKES...

Fully Automatic Savings with NELCO TOOLS on Tape Controlled Miller!

OPERATION #1 PROFILE MILLING AROUND WING SECTION

MATERIAL: Aluminum Alloy, Tough & Abrasive.

NELCO Carbide Tipped End Mill. Negative Helix.

FEED: 20" per minute. WIDTH OF CUT: 1½".

PRODUCTION: Nelco End Mill conformed to aircraft tolerances and to rugged automated production schedule.

There are 121 Nelco End Mills specially engineered to mill Aluminum.



Machine: Giddings & Lewis, 2 spindle vertical, 100 H.P. each spindle, tape controlled.

OPERATION #2 FACE MILLING WING SECTION

MATERIAL: Aluminum Alloy, Tough and Abrasive. CUTTER USED: Standard 6" diameter Nelco Face Mill modified with 30° chamfer. SPEED: 3600 R.P.M., 5400 S.F.M. FEED: 80" per minute. WIDTH OF CUT: 6" DEPTH OF CUT: ¼ to ¾ inch. PRODUCTION: 2 cubic feet of metal removed in 20 minutes. 6 pieces per grind—12 cubic feet of metal removed per grind.



Again, NELCO Carbide Tipped Tools prove their economy and dependability. NELCO manufactures the most complete line of Carbide Cutting Tools engineered to mill ALUMINUM. They are available through your Local Distributor.

For that EXTRA Edge in Production!

NELCO

NELCO TOOL CO., INC.
Subsidiary of: Cutting Tool Division
Brown & Sharpe Mfg., Co.
Providence 1, Rhode Island

Send for the NELCO Catalog today!



Another P.D.Q. FIRST!

NEW ADJUSTABLE RAKE

Manchester...

Cut-off Tool



Re-setting without losing center location. Eliminates grinding for proper rake angle. Available for all makes of Turret Lathes, Engine Lathes, Automatics and Cut-off Machines.

This new "Manchester" tool can save special tooling costs and time costs in special tool grinding. The tool is infinitely adjustable to any setting from 0° rake to positive 16°. Cutting point is always at center height regardless of rake angle to insure correct cutting action. Complete facts are available, write for literature.

ASTE SHOW ... Booth No. 3063



PORTAGE Double-Quick, Inc.

1037 SWEITZER AVENUE . AKRON 11, OHIO

Use postpaid card. Circle No. 269




ONE machine-ONE operator-ONE pass

Let's face facts—costs are high and will go higher. You can, however, REDUCE flat finishing costs with a Hammond Flat Finisher. Grinding, deburring, and finishing of flat surfaces of plates, printed circuits, bars, stampings, extrusions, etc., can be done uniformly on a high production basis with ONE machine ... ONE operator ... ONE pass.

Hammond Flat Finishers have the latest features: automatic belt tracking and oscillation, automatic air tensioning for abrasive belts and conveyor belt, variable speed conveyor, ammeter on each head, and other features which contribute to maximum production at lowest possible cost.





1614 DOUGLAS AVE. • KALAMAZOO, MICHIGAN
See us at the ASTME Show, May 22-26, New York Collegum.

Use postpaid card, Circle No. 270

/EL

High-speed tables . . . 10 to 70 FPM cross feed .005" to .250" with rapid traverse...hardened and ground lead screws . . . chrome plated table ways (at extra cost) . . . direct motor driven spindles.

No. 10-H

6" x 18" working surface, 161/2" height under a 7" wheel. Jobs set up quickly for tool room or production grinding, 1 HP 3600 RPM spindle drives 7" grinding wheel.

No. 17-H

10" x 16" working surface for die block work requiring wide cross feed, or general tool room and production work, 2 HP 1750 RPM spindle drives 12" grinding wheel for heavy stock removal.

now offers 2 HYDRAULIC SURFACE GRINDERS

6" x 18" and 10" x 16"

> \$ 3285 and \$3580 complete



Use postpaid card. Circle No. 271

MICHIGAN

PRECISION

GRINDERS

SEND TODAY for details on 10-H and 17-H — and on Covel's complete line.

BULLETIN BB41




NEW Automatic Loading and Feeding for Grieder Tube Cut-Off Machines ... 4500 to 6500 cut-offs per hour!

The Grieder automatic loader and feeder holds up to 15,000 pounds of tubing and will automatically feed the entire load through a Grieder Tube Cut-Off Machine without attention from the operator. Standard stock cradle handles 22' lengths. Shorter or longer capacities are available. Note! This equipment will also feed round stock to other types of machinery.

 GriederTubeCut-OffMachines. cut tubing of any shape to any length faster than any other machine.

 Length tolerance plus or minus .002 " on light wall tubing, .003 " on heavier. Precision clamping dies prevent tube distortion and provide clean, quality cuts. Tube does not rotate.

Write for literature. Tell us sizes of steel, copper, brass, aluminum or alloy tubes to be cut and production requirements.



GRIEDER INDUSTRIES, INC. P. O. Box 169 · Bowling Green, Ohio

> Please send bulletin describing Grieder Tube Cut-Off Machines.

NAME

COMPANY___

CITY____ZONE

STATE

Frieder

TUBE CUT-OFF MACHINES

HAVING BORE SIZING **PROBLEMS**

WITH

SIZE

ROUNDNESS

STRAIGHTNESS

TOLERANCE

One piece . Job lot . or Production run ... Sunnen Honing levels out all hole errors from previous operations with a minimum of stock removal. Corrects out-of-round, chatter, waviness, bow, taper, barrel, bellmouth. Guarantees bore

accuracy to .0001" with controlled surface finish

From stock removal through finish sizing — from deburring through micro-fitting, Sunnen Honing is the most economical solution for internal work. No fixtures or time consuming set-up required; no

Range .100" through 2.625" with stock tooling -

SURFACE FINISH !



AST STOCK REMOVAL



GEOMETRIC ACCURACY




PRECISION SIZING







CONTROLLED FINISH



chucking pressure to distort the hole.

as fine as desired.

the advantages of this fast stock removal process. Ask us for a copy of Bulletin SP-11 or an equipment demonstration in your shop. No obligation is involved.



7922 Manchester Ave. - St. Louis 17, Mo. Canadian Factory: Chatham, Ontario

PRECISION HONING MACHINE Average cost

with tooling about \$1000




8880

U.S.S. KASKASKIA is typical of many ships which have had extensive bulkhead and other repairs at Moore Dry Dock Company.

Official U. S. Navy Photograph



Moore Dry Dock SPEEDS MARINE REPAIRS



Fluted bulkhead plate being formed by Steelweld bending press in plate shop of Moore Dry Dock Company for bulkhead

renewal job on U.S.S. "KASKASKIA" (A027) Size of plate: length 26", width 6", thickness 32"

Tong a leading West Coast ship builder and marine repairs concern, the Moore Dry Dock Company, Oakland, California, has found a large Steelweld Bending Press to be a great asset in speeding the forming of heavy plate.

Ship repair, which constitutes an important part of the company's business, often requires replacement of large sections, such as bulkheads. This necessitates the forming of plates to various shapes to accurately replace those removed. Because of the power of their Steelweld and the ease of making adjustments, this work is carried on efficiently and satisfactorily.

The entire line of Steelwelds has an enviable reputation for continuous high-production performance. We urge you to get the facts on their many outstanding features.

THE CLEVELAND CRANE & ENGINEERING CO. 5262 East 281 Street, Wickliffe, O.



sely illemeted. 3202 East 261 Street, Wickliffe,

STEELWELD BENDING PRESSES

BRAKING - FORMING - BLANKING - DRAWING - CORRUGATING - PUNCHING

Haria 612 SURFACE GRINDER

with

NEW...EXCLUSIVE

AUTOMATIC FORCED LUBRICATION

- · Continuous flow, recirculating system
- Washes away damaging grinding dust
- Triples life of ways
- Preserves original accuracy
- e Promotes easy table operation
- Reduces maintenanceoils complete machine

... and many other features included as standard equipment, all at a surprisingly low price!

WRITE FOR HARIG 612 BROCHURE







Easily grinds various shaped perforators to ± .0001 accuracy.

Also, attachment to convert Grind-All

into precision Radius Dresser.



5763 W. HOWARD ST. . CHICAGO 48, ILL.

VISIT HARIG BOOTH 1514 (A.S.T.E. SHOW)

For THROWAWAY-INSERTS and TOOLS . . . get to know

MISS VI KING ...

YOUR ONE SOURCE SUPPLIER



ONE FOR ALL . . . ALL FROM ONE

The wise way to buy Carbide, High Speed Steel, Cast Alloy and Ceramic Throwaway-Inserts, and Tool Holders, Milling Cutters, and Boring Bars is to buy from one knowledgeable source. Viking tool engineers know the applications of not merely one of these items, but of all of them as they so vitally relate to each other in order to obtain maximum cutting performance with minimum loss in time and materials. Because Viking engineers are pioneers in the throwaway-insert and tool Industry, they are uniquely able to recommend the right tool and/or insert for your particular need. They are at your service.

ASK FOR AN INTRODUCTION

Negative and Positive rake inserts.



25 Nichols Road, Shelton, Connecticut

ARE YOU PROPERLY GEARED FOR

MINIATURIZATION?

DRILL MICRO-HOLES

DOWN TO .0016" with SPEED & ACCURACY

EVIN MICRO-DRILLING MACHINE

Designed for the most precise drilling of small holes. evolves and thus the maximum straightness and and the smallest drills may be safely used. The drilling spindle, as well as the head stock spindle, concentricity are assured. The feed is so arranged that it does not depend on the operator's sense of feel

For full Drilling details of commercial drill

Smallest

Lathes Machine and send for Instrument



Louis Levin & Son, Inc., 3573 Hayden Ave., Culver City, Calif.

GROB SPELLS THE DIFFERENCE IN BAND SAW MACHINES

The new GROB 24" universal band saw has all the famous GROB features:

Quality . Efficiency . Durability . Strength Utility . Low Maintenance . Reasonable Cost



- Speeds infinite from 35-12000 FPM covers both cold and hot sawing
- · Variable drive 3-speed transmission with precision rolled gears and splines transmits 15 HP
- Hydraulic table feed

See the difference demonstrated in our dealers' showrooms

Write GROB INC. for complete specifications

GROB also manufactures a complete line of:



BUTT WELDERS FILING MACHINES GEAR ROLLING MACHINES

GRAFTON, WISCONSIN

with men who know cutting tools...it's MORSE everytime



TRY MORSE...BUY MORSE
SEE YOUR NEARBY MORSE DISTRIBUTOR

MORSE

NEW BEDFORD, MASSACHUSETTS



Islan of VAN NORMAN INDUSTRIES, INC

Warehouses in: NEW YORK . CHICAGO . DETROIT . DALLAS

SAN FRANCISCO

Use postpaid card. Circle No. 280

April, 1961

77

BREAK COST-BARRIERS

with timely

BRIGHTBOY

Rubber Cushioned Abrasives

Multi-use Brightboy extensively broadens the scope of abrasive applications, replacing various older, costlier methods. Now, more than ever, you probably can utilize Brightboy's economical new concept for working:

ALL METALS . WOOD . GLASS
LAMINATED MATERIALS . SOME PLASTICS

Brightboy's simultaneous rubber-andabrasive working action frequently reduces

> BURRING • CLEANING FINISHING • POLISHING

to one operation

WIDE RANGE OF READILY AVAILABLE

STOCK TEXTURES FOR IMMEDIATE DELIVERY

The only complete, comprehensive line of soft rubber bonded abrasives, available in Silicon Carbide and Aluminum Oxide stock textures — extra fine to extra coarse — in soft, semi-firm, firm and tough rubber binders. Revolutionary Brightboy is saving money for countless users now, in machine, manual and automation operations.



WRITE NOW for BRIGHTBOY'S CATALOG-MANUAL covering:



- . METHODS & APPLICATIONS
- . MACHINE SPEEDS
- JOB-MATCHED, STOCK WHEELS, STICKS, RODS, BLOCKS & POINTS
- . WHEEL SIZES COMPLETE RANGE



BRIGHTBOY INDUSTRIAL DIVISION WELDON ROBERTS RUBBER CO.

95 North 13th Street Newark 7, N.J.
America's Pioneer Manufacturer of Rubber-Bonded Abrasives

NEW

HAMILTON VARIMATIC® PRECISION DRILLING MACHINE

SUPER SENSITIVE CAPACITY TO 5/16"

Brings a new dimension to the production drilling of small precision holes. Drills to the center of a 10" circle. Head swings radially on column and locks at any position. 6" vertical adjustment of head on column. 2½" feed of spindle. Speeds from 840 to 9300 R.P.M. infinitely variable in two ranges.

If you would like the complete Varimatic story . . . with pictures, and a sectional engineering drawing . . write for our FREE Bulletin No. V/2961.



use it with confidence!

THE HAMILTON TOOL COMPANY


826 SOUTH NINTH STREET

Use postpaid card. Circle No. 282


HAMILTON, OHIO

FOOL STEEL SERVICE NEW

inventory costs cuts



Using too many grades of tool steel can lead to over-stocking —



that's when you need the benefits of Crucible's new Tool Steel Service!







A Crucible Service Engineer can prove that buying a few basic grades -

fewer pounds in stock ...

in quantity - enables you to carry

gives you a lower price per pound (you eliminate small quantity "extras"),

For the full story

cost-reducing

service,

call in a




All through standardizing on a few

and with fewer grades to identify, you reduce the possibility of "mixed" steel.

Service Engineer

Crucible



CRUCIBLE STEEL COMPANY OF AMERICA

Branch Offices and Warehouses: Atlanta • Battimore • Boston • Buffalo • Caldwell, N. J. • Charlotte • Chicago • Cincinnati • Cieveland • Columbus • Dallas • Dayton

Branch • Detroit • Erie, P.a. • Crand Rapids • Houston • Indianapolis • Los Angeles • Minnanie • Milwaukee • Minneapolis • New How Fork • Philadelphia

Phttaburgh • Portidand, Ore, Pervidence • Rockford • Salt Lake City • San Francisco • Seattle • Springfield, Mass. • St. Louis • E. Syracuse • Tampa • Toledo • Tulsa CRUCIBLE STEEL OF CANADA, LTD., SOREL, QUEBEC, CANADA




DON'T SACRIFICE PRICE FOR QUALITY

You can have BOTH!

No. 6 60 Ton O.B.I. \$264000

For unmatched production this 60 ton press can be factory equipped with the time proven Econo Air Clutch and Brake complete with controls for the amazingly low additional price of





& TYPES 5-60 TON

. . . see your dealer or write for additional information:

SERVICE MACHINE CO., INC.

MANUFACTURERS OF ROUSSELLE PRESSES 2310 WEST 78th ST., CHICAGO 20, ILL



Precision ball bearing workhead 6B mounted on compound \$lide for setting cutter to correct position when grinding end cutting flutes and radii. Other type workheads available.

THE UNIVERSAL CUTTER GRINDING FIXTURE

Radial Grinding Attachment D combines with Unit 1A for sharpening end mills with square, conical, or ball nose shapes.

> UNIT 1A. Universal Cutter Grinding Fixture fits any universal tool or surface grinder.



UNIT 4A. Radial Grinding Fixture for sharpening fluted end mills with square, conical, or ball-nose mills. The index disc provides for multi-flute cutters.



NEW FINE-ADJUSTMENT SLIDING SWIVEL GIVES SMOOTH, PRECISE INDI-CATOR SETTING. Smooth, positive positioning of finest dial indicator is readily accomplished by the fine-adjustment Sliding Swivel. Final precise position-ing is accurately made by ing is accurately made by slight movement of conven-ient lever "A"



WRITE FOR: SLIDING SWIVEL FOLDER



ROCHELEAU TOOL AND DIE CO. INC.

650 NO. MAIN STREET, LEOMINSTER, MASS.





TO CUT OFF AND FORM TUBING AND BAR STOCK IN A SINGLE OPERATION


Here is a combination that feeds tubing and bar stock — automatically — to a fast, automatic cutting-off machine. Best of all, the pieces being cut off can be formed, grooved, flanged or chamfered at the same time.

There are models that handle tubing, pipe and bar stock from ½" diameter up to solid bar stock of 3" OD and tubing up to 8" OD.

Why not investigate?

WRITE FOR CATALOG

MODERN MACHINE TOOL CO. 2005 Losey St. • Jackson, Michigan



Use postpaid card. Circle No. 286
MACHINE and TOOL BLUE BOOK


DE LUXE SURFACE GRINDER by Boyar-Schultz

A De Luxe Boyar-Schultz Surface Grinder incorporating many new accessories for those who want the ultimate.

FEATURING

- AUTOMATIC OILING SYSTEM. A motorized lubrication system providing continuous flow of lubrication to all bearing surfaces.
- OIL HARDENED AND GROUND tool steel inserts on saddle ways.
- NEW WHEEL GUARD to accommodate an eight inch grinding wheel.
- SLIP RINGS ON HAND WHEELS for vertical feed and cross feed permit the graduated dials to be set at 0 or any other desired graduation.
- NEW HEAVY DUTY BASE with welded structural steel inner frame for maximum rigidity and increased weight. Also available with patented built-in dust collector.

6-12 De Luxe Surface Grinder is available with hand or hydraulic feed.



HIGH SPEED GRINDING ATTACHMENT — for grinding angles and slots too small to permit using standard wheels. Available as additional cost.



Boyar-Schultz Corporation

2008 SOUTH 25th AVENUE

BROADVIEW, ILLINOIS

new POPE

INTERNAL Precision Grinding SPINDLES


used on BROWN & SHARPE BRYANT BULLARD CINCINNATI COVEL

EXCELLO

LANDIS NORTON REID THOMPSON SPRINGFIELD and others

with important new features that add up to





total eccentricity of shaft, measured in the tapered hole, will not exceed 20 millionths (.000020)

Assembled spindles are dynamically balanced with all rotating parts in full assembly to 25 millionths (.000025) amplitude of vibration. This assures low micro-inch surface finishes.

INCREASED PRODUCTION

Pope Spindles have the rigidity and the ability to take heavy cuts and produce uniform parts.

LOWER OPERATING

Increased wheel life because the extra large shaft is rigidly supported by ample size bearings.

Saved operating time — one motor driving pulley serves all spindles in most cases.

Permanent lubrication — Pope system of grease lubrication prolongs bearing life, minimizes maintenance expense, and the spindles run cool.

New concealed axial air flow coolant repelling flinger increases bearing life and reduces maintenance expense.

Ask for Catalog No. 57-A and Bulletin No. WA-10, or send us your specifications on the spindles you require.

No. 128



ENGINEERS, DESIGNS AND BUILDS
PRECISION ANTI-FRICTION BEARING SPINDLES
FOR EVERY PURPOSE

INERY CORPORATION . 261 RIVER STREET . HAVERHILL, MASS.

Established 1920

Use postpaid card. Circle No. 288

MACHINE and TOOL BLUE BOOK

PRODUCTION of ex

the metal cutting band saw picture

Modern industry's metal sawing needs are extremely varied, involving a very broad range of metals and production requirements. Obviously, no single type of metal cutting band saw blade can possibly meet all these cutting requirements on all types of band saw machines. To meet these varied needs, MILFORD makes available three types of band saw blades. The following will clarify the band saw picture for you... and help you select the best and most economical type for your specific cutting operations.

THE MILFORD REZISTOR HIGH SPEED STEEL BAND SAW BLADE—is made from genuine red hardness high speed steel and provides maximum resistance to both heat and abrasion. The ultimate for high-production cut-off sawing, it is the only blade recommended for use with the newer, heavy-duty band saw machines. It can also be used advantageously with some of the lighter duty machines when they are used to saw quantities of hard-to-machine metals.

THE MILFORD INTERBAND SAW BLADE
... is a recent introduction made from
a new type of alloy steel that contains
carbide-forming elements and affords
good wear resistance. Best suited for
use on light-duty band saw machines
where hard-to-machine metals are cut
occasionally, it falls between the carbon steel blade and the genuine high
speed steei blade in both price and
performance.

THE MILFORD FLEXIBLE BACK BAND SAW BLADE . . . is the standard high carbon steel type, ideal for general purpose cut-off, profile and contour sawing of all but the hardest-to-machine materials. It is also the preferred blade for riction sawing and for cutting most non-ferrous metals. On a price-performance basis, this blade is still — within its range of recommended applications — the best choice for general use on conventional types of machines.

BUY FROM YOUR MILFORD DISTRIBUTOR. . . a local businessman uho stocks the tools and equipment you need. You'll SAVE TIME, CUT BUYING COSTS and REDUCE INVENTORIES!





STANDARD EQUIPMENT

Air clutch and brake. J.I.C. controls. Dual air valves. Adjustable gibs. Hard bronze crankshaft bearings. Forced lubrication.

WRITE for information. Also, other O.B.I. presses, straight side and gap frame presses.

- Completely new design in geared and non-geared types incorporates proven construction features.
- Exceptional rigidity insures long die life and close product tolerances.
- Large box-type slide mounted in long gibs holds accurate alignment.
- 125 ton capacity covers wide variety of jobs.
- Big die capacity—bolster area 42" x 29"—shut height 18", or to suit.
- Versatile efficient dependable.

L&J PRESS CORPORATION

1625 STERLING AVE.

Ruggedly
Built for
INCREASED SPEEDS - HEAVIER FEEDS



GUPER POWER
CHUCKS
DEPENDABLE SINCE 1916



RUGGEDLY BUILT

with improved cam (1) and lever (2) action that can take the shock of heavy, tougher jobs.

GREATER GRIP

with longer jaw travel, holds work more rigid, resists opening of jaws by centrifugal force for extra safety.

FLAME-HARDENED WAYS (3)

resist wear, prevent bellmouthing.



ROTATING CYLINDERS

Bore sizes for air: 3" through 16". For hydraulic: 3" through 8" and larger. Speeds up to 3600 R.P.M. American Standard mountings.



SELF-CENTERING and COMPENSATING CHUCKS

3

American Standard or serrated; 2 or 3 jaws; sizes 6 to 18".



Phone or Write Today for Catalog 112
Representatives in principal cities
FREE Engineering Service



THE SOP MANUFACTURING CORP.

A RECEPT COMPANY . IN CREATER CLEVELAND. . ESTABLISHED 1916

POWER CHUCKS . COLLET and DRILL PRESS CHUCKS . ACCESSORIES
Rotating and Non-Rotating AIR and HYDRAULIC CYLINDERS . VALVES

For best results in Surface Grinding . . . Always Use Blanchard Wheels!

The flexibility in application of your Blanchard Surface Grinder enables you to attain peak production at lowest cost on hundreds of different grinding jobs. But, it is very important that you use the right wheel for each job!

Blanchard makes and stocks a great variety of silicate, resinoid and vitrified bonded wheels and segments. Ask your Blanchard representative to help you select the wheel — or wheels—best suited to your requirements. Call or write him today. And may we send you a copy of "The Art of Blanchard Surface Grinding" (4th Edition)?

THE BLANCHARD

RD MACHINE COMPANY 64 State Street,

Cambridge 39, Mass., U. S. A.




Use postpaid card. Circle No. 292

HYDRAULIC W & W KEYSEATER AND VERTICAL CUTTING MACHINE

does the work of many machines

In addition to a keyseater that cuts internal keyways up to 3" wide x 24" long, the new hydraulic M & M is a handy tool room machine and can be easily adapted to special production jobs other than keyways. A wide variety of internal or external cuts, serrations, grooves and teeth can be rapidly made on this machine. With a combination tilting table and index table (shown on machine at right) straight or tapered bores and accurately spaced multiple keyways or splines may be cut at any degree of the circle. Send us prints of your

> Right: Set-up for internal cutting Below: Set-up for external cutting



106

cutting problems.




BUILDERS OF MACHINERY
SINCE 1854

M&M KEYSEATERS AND

MITTS & MERRILL . 1015 S. Water St. . SAGINAW, MICHIGAN

NEW! **GREATEST CUT-OFF** CAPACITY IN ITS CLASS




· This newest addition to the Sever-All line of abrasive cutting machines-the Model 2-A-provides greater cutting capacity and more flexibility than any other machine in its class. Check these important advantages:

Big capacity . cuts 4" round or square solids, 6" diameter tubing or standard pipe, 6"x1" flat stock, 6" angle iron and 8" channels. Cuts practically all metals.

Fast operation • accurate cuts at 2 to 3 seconds per square inch. Power oscillation · oscillation is the forward and backward motion of the cutting wheel as it is fed down into the cut. It provides extra cutting capacity, longer wheel life, cooler cutting and reduced operator fatigue. Quality cuts . clean, smooth cuts, require little or no finishing operation. **Economy** • Sever-All wheels, developed especially for the Model 2-A, provide lowest cost per cut.

Y OF WORK HOLDERS GIVES UNUSUAL VERSATILITY







· Choose the work holders you need from chine at top, plus the V-block, angle-cutting several optional arrangements. These in- and 2-way clamp fixtures above. Screw-type clude the vise-type holder shown on the ma- and quick-action clamping interchangeable.

Write for details on the new Model 2-A Sever-All abrasive cutting machine. Ask for Bulletin DH-299

VER-ALL CUTTING MACH

Allison-Campbell Division, American Chain & Cable Company, Inc.

937 Connecticut Avenue, Bridgeport 2, Conn.

Use postpaid card. Circle No. 294

K



with (H*G) style DMS Stationary Die Heads and Throw-away Insert Chasers

On your turret lathes and hand screw machines, get big savings in dollars and time with H & G Stationary Die Heads because:

- 1. Economy! You can buy 3 to 5 sets of H & G Insert Chasers for the price of 1 ordinary set. You can let used H & G Chasers accumulate, with less investment, to be ground more economically at one setting. Or, you might find it less expensive to throw dull Chasers away.
- 2. Rejects reduced! The H & G Insert Chaser is held rigidly in the Chaser Carrier. The Carrier, being larger in area than ordinary chasers, affords greater Chaser "guiding power" for reducing chatter, taper and poor starts.
- 3. Thread close to shoulders! H & G Chasers extend beyond the Die Head face, making extension chasers unnecessary.

 Use postpoid card. Circle No. 295

- 4. One Die Head gives big threading range! The Style DMS 102 (4 chaser) or Style DMS 152 (5 chaser) Die Heads, for instance, cuts from No. 5 to 1¼" Dia. with only 4 ranges of Carriers. Other sizes available for smaller or larger ranges.
- 5. Quick change! H & G Carriers, complete with Insert Chasers, can be changed with the Die Head in the machine.

Why not write for Bulletin No. 12D on H & G Style DMS Stationary Die Heads today?





CORPORATION

64 Barclay Street . New Haven 6, Connecticut



WHY STUBBY?

Jarvis Stubby, a new screw machine stub tap developed for production tapping on bar automatics, is designed to cut costs by eliminating down time and improving performance.

SECRET OF STUBBY'S "NECKING"

The area directly behind Stubby's threads has been necked down to below the root diameter. This "necking" creates more chip room . . . reduces drag . . . facilitates application of cutting oils or coolants to the cutting edges for larger tap life.

STUBBY IS STRONGER

Its short threaded section and shorter overall length make Stubby a much stronger tap. You use standard size bushings (eliminating the need for special drills when making tap holders), because Stubby's shank is ground to standard fractional dimensions. Depth of thread is not a problem; for the combination of length of thread and length of necked shank is equal to the thread length on equivalent standard taps.

STUBBY BEATS COSTS ---

With Stubby you no longer need to alter standard taps for short clearance jobs. This means you cut costly machine down time, operator's time and minimize the possibility of having inconsistent tap performance.

STUBBY AVAILABLE FROM STOCK!

Stubby is available from stock in Spiral Flute Bottoming #SF-01, Spiral Point Plug #SP-50, and Bottoming Spiral Point #SP-70. All 3 styles available in machine screw sizes #2 thru #10. Other sizes available on request. WRITE FOR STUBBY LITERATURE AND TAP CATALOG.





CUT SMOOTH!

New "No. 20" \$799 € 377

OSCILLATOR

THE ANSWER TO YOUR "TOUGH STUFF TO CUT" PROBLEMS

CUTS LARGER SOLIDS

LEAVES "MACHINE TOOL" FINISH

IT OSCILLATES WHILE IT CUTS



Available on leasing or extended payment plan.

Speed & Gut

Abrasive Cutting Machines Manual or Power-Operated Models For Wet, Dry or any-Angle Cutting

Speed Cut

Send for complete -- catalog and name -- of nearest distributor

(Company)

BEAVER PIPE TOOLS, INC.

DANA AVE. WARREN, OHIO

Solve your "Small Parts" production problems



The husky Hannifin "Han-D-Press" takes operator fatigue out of light production operations where speed is the key to economy. A safe, easy-to-operate Hannifin air-operated bench press can handle these sometimes troublesome jobs better, faster and easier.

RIVETING STAKING PUNCHING PRESSING ASSEMBLING MARKING

CHECK THESE FEATURES:

- Electric control through Hannifin 4-way solenoidactuated valve.
- · Guided ram. Speed easily adjustable. Automatic
- Removable steel base plate. Easy to change job set-ups using alternate work bases.
- Minimum maintenance. Rigid frame; cylinder "trubored" and honed.
- Half-ton and one-ton models. Low prices. Immediate

Call Your Hannifin Man for Complete Information



South Wolf Road . Des Plaines, Illinois

IC AND HYDRAULIC SYSTEM COMPONENTS

DIVISION . PARKER-HANNIFIN N. V. . SCHIPHOL . THE NETHERLANDS



INDUSTRY'S FIFTH COLUMN

Tunnel vision! Restricted outlook! Tunnel vision acts as a fifth column in America's war for economic survival. It causes management to see only the balance sheet and ignore the pressing need to retool. It causes labor to picture only pay hikes without compensating productivity. It causes government to kill, with unrealistic depreciation allowances, the goose that lays its golden tax eggs. Tunnel vision distorts American industry. Let's open our eyes. It's later than we think. A machine tool is only as good as the CUTTING TOOL it drives. The industrialist who "economizes" on a cutting tool defrauds himselfnot only of machining accuracy but of the increased production and resulting profits which can be delivered. Pratt & Whitney Cutting Tools will bring out the best in your machine tools, will help win your battle for economic survival.



WANTED NOW!
GUSTOMERS WHO WANT TO WIN
THE FIGHT FOR SURVIVAL



PAW MACHINE TOOLS


Are you producing prototypes, dies, large or small lots of production parts? Ultra-precision locating (to "tenths" accuracy)? Boring, profile milling (with or without masters)? All these and countless other problems can be solved with P&W machine tools at production line speed, efficiency and economy. Machines such as the world-famous P&W KELLER. PAW JIG BORER. P&W ROTARY TABLE and P&W POTTER & JOHNSON AUTO-MATIC TURRET LATHE are available with manual or numerical controls in a variety of models to fit your needs. P&W can also supply the MAGNETRACE PROFILER, SIM LATHE, INNO-CENTI-MITSUBISHI MILL and the DIAFORM WHEEL FORM-ING ATTACHMENT...high grade performers all. For more information ask your P&W representative.



IN YOUR FIGHT TO SURVIVE YOU NEED THE FINEST WEAPONS

PAW GAGES

More than ever, production efficiency depends on fast, precise, economical gaging. P&W supplies all types of gaging equipment. Thus, you can choose those that do your job at lowest cost . . from simple CONVENTIONAL GAGES to the most intricate tape-controlled INSTRUMENT GAGES. Types include PLUG, RING, THREAD and SNAP GAGES, INTERNAL and EX-TERNAL COMPARATORS, and PRECISION GAGE BLOCKS ... all available through selected Industrial Distributors. The exclusive series of AIR-O-LIMIT,® TRANS-O-LIMIT® and DATA-LIMIT® gages and famous "FLY-ING MIKE" CONTINUOUS GAGE are available from your P&W representative. Bring your gaging problems to him.



MACHINE TOOLS - CUTTING TOOLS - GAGES . HEADQUARTERS FOR AMERICA'S WAR AGAINST OBSOLESCENCE





GUSHOF COOLANT PUMPS

GIVE 1 A PART HARMONY

IN DESIGN ...

Gusher Pumps contain no seals, pre-lubricated heavy duty ball bearings reduce maintenance to a minimum.

IN WORKMANSHIP ...

Gusher Pumps are precision built; there is no metal to metal contact within the pump.

IN SERVICE . . .

All of us at Ruthman are interested in your business. We want to earn it by giving you the best service at all times.



IN EFFICIENT OPERATION.

on your machine. Follow the leading machine tool builders; specify GUSHER Coolant Pumps.




Ruthman

MACHINERY CO

Use postpaid card. Circle No. 300

1816 Reading Rd. Cincinnati, Ohio

THE FIRST MAJOR CHUCK DEVELOPMENT IN FIFTY YEARS



This radically different chuck combines all the desirable features of hand and power chucks. It has accuracy within .001 TIR, repeatability within .0005 TIR, unequalled gripping power, and no size limitation.

This major chuck development is a principle utilizing combination of pinion, gear plate, screw and wedge. The lug-type pinion is turned manually or by a power wrench. A pinion engages the gear plate causing the screw to

move the wedge. The action of the screw on the wedge controls the chuck jaws. The force of the wedge on the jaws holds the work with tremendous power.

In addition to this unique, new principle, this chuck offers such features as over-tightening protection, operator protection, higher speeds, centerhole chucking and many more. For details, write us at the address below, Department 144.



SKINNERCHUCKS

THE CREST OF QUALITY

SKINNER-HORTON CHUCK DIVISION

SKINNER PRECISION INDUSTRIES, INC. • NEW BRITAIN, CONNECTICUT, U.S.A.

Use postpoid card. Circle No. 301



Features In This Issue

- CHIPLESS MACHINING will be discussed each month by columnist Charles H. Wick, an authority and author of a book on the subject. This month's column reviews cost-cutting advantages, higher production efficiencies, improved product quality, limitations of chipless machining, and the future of chipless machining.

 Page 128

NEW



14" LATHES
BEST DOLLAR VALUE
IN THE LATHE FIELD

These new Logan 14" swing lathes are **DEPENDABLE**. Their capacity permits a broad range of machining operations. They have a 14%" swing over bed, a swing over saddle cross slide of 9", and a center distance of 28". Logan lathes are **ACCURATE**. The ball bearing spindle has a 1%" hole and a draw in collet capacity of 11%6". The variable speed drive (40 to 1400 RPM) adjusts while running—no need to stop and shift belts! Also, the two V-ways and flat ways are precision ground. Logan 14" lathes are **RUGGED**. The 10" wide and 56" long lathe beds are braced by oversize ribs to withstand torsional stresses. The Logan 14" lathe is your best dollar value. No other lathe in this price category offers you this same big work capacity with variable speed drive.



Model 6510 \$1,77500 F.O.B. Factory

Write for complete specifications.



LOGAN ENGINEERING CO., 4901 W. Lawrence Ave., Chicago 30, III.

WITH THE EDITOR:



The Big "Push" to Chipless Machining

Techniques for cold-forming metal to shape are being explored and exploited at an accelerated pace. The advantage inherent in "moving" instead of "removing" metal is that the raw product and the finished product represent substantially the same amount of material.

Of the three elements which constitute the cost of a metal product (material, labor, and overhead), the cost of the material is frequently the predominant one. When it is realized that an average of 30% of the raw material weight of the cut-machined part ends up in the scrap pan of the machine tool, the appeal of "chipless machining" becomes apparent.

Forging, hammering, and coining are rooted in antiquity. Wire drawing, cold heading, and a few other versions of the art of plastic deformation have appeared in more contemporary times. In the main, however, the bulk of metalworking technological development has been concentrated in areas where cutting processes and equipment have been involved.

Today's changing emphasis stems

from a number of factors, in addition to the obvious one of saving material. Many chipless machining techniques are decimating production time. Products with superior metallurgical properties are being obtained. And what is more, shapes and sizes impractical to create by cut machining are now available to the product designer.

Recognizing an urgent need for greater editorial attention to chipless machining, BLUE BOOK This month presents the first of a series which



will explore every facet of this mushrooming field. The author, Charles H.
Wick, is a familiar figure in metalworking circles. A graduate engineer,
product designer, and former managing editor of Machinery magazine, he
is presently a vice-president and director of editorial relations for Dudgeon,
Taylor & Bruske, Inc. We feel honored
that our readers can now share his
comprehensive, complete, and unbiased knowledge of chipless machining.

Edgar Altholz

Begar Gerhal








AMERICA'S AMAZING ABILITIES

Abilities Inc., Albertson, Long Island, is a bustling metalworking and electronics plant having but one employment requirement of its 385 people: You have to be seriously disabled to get a job there. In vigorous competition with other firms, Abilities pays prevailing wages, asks no favors, accepts no charity.

Here is the substance of a recent interview the editor of BLUE BOOK had with the company's inspiring president, Henry Viscardi, Jr.



Q. What do you think, Hank, is the best approach to the hiring of the disabled in manufacturing?

A. The first thing we have to do in the metalworking trades or anywhere else in American industry is to have a broader concept and not feel that we are working under restraints and doing something charitable for disabled workers. If we begin to think in terms of how comfortable and convenient it is to move around in a wheel chair instead of walking around. a wheel chair isn't as frightening to us any more. You have seen me walk around and I walk around pretty well, even though I have two artificial limbs. But you ought to see me when I get into a wheel chair. I go spinning around corners and I am the whirling dervish for sure.

We first have to overcome some blocks that we seem to have that are latent—we don't recognize them. they've been there a long time-that people with disabilities cannot be as good as others. The man who shows up at the employment office in a wheel chair or on crutches or with one arm off, or with other problems that are disabling, immediately presents certain barriers to the mind of the recruitment officer or the employment manager. He presents barriers to the training supervisor, who hasn't seen him yet, he presents barriers to the foreman, who after all, wants the best of material and the best of men to turn out the product that he is going to answer for at the end of the month. The foreman rightly says to himself that he won't take any chances with this marginal "commodity."

Secondly, we have to recognize that disability never became a common denominator of any kind. People are people, and percentage-wise there probably as just as many lazy loafers in wheel chairs and on crutches as there are in the average population, and disability never made great people or great potential workers any more than red hair or brown eyes did. So if we can judge them then as people, accepting them without the barriers that are presented because they are different in some way when we first look at them, half the battle is won. The rest of it lies in the techniques of training, and in making certain modifications and adaptations of tooling and equipment, which should not be expensive; in fact, which would flow in most naturally from an interested worker seeking to adjust himself to his new environment.

Q. When a proposal for a job comes in do you automatically accept it or reject it on the basis of the capability of your present personnel? In other words, suppose some job came in which you could not handle, would you go out and look for people with the specific skill to do this, or would you retrain the people you have to do it, or would you reject the job?

A. It would depend on the potential in it for us. Take our motor department, for example. We are pretty proud of it. We think we have a real future in this, in building such things as synchros and resolvers. When we first went into this, before we could build up our own capacities so that we knew there was a five year curve we were planning on, we bought our special skills. Now as we get deeper into the motor program, we realize we are in it for keeps, and we train our own people. The fact that we are disabled has nothing to do with this.


Q. In other words, the considerations are primarily economic and not sentimental?

A. Precisely.

Q. What are some of the machine

 This wheel-chair case has been able to operate a surface grinder after a platform and a short ramp approach were constructed in front of the machine.





2. With the speed-selector handwheel lowered through an extension rod, this drill press can be operated with considerably less fatigue—even for a non-disabled person.

tools which your people have been able to operate?

A. It would be a lot easier for me to tell you, if I could think of them, what we have not been able to operate. For example, when we first tooled up a turret lathe, one of our men operated it from a wheel chair. This mar. was a paratrooper and had both legs blown off in World War II. We were able to fixture that machine so that he ran it efficiently and completely. It might also interest you to know that for certain operations we were able to adapt that turret lathe for a blind man to operate.

Q. Doesn't that additional fixturing and tooling time put you at a competitive disadvantage?

A. No, because this is a bio-engineering study that we perform separately in our research and teaching group, the Human Resources Foundation. HRF would undertake a study to find out how we could adapt a turret lathe to a specific disability.

Having accomplished this, we'd be in business to ask, 'Where can we sell this?' What is more, the research would be made available to anyone in industry. So you see, by our own accomplishment we have helped to break down that barrier.

Likewise, research that we've done in regard to posture and comfort for the disabled worker has proved to be of infinitely even greater benefit to the so-called normal worker. A great deal of our research is conducted on this premise. Research in motivation, for example, the will to work. What an important topic this is for everyone!

Q. Is it your wish to see industry eventually absorb all disabled workers, or would you rather see more plants like Abilities around the country?

A. I would much prefer industry absorb the disabled. Frankly, I look upon Abilities more as a demonstration laboratory to show what these people really can do. Because our country is so big, I would like to see

more plants like Abilities established in regional areas.

Here, under one roof, we have approximately 385 people operating competitively, meeting quality standards and delivery schedules in the metalworking and electronics fields. What we learn about the performance of these people is being passed on to industry so that it can take full advantage of this segment of manpower available everywhere in America.

Think of it this way. I believe there are in Abilities right now ten or twelve cases of industrial accidents. Now for every year that these people work, we are saving some insurance carrier approximately \$100,000. If we could get more industrial accident cases back to work, it would be better for the individuals—they'd be healthier and happier working than sitting home collecting compensation.

Q. How about your own safety record right here in Abilities?

A. Our experience in Abilities has

been so good that we are presently downrated 47%. We have a credit, and it's been as high as 52%.


Q. Has what you've done so far resulted in the absorption by industry of the disabled worker to any great extent?

A. Indeed it has. We have men who have never worked before because of their disability, or who have never worked since the onset of their disability, who have now not only successfully worked here for two or three years, but have left for better jobs in bigger companies where they are doing very well. Some of our men are supervisors and foremen in other companies in related fields.

Part of our function, as I see it, is to "graduate" people whom we have trained. We have to do this with discretion, however, because if we bled off our skilled leaders, we couldn't answer the demands of our customers. We are sending out on

3. Arthritis has left this worker's spine rigid from neck to hips, but he runs a belt sander on a full-shift basis without any adaptation of the equipment.





4. A person whose legs have to be in an elevated position is today gainfully employed as an adept bench hand, thanks to a pair of simple foot slings. Readily detachable, the devices permit him to be transferred from one bench station to another.

the average of 2.4 people per month. Remember, these are people who came from the shadows, that nobody would employ, but who built up their skills and physical capacities here.

Q. Does Abilities require any kind of pre-employment examination?

A. All of our people are severely disabled and most of them would be rejected by the pre-employment physical examination of the average company. Yet statistics show our safety record is one of the most outstanding in American industry.

We have no pre-employment physical examination. This has been done for a unique and interesting reason. In order to establish the best area for research, I said at the outset that we would have no pre-employment medical examination, no pre-employment psychological examination or aptitude evaluation. We take people in no matter how disabled who want to work. We want this to be a "purest"

laboratory. No, from our viewpoint, how sick a man is, or how disabled a man is, isn't nearly as important as whether he wants to work or not—his motivation, for want of a better word. If he wants to work, we can overcome all the problems of the disability.

Q. Don't you think that he might want to work so badly that he might fail to reveal some unknown disabilities to you, and you would be running a risk there?

A. Yes, I do. I would not advocate this policy for industry. I advocated it for us, because we wanted to find out all we could about these disabled people, and we didn't want any preconceived notions that would keep them from coming to us. We wanted to have all the experience—adverse and wholesome—out of which we could accumulate knowledge to pass on to industry. Now, I think however, that we are beginning to feel that



5. A totally blind worker assembles connectors on a jet-engine analyzer by means of an air screwdriver and a holding jig. His production performance compares favorably with that of a sighted worker.

industry should update it's pre-employment physicals to meet the new concepts of what disabled people can do. Some of industry's physical standards of recruitment have not been updated in many years, and some industrial medical men need the advantage of this new knowledge of what we know about things like heart disease, epilepsy, and paraplegia.

Q. How about the attendance record of these people?

A. It's outstanding. The average absentee rate in American industry is 3.8 days per 100 working days. Ours is about 1.1.

Q. Does the enthusiasm of your people wane after they have been on the job for a period of time?

A. We have to strive continually to maintain a high level of motivation. This comes from good management, interest in the worker as an individual, and genuine love for him. It involves an appreciation for his dignity as an individual, his right to be informed about what's happening in his company, and his personal problems. I think there is a basic weakness in suggestion systems, where your payoff is in the form of a check. It's a poor substitute for a "thank you," the sense of real appreciation for something that somebody has done for the company and for himself.

When we put a person to work after everyone else has rejected him, we acquire a highly motivated individual. But we know that if we don't keep the level of job satisfaction up, he will be no different than anyone else. We've got a wonderful person to work with in the disabled worker, and the chances are that he is going to give us back just a little bit more because this is his priceless opportunity. But basically what he requires—and this should be comforting to industry—is pretty much the same as anybody else.

How the NBS uses the new wave-length standard in

Parallelism of a set of gage blocks being measured with an interferometer recently developed at the Bureau.

CALIBRATING





PRECISION GAGE BLOCKS


By calibrating from five to six thousand gage blocks each year, the National Bureau of Standards of the U.S. Dept. of Commerce is providing industry with one of its most effective means of monitoring the increasingly close dimensional tolerances. Calibrations with uncertainties as low as one part in a million are available, permitting industry in turn to use the gage blocks for calibrating other equipment with only slightly less accuracy. However, gage blocks of the highest attainable accuracy are also being applied directly in "custom" production work on critical projects.

In principle, it should be possible to provide calibrations of substantially higher accuracy than in the past, as a result of the recent adoption of a wave-length standard of length and better auxiliary equipment, such as interferometers. A continuing obstacle, however, is the dimensional instability of even the best alloys commercially available for manufacturing gage blocks. In special cases it has been possible to certify gage blocks to an accuracy of better than one part in five million. Research is now under way at the Bureau to find allovs which, it is hoped, will permit regular calibrations to one part in ten million.

Gage Block Applications

In its simplest form, a gage block is a rectangular block of steel with square or oblong cross section and with two opposite edges-the gaging surfaces defining its length-ground and lapped flat and parallel. These extremely flat and highly finished surfaces make possible two very useful characteristics of gage blocks. They can be measured directly in terms of wave-lengths of light by interferometric methods, in which light beams are reflected from the gaging surfaces. Also, by carefully sliding a gaging surface of one block over a gaging surface of another, the two can be "wrung" together so that they offer considerable resistance to separation; in this way, a series of blocks can be assembled for a required length.


A typical set consists of eighty-one gage blocks, with sizes ranging from .05" to 4". Of the eighty-one, there are ten blocks with lengths from .1000" to .1009", in steps of .0001"; fifty blocks from .101" to .150", in steps of .001"; seventeen blocks from



Black diagram of the procedure followed by the National Bureau of Standards in calibrating precision gage blacks.

.20" to 1.00", in steps of .05"; and single blocks with lengths of .05", 2", 3", and 4". With these eighty-one blocks, over 100,000 combinations of measurements are possible in steps of .0001". By the additional use of .100025", .100050", and .100075" blocks, combinations can be made in steps of as little as .000025".

Many industrial and scientific laboratories maintain one or more sets of master gage blocks which are used only to calibrate working sets; and the latter are used for direct measurements or for calibrating various kinds of measuring instruments. Among many other applications, the blocks serve to test the accuracy of micrometer calipers, and of ring, plug, and snap gages; to check the lead of screw-thread gages; to calibrate strain gages and mechanical or electronic indicating gages and comparators; and they are used with sine bars for precision angle measurements. At the Bureau they are often employed in measuring of derived quantities. In the calibration of precision ba-



To determine the degree of flatness in gage blocks, interferometric patterns such as these are obtained. Broad dark lines on the surface of this block indicate a high degree of flatness.


rometers, for example, gage blocks are used in determining the height of the mercury column.

Precision gage blocks are classified as Grade AA (laboratory quality) and Grade A (inspection quality). Laboratory quality blocks are manufactured to within a few microinches of their nominal length; that is, the length indicated on the blocks. As mentioned previously, gage blocks exhibit a dimensional instability with the passage of time, an effect that is in addition to changes due to wear.

In the case of master blocks that are seldom and very carefully handled, the change due to wear is quite small; while the change caused by instability may in some cases amount to several microinches per year. It is therefore considered necessary to recalibrate master blocks at intervals of from one to several years, depending on the type of usage and level of accuracy.

Calibration Procedure

The first step in the Bureau's calibration procedure is to test the gaging



By exerting a slight pressure, gage blocks can be wrung tagether to make highly accurate measurements.



surfaces for flatness and parallelism. Blocks with excessive deviations in either of these respects are as a rule not calibrated; or, if they are, the accuracy of the measurements is not certified. In maximum precision applications, it may be necessary to take into account even fairly small deviations, since lack of flatness or parallelism means that the length of the block will vary from point to point on the gaging surfaces.

The lengths of all blocks submitted for calibration are then determined by comparison with NBS master blocks of the same nominal size. These master blocks are calibrated against the laboratory's reference

standards—light waves produced by cadmium and mercury 198. The lengths of these light waves are known very accurately in terms of the new international standard of length, the wave-length of the orange-red spectral line emitted from atoms of krypton 86. Electromechanical comparators of the dual transducer type show the difference in length between master block and test block. Each test block is compared at least twice with the master blocks. Tongs are used to handle the blocks so that variations from the 68° F temperature maintained in the laboratory will be held to a minimum.

Data from the electromechanical



Recording length measurements obtained with one of the electromechanical comparators used in calibrating gage blocks,



comparators are recorded on punched cards for processing in a high-speed electronic computer which calculates the deviation of each block from its nominal length. In arriving at an average value for the block, the computer examines both comparisons for excessive spread or variation between their values. When too much spread is noted, the block must be recalibrated.

If the set is being given an "A" calibration, the test is now complete and the final report is assembled. This report consists of a table showing the nominal size, identification, deviation from nominal length of each block, and any excessive deviations in flatness and parallelism. A text



Inserting an optical flat, to which gage blocks have been wrung, into one of the interferometers used to measure the lengths of the blocks by means of light waves.

explaining the calibration is attached to the report.

When accuracies of a higher degree are required ("AA" calibration), interferometric measurements with light waves are made. Because the blocks are wrung to steel optical flats for measurements, the gaging surfaces must be completely free from burrs, and substantially in "new block" condition. After wringing, sufficient time is allowed for temperature equalization. The flats are then placed in the interferometer where the upper surfaces of the blocks and the flat become mirrors in the optical system.

Two interferometers, in which cadmium and the mercury isotope 198 are the light sources, are used to make two separate sets of measurements. The light from these sources consists of a number of monochromatic radiations (spectral lines), one of which is used from each source. Two determinations are made, using each source in turn; the blocks are then wrung to another optical flat, and this operation is repeated.

Each of the spectral lines produces a pattern of optical interference fringes which serves, in effect, as a finely divided scale. One division on these

NOMINAL VALUE (inches)	ACCURACY OF CALIBRATION (microinches)	Blocks in this size range are usually warped and do not warrant calibration to a higher accuracy. If errors in flatness are not excessive, it may be possible to calibrate blocks 0.040" and thicker to an accuracy of ±2 microinches.	· 医多位性 · · · · · · · · · · · · · · · · · · ·
0.100 to 2.000	±2 or ±4	Two types of calibrations are available for gage blocks in these size ranges: Type AA,	
2 to 3	±3 or ±5	for Grade AA, (laboratory quality) blocks, is indicated by the first listed accuracy at	
3 to 4	=4 or =6	left; Type A, for Grade A (inspection quality) blocks, is indicated by the second listed accuracy.	
5 to 20	1 per inch of length	Accuracy contingent on quality of gaging surfaces.	

scales corresponds to half a wavelength of the light used (approximately .00001"), and it can be subdivided into tenths (approximately .000001") without difficulty. During the measurements, precise determinations are made of air temperature, barometric pressure, and humidity, since these factors affect the wave-length of light by changing the index of refraction of air. Temperature of the blocks is also measured and corrections are applied so that the final reported lengths are at the standard 68° F.

The additional data obtained from the interferometric measurements are then fed into the computer which uses them to calculate the length of each block. It is interesting to note that from computations such as these, the accuracy of the Bureau's master gage blocks is indirectly verified. This verification is accomplished by comparing the results of the mechanical comparisons with those of the interferometric comparisons.

The final report for an "A" calibration is essentially the same except that more stringent requirements for flatness and parallelism are observed, and higher accuracies are


obtained.

If Tape Preparation Is Holding

There's No Need To Postpone Numerical Control

By James B. Pond, Managing Editor





Computer services that are available to industry take the headaches out of N.C.

You Back...





COMPUTER-ASSIST PROGRAMS greatly speed tape preparations and give optimum performance. It is in rooms such as this that most of the procedures normally followed by shop personnel are broken down into sub-routines, and this information is fed into the computers where it is stored until needed. Pictured here is one of two consoles of IBM 705 in operation at BOEING AIRPLANE COMPANY'S Wichita Division.

■ Numerical control is rapidly becoming an everyday production tool for all industry. It is tumbling costs as more and more people gain experience and can take advantage of the changes in manufacturing procedures that it is bringing about.

Those who still are apprehensive about numerical control will find that the frustrating aspects of tape preparation are being solved nicely and painlessly. Actually, there is no more reason to shy away from numerical control than there is from camoperated or tracer-controlled machine tools.

The screw-machine cam designer and the numerical-control parts programmer have much in common. Each must decide which tools to use, the order of operations, speeds and feeds, and other machining data.


Numerical control is no more than a means of directing a machine's movements by numbers. It does involve considerable mathematics but



TAPES PREPARED AT BOEING are checked out in a specially built plotter-verifier that reproduces the tapes in visual form. Value of this method of checking is that the user does not have to utilize valuable machining time with a dry run to prove the tape.

operational level personnel do not get involved in higher mathematics. Tapes for point-to-point positioning systems can be prepared manually from dimensioned drawings by persons having only a high school level of mathematics. But, manual preparation of tapes is laborious and sometimes the manually prepared tape does not produce the most efficient results. Computer-assist programs greatly speed tape preparation and give optimum performance.

The reason why complicated and simple tapes can be prepared quickly by a computer is that most of the procedures normally followed by shop personnel are broken down into subroutines, and this information is fed into the computers where it is stored until needed. Thus, if a pocket is to be milled, a programmer only has to define the periphery and then command the computer to supply the details necessary to direct the cutter back and forth to clean the pocket.



TAPE CONTROL GALOREI These five Milwaukee-Matics at Boeing's Wichita plant are located in a single centralized area for efficient operation. Note the ample working space around each machine in what appears to be, but is not, an isle. This area is needed to expedite the flow of fixtures and tooling to and from the machines.

An excellent example of numerical control in action is at Boeing Airplane Co.'s Wichita plant, where there are nineteen numerically controlled machines, some simple and some complex, now working on a three-shift, six-day week basis.

Boeing's first numerically controlled machine arrived in November, 1956. It was a three-dimensional continuous-path profiling machine that required the use of a computer to prepare the system's punched tape.

By tackling the more difficult continuous-path system first, Boeing engineers found that their computer experience paid off when it became necessary to produce tapes for pointto-point positioning. They got better tapes and produced them in less time.

With the addition of other numerically controlled equipment, a variety of control systems have been involved. The problems of providing complete control media have been solved by Boeing through the development of

EXAMPLES OF SUB-ROUTINE SOLUTIONS





HTION: GENERAL CURVE INTERPOLATIO

IVEN: POINTS ON CURVE.
TOLERANCE (UNITED BY BEINT FROM CURVATURE)
NO: XY Z COORDINATES FOR SUFFICIENT QUANTITY
OP POINTS TO DEFINE CURVATURE WITHIN
GIVEN LIMITS







CONDITION: POCKET SIVEN: GEOMETRIC SHAPE (HIDIVIDUAL LINES, CIRCLES, CURVES) DISTANCE DETIMEN CENTER PATHS

EYE COORDINATES DESCRIBING CUTTER MINS FOR REMOVING INTERNAL MATERI DATA DESCRIBING FINISH CUT FOR PERIPHERY & ISLANDS WITHIN PERIPHERY

THE REASON WHY TAPES can be prepared quickly by a computer is that most procedures normally followed by shop personnel are broken down into sub-routines that are stored in the computer. In the example where it is desired to mill a packet with an island within it is only necessary to define the geometric shapes, the distance between center paths, and the feed rate. The computer will then figure the best method to accomplish these results. The center drawing shows the roughing cuts and the drawing at the right shows the route of the cutter during the finishing cut.

computer programs. Machining information and experience have been broken down into subroutines and stored in the high-speed computers' memory devices. These programs are identified at Boeing as WALDO, short for Wichita Automatic Linear Data Output.

Of interest is the fact that Waldo's experience and tape preparation equipment are available to all industry through Boeing Applied Computer Services. These services include: parts programming, computing, tape processing, tool design, tool fabrication,

parts fabrication, consulting and training.

Who Should Use Numerical Control?

Large plant or small, there are two conditions which indicate potential profitable use of numerical control. The two are short runs and constantly changing dimensions or designs. And, there's the rub-when runs are short and changes are constantly being made, many tapes will be required. That's why it is important to shake any lethargy one has toward the making of tapes.

The basic elements of numerical control include the dimensional drawing, part programming, data processing, and finally, the machine tool.

Although point-to-point positioning systems can be programmed manually at the user's plant, those who do utilize computer services such as Boeing's will find most of their activities centered around dimensional drawings and part programming, areas in which they are on familiar ground.


Engineering drawings are used now, but with numerical control they are not absolutely necessary. Since it is possible to work directly from formulas, prints should be completely dimensioned. Boeing programmers report that many drawings submitted to its service are not ready for production. Too much is left to the discretion of the machine operator. In this respect, airframe manufacturers are probably as guilty as the rest. They will have to change their established


procedure of using a French curve to shape panels because a French curve can not be "dropped" into a computer. Parts must be completely defined.

The information to be taken from the dimensioned drawings or mathematical formula must be put into a language and form acceptable to the control system being employed. It is here that such vital information as the sequence of operations, speeds and feeds, direction of cutter rotation. and type of mounting of the cutter and workpiece are decided. It is interesting that production planners who do this translating do not need more than high school mathematics and practical shop experience as machine operators.

After a program sheet has been prepared, the information can go either to a card or tape punch. The punched cards or tape then may go directly to the machine control unit

ALREADY AN OLD FAVORITE with management and operators alike. It takes awhile to get used to seeing difficult jobs run, one after the other, without stopping the machine for lengthly changeover.





ADVANTAGES OF NUMERICAL CONTROL apply to machines other than for metal cutting. This is one of four General Riveting Co. Drivmatic riveters which rivet stringers to wing skins of the Air Force's new B-52H missile launchers. These tape controlled riveters drill, countersink and set, drive and shear the rivets.

NO NEED TO POSTPONE TAPE CONTROL

or to a general purpose computer for further refinement necessitated by the characteristics of different numerical control systems.

Some systems employ magnetic tape for continuous-path contouring, while others employ punched tape; other systems employ punched tape for point-to-point positioning. Then too, within each control system the method of application will vary from one machine tool builder to another. Such variations must be provided for, and this is done in what is called post processing. A post processor is the part of the computor program that converts raw "point data" into information acceptable to the machine control system, taking into considera-

continued

tion the dynamics of the machine involved.

Tapes are checked out at Boeing in a specially built plotter-verifier that reproduces them in visual form. It is unnecessary for the user to place them in the machine tool and make a dry run.


Numerical control is being applied to a growing list of machines—milling machines, profilers, lathes, grinders, drilling machines, riveting machines, welders, flame-cutting machines, and inspection machines. With computer services now available for the tape preparation, the tremendous cost-saving potential of numerical control should be expored by everyone.

Accuracy of Positioning

Longitudinal Travel:	
Greatest error in any inch	15 millionths
Greatest error in any 18 inches	35 millionths
Cross Travel:	
Greatest error in any inch.	
Greatest error in 11 inches	

Squareness:	
Compound slide	20 millionths
Travel, spindle housing	
Travel spindle	30 millionths in 214"

Spindle Axis:	
Runs true	within 3 millionths



The tolerances shown at the top of this page will be proven in front of you before final acceptance of the machine, as it was with each customer shown at right.

These users will also attest to the advantages of this machine: its capacity for ultra-precise measuring and inspecting of larger workpieces; the choice of an electronic indicator supported on an accurate, rotatable spindle, or a universal microscope for pickup; a combination of rectilinear and angular positioning, making possible the measurement of the most complex contours. All ways are hardened, ground and lapped steel, fitted to handscraped cast iron. Table positioning in two directions of travel is by means of master lead screws. Note motorized lead screw drive, offered as optional equipment.

Write today for complete details.

MOORE SPECIAL TOOL COMPANY, Inc. 728 Union Avenue, Bridgesort 7, Com.

Sperry Gyroscope Division, Sperry Rand Mineola, New York Eonic, Inc. Detroit, Michigan Dow Chemical Company Rocky Flats, Colo.

Massachusetts Institute of Technology Cambridge, Massachusetts DeVlieg Machine Company Royal Oak, Mich. Douglas Aircraft Co., Inc. Charlotte, N. C. AC Spark Plug Division, General Motors

Milwaukee, Wisconsin
Sangamo Electric Company Springfield, III.
University of California ... Les Alamos, N. M.
Raytheon Manufacturing Company
Andover, Massachusetts

Kollsman Instrument Corporation
Elmhurst, New York

Elmhurst, New York A. C. F. Industries, Inc.... Albuquerque, N. M. General Electric Company... Richland, Wash. Naval Grdnance Pfant

South Charleston, W. Virginia

Catmur Machine Tool Corp., Ltd. England North American Aviation, Inc. El Segundo, California

Eİ Segundo, California University of California Livermore, Calif. Bendix Aviation Corporation Kansas City, Mo. Chandler Evans Corporation Hartford, Conn. Mason & Hanger—Silas Mason Co., Inc.

Mason & Hanger—Silas Mason Co., Inc. Amarillo, Texas International Business Machines Corp. Owego, New York

Union Carbide Nuclear Co... Oakridge, Tenn.

*University of California Livermore, Calif.

*General Electric Company Schenectady, N.Y.

*Dow Chemical Company Denver, Colorado

*Rendix Aviation Compration

Bendix Aviation Corporation
Kansas City, Kansas

Federal Products Corporation
 Providence, Rhode Island
 *Union Carbide Nuclear Co.... Oakridge, Tenn.

REPEAT ORDER

ADD (TABLE) TO YOUR TOOLROOM

JIG BORERS - JIG GRINDERS - MEASURING MACHINES - PANTOGRAPH WHEEL DRESSERS - PRECISION ROTARY TABLES - HOLE LOCATION ACCESSORIES

Use postpaid card, Circle No. 303



INTERESTING MOTIONS

Increasing a Press's Capacity


By L. Kasper

■ Once in a while a machine isn't quite big enough for a job. Such was the case recently in our plant when the only machine available for a riveting operation was a small punch press. The press had sufficient power and shut height but its short stroke would not permit the workpiece to be inserted between rivet sets. The die shown on the opposite page was designed to increase this opening between the rivet sets when the ram was in its upper position.

The die is shown in Figure 1 in the open position. The workpiece is in position but it is mounted in a fixture that is not illustrated. Figure 2 shows the die in the closed position with the rivet set.

Here's how it works: The two rivet sets A are mounted on levers B and C. Lever B swivels on a pin mounted in block D, which is attached to block F mounted on the bolster plate. Lever C swivels on a pin mounted on the two extensions on lever B. Two links G connect lever B with the block H mounted on the ram of the press. Block F carries a roller E which supports lever C.

After the workpiece has been inserted, the press is tripped, causing the end of lever C to swing upward by the downward movement of lever B, to the position shown in Figure 2, setting the rivet. The lever arrangement provides an opening for the insertion of the workpiece approximately equal to four times the stroke of the press.



April, 1961



Chipless Machining

By **Charles H. Wick**, Vice-President Dudgeon, Taylor & Bruske, Inc. Detroit, Michigan

Three Good Reasons for Investigating This Important Area of Metalworking

■ Chipless machining, as discussed in this column, refers to production methods of cold forming (plastically deforming) metal to finished part shapes without making chips. Actually, the term is a misnomer, since "machining" is more commonly thought of as some type of metal-cutting, chip-producing process of shaping a part to a required contour. However, the term chipless machining is being widely used by the manufacturers of cold-forming equipment, the users of such equipment, and the purchasers of parts made by the various cold-forming processes.

These processes are being increasingly applied in industry today because they offer one or more of the following three advantages:

- 1. Lower cost.
- 2. Higher production efficiency.
- 3. Improved product quality.

Cost-Cutting Advantages

The lower cost of chipless-machined parts results primarily from the fact that less material is required. Production of chips is either reduced or eliminated, since the need for subsequent machining is either decreased or not required. In many cases, all of the original material is present in the finished part. With chipless machining, metal is moved rather than being removed.

Waste in the form of chips can be as much as 70% or more in the production of some metal parts, with an average of about 30% by weight. With the continual rise in the cost of raw materials, chipless production processes thus offer an important economy.

Another cost-cutting advantage is that cheaper raw materials can sometimes be used. For example, lower cost, hot-rolled steel bar stock is now being used for many cold-formed parts previously made from cold-drawn bars. This is possible because of the higher physical properties resulting from the plastic deformation of the material, and the unbroken, contoured flow-lines produced. In some instances, the need for previously required hardening of the parts has been eliminated. In other cases, the cross-sectional area of the part can be reduced because of increased strength.

Further savings are frequently obtained as the result of lower labor costs, since many of the cold-forming processes can be made completely automatic. Also, the investment necessary in capital equipment is generally less, because fewer machines are usually required. Tooling costs, too, are sometimes less, especially when large quantities of parts are needed.

Higher Production Efficiencies

Many chipless machining methods permit high rates of production. For example, in cold extruding small steel components, 100 or more parts are being produced per minute. With cold heading, outputs of 450 or more parts per minute are possible. In thread rolling, production rates of 2000 per minute are common. Such high rates result in economical, highly efficient production and assure a rapid return on capital investment.

Versatility of the processes and equipment also boosts production efficiency. Unusually shaped parts, difficult or costly to produce in any other way, can frequently be made rapidly and economically by chipless machining. Many parts and processes are easily adaptable to automation, with automatic loading, cycling, unloading, and handling between operations. Parts previously requiring the manufacture and assembly of several components can often be made in one piece, thus greatly facilitating production.

Improved Product Quality

The high quality of parts produced is an important benefit derived from chipless machining methods. Since the raw material does not have to be heated, as in casting and forging, there is no scale formed on the surfaces of the parts, and no decarburization of the material. The smooth surface finishes produced, with well-rounded corners and fillets, and no burrs—as well as the close tolerances that can be maintained—generally eliminate the need for any subsequent machining of the cold formed parts.

Consistent uniformity of the parts produced is also important, since it eliminates the need for 100% inspection and assures customer satisfaction. Another factor contributing to improved product quality is the increased strength (tensile, yield, shear, and

fatigue) and higher hardness resulting from cold working.

Limitations of Chipless Machining

While fewer machines are generally necessary for cold forming, the cost of the machines are usually quite high. Also, tooling for the equipment can be expensive unless it is amortized over large production requirements. As a result, many chipless machining methods are not economical for short runs of a large variety of parts.

The size of the parts that can be produced by chipless machining methods is limited because of the large, expensive equipment required to produce the necessary high pressures. Also, some of the higher alloy steels and the newer superalloys cannot be cold formed because of the high pressures required.

However, continued progress in improved equipment, tooling, lubricants, and techniques will remove these obstacles. In fact, most of the limitations mentioned do not pertain to explosive and high-energy-rate forming methods which will be discussed in subsequent columns.

The Future of Chipless Machining

Cold forming methods of producing metal parts are, with few exceptions, not new. However, they are only now beginning to grow in popularity and be increasingly applied in all metal-working industries. Automotive, aircraft, and other industries are devoting considerable time and money to the development of such processes and their application to the manufacture of their products.

Continued growth in the application of chipless manufacturing processes will require an entirely new concept on the part of management, designers, and production engineers. They should no longer ask, "What machines can we produce the parts on?" Instead, they should think in terms of processes, and be familiar enough with chipless machining methods to consider them for their production requirements. The ideal time to consider any process is in the product design stage, when minor modifications might mean major savings.

Chipless machining undoubtedly has a bright future. Larger machines, better tooling, more suitable lubricants, and improved techniques are continually being developed. "Warmforming"—the plastic deformation of metals heated to below their transformation temperatures; huge powerspinning machines for missile airframes; and new high-energy-rate forming methods are some of the important developments that will be discussed in future columns. • • •







The Practical Diemaker

By **Paul Prikos** Prikos & Becker Tool Co. Skokie, Illinois

Want quality production?

Check Your Attitude Toward Maintenance

■ Today's emphasis is definitely on quality and excellence in manufacturing. It is folly to expect to attain these high demands without topnotch equipment. Since few can afford to purchase new or nearly new machinery every year, good maintenance schedules should be followed to at least sustain the specified performance of the machines during their depreciation period.

Though most large companies have established a maintenance setup that blankets all physical assets of the factory, a little extra effort in most cases would see improved results. Small companies, where there is a more personal interest by owners, have an advantage, they can keep a closer scrutiny on the upkeep of equipment.

The die room or die shop of any captive or job shop must be considered as small scale companies; they should have scheduled maintenance procedures with periodic checks by interested personnel to maintain top efficiency.

A suggested maintenance procedure for die room equipment could be as follows:

SURFACE GRINDERS (light type)

Every week or two, depending upon their usage, turn the tables over and thoroughly clean out their ways. Check for score marks and for foreign particles that may be embedded in the ways. Freshly oil the way and clean the machine thoroughly. Test dust collector, and observe for excess slack in all lead screws and downfeed screws.

SURFACE GRINDERS (heavy duty-hydraulic)

Clean thoroughly without dismantling. Make certain oil is reaching all recommended spots. Check for leaks in the hydraulic line and test for excess slack in all lead screws and downfeed screws. Any grinding coolant should be replaced and the pump checked to see if it is functioning properly.

3. JIG BORERS and JIG GRINDERS

These machines should be in tiptop shape and it is advisable for the respective operators to thoroughly maintain their machines according to the manufacturer's directions.

4. LATHES

Weekly clean them down with commercial solvents or kerosene. Ways should be checked for nicks and damage. All oil points must be filled and the machine greased wherever necessary. Check the tool saddle and compound for wear because most wear is usually found at this place in the lathe.

5. MILLS and SHAPERS

Same maintenance as the lathes.

6. DRILL PRESSES

Check all belts and spindles for wear and be certain table is perpendicular to spindle. Drill chuck should be checked out for excessive wear and drill press vises checked for damage.

7. TRYOUT PUNCH PRESSES

Properly grease and oil. Clean out any slugs caught in bolster and other depressions about the press. Check all safety devices so they function as required.

8. INSPECTION EQUIPMENT

Micrometers, indicators and surface plates require double checking against the master gages.


Preventive Maintenance

Keeps Costs Low

If the above conditions are met, I am certain that heavy maintenance bills could be avoided. Die makers and machine operators will work with complete confidence when they realize the equipment is safe and reliable. Failure and impending breakdown of equipment can, in this way, be detected in advance and preparations made to correct any malfunctions.

Try also to encourage all employees to report any damage or improper machine performance to the foreman so that on the spot maintenance can be done without having the machine stand idle for the long periods of time needed for major overhauls.

In our plant, we usually make our own minor machine corrections. However, when major maintenance is required we usually have a qualified machinery rebuilder or original equipment serviceman repair the machine.





Punch Multiple Holes in One Operation with REUSABLE

DI-ACRO ADJUSTABLE PUNCHES AND DIES









Di-Acro Adjustable Punches and Dies offer you an inexpensive means of rapid tooling for multiple punching of holes of a variety of shapes and sizes. They will do the job in a fraction of the time it would take using a single station punch press and at a fraction of the cost of standard tooling. All tooling can be arranged in a countless number of patterns so that most multiple hole punching jobs can be accomplished in one operation. Tooling can be reused again and again. Holes can be as close together as ¾" on centers. A template locates your punches and dies accurately. Di-Acro punches and dies are concentric, readily interchangeable. Standard rounds, squares, rectangles, ovals, D's and other shapes in a variety of sizes are available from stock.




Di-Acro Adjustable Punch and Die catalog is complete with detailed instructions and prices on all die sets, punches and dies. Consult the yellow pages of your phone book for the name of your nearest Di-Acro Distributor or write us for your free copy.

Di-Acro Distributor or write us fo

OI-ACRO CORPORATION 604 Eighth Ave. Lake City, Minn.
(Formerly O'Neil-Irwin Mfg. Co.)

Use postpaid card, Circle No. 304




Johnson's Cold Stream stops rust—resists rancidity—reduces causes of dermatitis. These problems start when your coolant gets dirty. Cold Stream stays clean week after week—even on cast iron. Cold Stream gives longest tool life. Finest finishes. Highest speeds and feeds. Best dimensional control. Cold Stream gives you all the performance you pay for. JOHNSON/S WAX

For information, see your local Johnson industrial distributor.

"Cold Stream" and "Johnson's" ere trademarks of S. C. Johnson & Son, Inc., Racine, Wis.

Use postpaid card. Circle No. 305







By Ray W. Ruckel, President Wesson Company

Now Finish Milling With Throw-Aways!

■ About five years ago we completed a rather extensive survey to see what industry thought about throw-away carbide inserts for milling. As might be expected, we found a great deal of interest and some throw-away cutters being used. The applications were all in roughing operations, but the interest was equally high for roughing and finishing.

Within five or six years, the composite survey opinion indicated, the percentage of milling operations done with throw-aways could well be higher than for any other type of operation—including turning, boring and facing. Obviously, the potential savings with throw-aways—eliminating regrinding, reducing set-up time, etc.—would be higher per tool for multiple-point tools such as milling cutters than for single-point tools.


As we all know, the rush to throw-aways for milling cutters didn't live up to industry's own expectations. While there has been a steady, but slow, rise in the number of rough-milling cuts taken with throw-aways, finish milling with these new cutters had run up against a stone wall.

Adjustable feature in milling cutter bodies permits use of throw-aways for finishing cuts

Throw-away cutters just didn't do the job. Further, many plants—disenchanted with throw-aways for finishing—did not adopt them for roughing because they didn't want two different cutter systems and the headaches such a double standard implied. So the cutter industry, including ourselves, continued to sell more conventional cutters than throwaways.

In a nutshell, the problem was variable run-out from insert to insert. For roughing, the run-out wouldn't bother anybody. For finishing, it did.

In trying to solve the problem, cutter manufacturers concentrated their early efforts on greater precision in cutter bodies. Progress with this approach stopped when cutters with practically zero run-out in their bodies still had too much insert variation because of the tolerances on commercially ground inserts. Special grinding of inserts would have been a step backwards, economically, so greater precision of components was cancelled out as a possible solution.




 Cam-shaped pin permits individual axial adjustment for throw-away inserts so cutter run-out can be reduced to tenths. Insert bears against cam section, which can be turned and tightened to position the insert accurately anywhere within a 0.030" range.

The first big step in getting the answer was, as so often happens, a simple one. Since variation of individual inserts was the problem, ability to adjust individual inserts was the solution to finish milling with throwaways. This obvious answer probably was overlooked because nobody wanted to add a lot of adjustment "machinery" to a tool having a simple, clean design.

A practical answer to this came from work being done on boring bars to make them micro-adjustable. In a new design of milling cutters, the traditional fixed-pin used to support an insert is replaced by one with a straight-sided constant-rise-cam section for adjusting, Figure 1. With this arrangement, it is possible to adjust each insert to close limits within an axial range of 0.030". Cutters with over-all run-out in tenths are now feasible and finish milling can be done with commercially ground throw-away inserts.

With a normal amount of care in setting up, such cutters now produce with ease surface finishes of from 60 to 100 microinches—limits which cover the bulk of production-type finish-milling operations. To obtain finer surfaces, greater care is simply exercised in setting up the cutter. This takes time but, since it would be done off the machine, downtime would not be increased.

Admittedly, surface finish is a difficult specification to pin down. At the finer end of the scale, you can't be sure what you are measuring. In many instances, one ends up measuring porosity rather than surface finish. We ourselves have had field reports of production surfaces that



 By replacing one standard insert in a campin cutter with a micro-finishing blade, surface finish can be improved consistently. The special blade has a wiping action to remove cutter feed marks.

consistently measure at 3 microinches but we feel this is a happy accident rather than something to be expected.

Another recent development has, however, lowered the practical surface-finish limits that can be specified and met. By replacing one of the inserts on one of these newer throwaway cutters with a "micro-finishing" blade, Figure 2, cutter marks can be practically eliminated. This blade has a wiping action and, therefore, also permits a higher feed rate on some jobs.

There was still another problem in milling with throw-aways—the restriction on the number of teeth that could be packed into a cutter. Good design, however, has reduced this limitation to the point where cutters

How would you choose... A THREADING MACHINE?



Thread Rolling Machines



LANDMACO Threading Machines



Pipe Threading Machines

Would you consider the results to be obtained first? Or, would you consider how much it's going to cost first? Perhaps your first thought would be to check on the reliability of the manufacturer. Could be you are strictly a name-brand buyer.

Maybe you choose a threading machine because it has been recommended by a satisfied user such as the Landis Machine Company customer who realized a 90% saving in time threading power screws on a LANDMACO Threading Machine.

How you would choose a threading machine of course only you can answer. But doesn't it make good sense to buy from a world leader such as the LANDIS Machine COMPANY? All kinds and sizes of threading machines, thread rolling machines, pipe and nipple threading machines, thread grinders, pipe threading and cutting machines, and automatic coupling tapping machines to meet every threading requirement are available from Landis.

To put the accumulated knowledge of our over 55 years in the threading field to work for you is as close as your phone.

LANDIS Machine Company

WAYNESBORO, PENNSYLVANIA

Use postpaid card, Circle No. 306


with three inserts per inch of diameter are common. We even have some experimental cutters with up to six inserts per inch of diameter, and successful tests with these point toward comparable commercial cutters in the not-too-distant future.

Because many of the major disadvantages of finish milling with throw-aways have vanished is no indication that design has reached the ultimate. In fact, as more throw-away cutters are applied in milling, new and unkown problems will arise.

For example, locating slots on forged crankshafts have been milled with half-side-milling cutters using brazed, inserted blades. Production results were satisfactory but grinding costs were high and many blades broke in use. The answer to this proved to be a special parallelogram

type of throw-away insert, Figure 3. With this, grinding costs dropped to zero, breakage was drastically reduced and production per cutter doubled. Without even considering the savings from fewer and shorter downtime periods for tool changing and adjustment, production savings for one year are one and one-half times as large as the cost of the new cutters.

It is quite possible that the switch to milling with throw-aways may rapidly accelerate now that finishing operations as well as roughing can be successfully converted to throw-aways. Although throw-aways will not necessarily offer the most practical or most economical answer to all production-milling problems, they should always be considered since they inherently offer a chance for large production savings.



 Special parallelogram throw-away inserts in a half-side-milling cutter have only four cutting edges but, in a special milling operation, dramatically reduce production costs while increasing consistency of results.



Field Reports


LIGHT POLES MADE ON TWIN PRESS BRAKES


■ Tying two new press brakes together in tandem has opened up brand new markets for Whiteway Mfg. Co., Cincinnati, outdoor lighting equipment manufacturer. Previously, the company specialized in lighting systems for service stations. The new equipment permits production of light poles up to 40′ long for streets, drive-ins, ball parks, and shopping centers.

Cycling is automatic, once the operator presses a button or engages a treadle. The ram runs down in high speed until just above the work, then automatically shifts into low speed through the bend. When the bend is com-

pleted, the ram returns in high speed.

Both Cincinnati brakes operate either as one unit or individually. Each brake has a rating of 150 tons mid-stroke and 225 tons bottom-stroke; distance between housings, 12½'; bed and ram extensions, 36" each and; total die length, 20'; and throat, 18".





TAPES MAKE DEBUT AT STEEL FABRICATOR'S

■ A Hill numerically controlled beam and column drilling machine installed at R. C. Mahon's Structural Div., Detroit, is said to be the first of its kind in the structural-steel fabricating industry. In its initial application, it is cutting the cost of hole patterns by more than 85% over previous layout, spacer-punching, reaming, and radial-drilling procedures. Patterns are so accurate that bridge reaming on the assembly floor is virtually eliminated.


Basically, the equipment consists of motorized run-in, beam-feed, and runout conveyors; and a high-speed drill having two opposed horizontal spindles and one vertical spindle. One operator controls the entire unit. It can drill 34" holes in steel at feeds up to 30 ipm.

Pushing the cycle start button actuates a tape reader in the control console, and it reads the first block of information on the tape. The machine immediately moves to the command locations, with all motions moving simultaneously. When the beam is in position, part clamps operate. Then, as soon as one of the drills begins to run, the next block of information on the tape is read and stored.

THREAD ROLLING COMBINED WITH TRACER TURNING

■ An automotive component plant rolls the thread on front wheel spindles in the same setup in which the outside of the work is being contoured. Equipment is a Seneca Falls Model LQ automatic tracer lathe fitted with an auxiliary front slide and a Reed thread-rolling attachment. Work is held between centers.

In operation, an overhead tracer slide feeds toward the tailstock, and a rear facing slide feeds toward the headstock. The rear slide carries an indexing tool block which presents a sharp cutting tool for a qualifying cut of the diameter to be threaded, on a short-length second pass. Immediately following the second pass, the thread rolls advance to the center line of the work and then retract in rapid traverse. The front cross slide, which supports the thread rolling attachment, is operated by a barrel type cam revolving through 360°.




FIELD REPORTS continued

RIGHT-ANGLE DRIVE MILLS KEYWAYS

■ Modern Machine Shop, San Francisco, cuts keyways in hard-to-reach sheave bores on a vertical milling machine equipped with an ABL angle drive. The shank of a ½" end mill, used to produce the ¾" by 5/16" keyways, was ground and fitted to the angle drive, which in turn was fitted to the milling machine with a company-designed adapter.






UNLOADER TIED TO PRESS RAM

■ The removal of blanks with a Lahr part unloader is appreciably increasing output of stampings on this 400-ton press, at Chrysler's Mack Avenue Stamping Plant, Detroit. The unloader accommodates four blanking dies of varying width, with a minimum of change-over time. Blanks are delivered to a moving conveyor which discharges them into the storage bin. Scrap is shed on a chute under and through the unloader to a conveyor which carries it to the scrap bin.

Power for operating the unloader is supplied from the press ram which drives twin vertical racks moving the tray in and out of the die area.



DRILL PRESS WITH HOLLOW MILL PROVES FASTER THAN LATHE



Titan Tool Company, Fairview, Pa., turns cold rolled steel faster and at lower cost by using a hollow mill in a standard 17" Delta drill press for work formerly done on a lathe. The work piece, a hand tool to be fitted with a plastic grip, is machined to 3/4" diameter a distance of 2".




TOOL BEAUTY SALON

■ In a Liquamatte wet blasting cabinet installed at Micromatic Hone Corp., Detroit, the company's line of honing tools is given a satiny, clean, and uniform surface. The method utilizes an abrasive slurry thrown from lightweight guns.

KENNEDY SPEAKS OUT FOR MODERNIZATION —see page 164 the precision cutting tool system with built-in micrometer vernier adjustment

MICROBORE



Patented micrometer vernier adjustment! That's the exclusive feature that makes DeVlieg Microbore cutting tools so fast and easy to set. It's the built-in feature that eliminates trial and error cuts; reduces machine downtime and rejects. Micrometer vernier adjustment is also the feature that makes it easy to achieve accuracies impossible or extremely difficult to arrive at with conventional tooling. But that's only part of the story! Write for complete information on Microbore. Introduce yourself to a system of multipurpose tooling designed to deliver the utmost in precision and production from today's high performance machine tools.

DEVLIEG MICROBORE . DIVISION OF DEVLIEG MACHINE COMPANY . FAIR STREET . ROYAL OAK, MICHIGAN

MICROBORE . PRECISION TOOLING CENTER

DEVLIEG MICROBORE SYSTEM

Use postpoid card, Circle No. 307



Here's economy for you, combined with finest quality . . . Nicholson or Black Diamond industrial saw blades—precision made and rugged to give you longer shop life per blade.

Because they're top quality in every respect, because they're Nicholson designed, you use a minimum number of these blades a year...and save valuable labor time each time you use one. You also get clean cutting because each

blade is designed for specific kinds of metal cutting.

Your distributor* carries a full line of these fine Nicholson or Black Diamond industrial blades—hand hacksaw, power hacksaw and band saw. Prove out the economy-through-quality story for yourself. Order a supply today.

* Industrial Distributors provide the finest goods and services in the shortest time. Our products are sold exclusively through them.



NICHOLSON



Nicholson File Company, Providence 1, R. I.

Files . Rotary Burs . Hacksaw and Band Saw Blades . Ground Flat Stock . Industrial Hammers

O PER NICHOLSON CHAIN

Kall Town

Use postpaid card. Circle No. 308



Shop Hints


MODIFIED VISE HOLDS CIRCULAR WORK

By H. J. Gerber

■ A simple adaptation to a milling machine vise broadens its capacity and permits many jobs, such as the circular workpiece shown here, to be safely held.

The sliding jaw block and the vise body have been drilled and reamed to receive four 3/8" dowel pins. The work is placed on the top surface of the vise jaws and is gripped by these pins.

After reaming the holes for the pins, I lapped them so the hardened and ground dowels would slip into place and could be easily removed. Small air release holes were drilled into the side of the vise to the dowel holes to assure bottoming of the pins.



SMALL SPRING SPEEDS PIN GRINDING


By Frederick King

■ In my work as a diemaker I often have occasion to grind pins of small diameter that extend beyond the recommended distance from a collet. Vibration of the pins often causes chatter marks and breakage, or does not give equal diameters for the length of the pin being ground.


I made up a tool to reduce this chatter and it has worked very well, both for my co-workers and myself. It is merely a block of steel with a flat surface and a spring of light springy metal such as beryllium copper. The spring is made from ½" wide, .008"

thick stock approximately 5" long. It is secured to the block by two round head screws.

The spring is bent enough so that when released it just touches the pin to be ground. The pressure is probably less than an ounce. A small groove is put in the end of the spring to keep it from shifting. When checking the diameter with a micrometer, the spring is depressed and need not be removed until the job is finished. Another advantage, the depth of grind can be greatly increased with a subsequent saving in time.



RAPID SETTING T-SLOT CLAMP SPEEDS PRODUCTION



By M. W. Loftus

■ In our shop we have many short run jobs that are strapped with general-use clamping equipment. Set-up and clamping time, which is high for this type of work, has been reduced considerably by adopting the clamps shown here. Several sizes of the clamp have been made up for our tool crib

inventory. We use ¾" bolts in 11/16"
T-slots by putting two small flats on the bolts for clearance. The handknob on the adjusting screw makes it easy to set the height of the clamp and to apply pressure. A slot permits the clamp to slide out of the way when removing the work.

ADHESIVE EXTENDS DIE LIFE

Bonding neoprene strips to the base plates of steel-rule dies at Templet Industries, Inc., Brooklyn, N.Y. The strips, which serve as ejector "springs" to release parts and scrap, are bonded to both metal and wooden base plates. Adhesive (Eastman 910) is a high-strength, quick-setting material, able to withstand the repeated compression resulting from long-run stamping. Only a small quantity of the clean, easy-to-apply material is needed.




POSITIVE STUD DRIVER BACKS OFF EASILY

By Roger Isetts

■ The positive automatic-releasing stud driver shown here is simple and very inexpensive to make, yet it is rigid enough to withstand considerable abuse. It can be used either manually or with a pneumatic wrench.

Basically, the unit consists of a steel adapter that has a tapped hole in one end to fit the stud. The other end is tapped to fit a coarse-thread squarehead set-screw. Slots are milled as shown to provide locking and releasing action.

A dowel pin is pressed into the set screw and as the stud is being driven in, the pin contacts one side of the slot. When reversing, the coarser thread on the set screw quickly backs off until the pin contacts the edge of the slot on the other side. This relieves the jamming effect of the set screw and the stud, and the driver backs-off easily. Since the set screw is already case hardened to about 50 Rc, it can be used as is and it is only necessary to grind off a small portion to get below the hardened surface in order to ream a hole for the pin.



REPACK BEARINGS WITH CLEAN GREASE

By George F. Burnley

When cleaning ball bearings while overhauling equipment, repacking the bearings often involves waste and exposes the bearings to possible contamination from minute specks of dirt.

To cope with the situation, I use a plastic bag, fill it with grease, drop the bearing in, knead the bag to work the grease into the bearing, and then retrieve the bearing with a wire hook.



MAGNETIC BASE STOP FITS MANY JOBS


By Norm Fried

■ Much of our experimental work is of the short run variety, calling for repetition setups. To avoid fixturing where it is not economical, a milling stop is useful. This enables a reference surface or dimension to be located or produced on part after part. We have several commercial units in the shop, but when they are not available, the device shown has proven very useful.

A standard magnetic base is used, the heavy-duty magnet type being preferred. Place the magnetic base on the machine's table as close to the work as is possible. Tighten the base's spindle collar for the greatest rigidity, and bring the ball end of the indicator rod arm into contact with the workpiece reference surface. Tighten the spindle arm clamp and proceed with the necessary machining.

Remove the work and bring the next piece to be machined into light but positive contact with the ball end of the rod. Tighten the vise and the machining cycle can be repeated.

The flexibility and rapid adjustment of this device to a wide variety of jobs have caused much favorable comment throughout our shop.



Standard magnetic base used as mill stop for repetitive work on milling machine.



LITERALLY FLOW THROUGH FERROUS METALS

At Blade Speeds of Almost 3 Miles Per Minute!

Frictional heat softens the metal ahead of the blade, and teeth remove the soft metal chips. Friction sawing is fast, even on the toughest alloys that are very difficult to cut by other methods.

Barnes Friction Cutting Bands are specifically made for this high speed service. Selected steel, specialized heat treatment and the famous Barnes factory-weld with perfectly matched teeth all contribute to the exceptional performance of Barnes Friction Cutting Bands.

Buy from your Barnes Distributor. His stock is maintained to meet your needs and he is always ready to give you prompt and efficient service.


W. O. BARNES CO., INC.

1297 TERMINAL AVENUE

DETROIT 14. MICHIGAN

BARNES-DISTRIBUTOR Teamwork means quality products .
available locally at lowest possible cost.

Use postpoid card. Circle No. 315







ble Presses and double crank Knuckie Joint Presse

BLISS presses than any other make





Eccentric Presses



Rolling Bolster Presser



TORRING TORRING DEA



BLISS is more than a name—it's a guarantee

1166 E. W. BI

E. W. BLISS COMPANY

Hastings, Michigan


Foreign Subsidiories: E. W. Bliss (Canada) Ust., E.W. Bliss (England) Ltd. E.W. Bliss Co. (Paris) France, E.W. Bliss-Henschel G.M.B.H., Düsseldorf, West Germany


PRESSES . ROLLING MILLS . ROLLS . DIE SETS . CONTAINER MACHINERY . CONTRACT MFG. . PUBLIC SAFETS


Use postpoid card. Circle No. 316





Free Literature











5. Turret Drilling Machines. Bulletin on Avey 6- and 8-spindle turret drilling machines with details on speeds, feeds, controls, table sizes, specifications, and dimensional drawings. The Avey Division, Motch and Merryweather Machinery Co., Box 1264, Cincinnati, 1.

6. Automatic Chucking Machine. Bulletin SM45 describing Brown and Sharpe No. 2 automatic chucking machine with specifications, cost-saving features, and typical production examples. Brown and Sharpe Mfg. Co., Providence 1, R.I.

7. High-Speed Steel Drill Sharpener. Folder on new Ampak electrolytic high-speed steel drill sharpener describing capabilities, features, and specifications. Connecticut Special Machine, Inc., Bridge St., Winsted, Connecticut.



(See Number 1)



(See Number 3)



(See Number 5)



(See Number 10)



(See Number 15)



(See Number 18)


- Gage Modifications. Booklet, entitled "Ideas," showing gage modifications, stock components, assemblies, common problems, and their solutions. Boice Gage, Inc., Hyde Park, N.Y.
- 9. Punches, Dies, and Rivet Sets. Catalog 60 describing punches, dies, rivet sets, and compression riveter dies of all sizes and shapes, including stock lists. George F. Marchant Co., 1420 S. Rockwell St., Chicago 8, Ill.
- 10. Threading Machine. Brochure explaining new Thred-O-Matic 22-A pipe, conduit, and bolt threader, with major features and specifications. Collins Machinery Corp., 955 Monterey Pass Rd., Monterey Park, Calif.
- 11. Welding Helmets and Hand Shields. Bulletin 1407 describing Oxweld welding helmets and hand shields, with shade selection and accessories. Linde Co., Division of Union Carbide Corp., 270 Park Ave., New York 17, N.Y.
- 12. Belt Grinder. Brochure on precision belt grinder with applications and specifications. Industrial Machines and Services, Inc., P.O. Box 995, New Britain, Connecticut.
- Cranks, Handles, and Wheels. Catalog of Balcrank products including order numbers and dimensional charts. Balcrank, Inc., Cincinnati 9, Ohio.

- 14. 5- and 10-ton Presses. Catalog on Havir Press-Rite Juniorline 5- and 10-ton presses contains specifications and price lists. Havir Mfg. Co., 444 N. Cleveland, St. Paul 4, Minn.
- 15. Tap Selector. Publication listing over 1,200 sizes and types of stock taps with recommendations and prices. The Hanson-Whitney Co., 169 Bartholomew Ave., Hartford, Conn.
- 16. Isolation of Marhine Vibration. Booklet describing Perf-O-Grip Vibra-Mount methods of isolating transmitted machine vibrations with descriptions of felt mountings and hints on vibration control materials. American Felt Co., 2 Glenville Rd., Glenville, Conn.
- 17. Indicating Snap Gage. Folder showing adjustable indicating snap gage with specifications, ranges, and prices. Mahr Gage Co., 274 Lafayette St., N.Y.C.
- 18. Sanding Discs. Brochure on new filter-backed abrasive discs. Shows use in polishing and blending applications. The Carborundum Co., P.O. Box 337, Niagara Falls, N.Y.
- 19. Cold Repair Systems. Catalog of Metalock cold repair systems for cracked or broken castings and forgings, with description of service. Metalock International, Inc., 36-15 48th Ave., Long Island City 1, N.Y.

Complete your shop with this modern metallizing installation



WIRE GUN-Sprays any metal that can be drawn into wire form.



POWDER GUN-Sprays hard-facing alloys and ceramics in powder form.

Without metallizing, no maintenance or "job" shop can offer the same complete service as the shop that uses industry's low-cost "putting-on" tool.

With modern, low-cost metallizing equipment you can spray carbon steels, stainless, babbitts, brass, bronze, nickel, aluminum, tin, zinc, special hard-facing alloys, including tungsten carbide.

■ Save up to 90% of replacement costs on machine repair jobs ■ Do your awn hardfacing at high speed, low cost ■ Apply long-wearing, corrosion-resistant coatings

A real opportunity for the smaller shop. Thousands of large, well-known companies and shops have been metallizing users for many years, not only in maintenance work but in production applications on original equipment. Now, with modern low-cost metallizing equipment this high-speed "putting-on" tool is within the reach of even the smallest shop.

FREE BULLETIN



Send off the coupon for detailed information—find out how a metallizing installation can pay for itself in a very short time.
No obligation, of course.

METCO INC.

Plame Spray Equipment and Supplies



METCO INC.

1115 Prospect Ave., Westbury, Long Island, N. Y.

Please send me free bulletin on metallizing.

Name

Title

TITLE

Company

Address

City

Zone State

- 20. Tooling Balls. Bulletin on stainlesssteel tooling balls including applications and specifications. Ball Division of Industrial Tectonics, Inc., 3686 Jackson Rd., Ann Arbor, Mich.
- 21. Accordion-Sleeve Protection. Bulletin on Gortite sleeves showing needs, applications, and sizes. A and A Mfg. Co., Inc., 712 S. 12th St., Milwaukee 4.
- 22. Mobile Platform Scale. Catalog 161 on Hydroscale, with mountings, capacities, and prices. Hydroway Scales, Inc., P.O. Box 531, Oakridge Station, Royal Oak, Mich.
- 23. Precision Boring. Bulletin describing new models of Fosdick jig borers. Fosdick Machine Tool Co., Cincinnati.
- 24. Special Work Bench. Brochure on special work bench for metalworking industry including specifications and applications. Dept. WBB, Manzel, 315 Babcock St., Buffalo 10, N.Y.
- 25. Standard Bearing Sizes. Brochure of 1066 standard bearing sizes carried by Amplex, including Oilite and super Oilite lines. Also engineering data on self-lubricating bearings. Amplex Division, Chrysler Corp., Box 2718, Detroit.
- 26. Industrial Diamond Products, Catalog A60 on diamond dressing tools featuring specifications and price lists.

- Diamond Tool Research Co., Inc., 380 Second Ave., New York 10, N.Y.
- 27. Tool Room Grinding. Booklet containing information on grinding and sharpening for tool makers and tool room foremen. Macklin Co., Jackson, Michigan.
- 28. Precision Boring Tools. Catalog on Kamset multi-point precision boring cutters showing shapers, sizes, cartridges, inserts, accessories, and adapters. Adjusting information included. Valenite Metals, Box 205, Royal Oak, Mich.
- 29. Drill Grinder. Bulletin 4000A on features and operations of Farrel-Sellers No. 46 drill grinder. Farrel-Birmingham Co., Inc., Consolidated Machine Tool Division, 565 Blossom Rd., Rochester 10, N.Y.
- 30. Spherical Corners. Catalog 611 describing spherical corner transitions for eliminating square inside corners; charts showing basic corner sizes and metal types included. Conner Steel Products, P.O. Box 25, Southfield, Mich.
- 31. Valve Tap. Bulletin on stationary and rotary valve taps, including diagrams of sizes, shapes, and lengths. Landis Machine Co., Waynesboro, Pa.



(See Number 23)



(See Number 28)



(See Number 31)

S A FACTI

DRILLHEADS


ARE OBVIOUS.

Tremendous scenemics from the use of multiplespindle drillheads are obvious. Drilling one hole at a time cannot be tolerated in this day of automation!

- 1. They are better built and cost no more (Full built bearing construction, hardened gears, spindles and driver, and precision grinding!)
- 2. This means they last longer
- 3. This eliminates down time
- 4. This eliminates production losses
- 5. This drastically reduces drilling costs

Drillheads are designed and produced by engineers

whose experience in this specific field dates back to 1923. This long accumulation of engineering technique and production "know-how" is reflected in our product—a quality tool...selid, substantial and dependable!



CCENTRIC **ADJUSTABLE**

DRILL .

REAM . BORE COUNTER - BORE

COUNTER - SINK

FACE ... with THRIFTMASTER PRODUCTS CORPORATION

Ask NOW for our new catalog!

1020 NORTH PLUM STREET LANCASTER, PENNSYLVANIA Phone Express 2-2101

DORMAN AUTOMATIC REVERSE TAPPERS

THOMSON INDUSTRIES, INC.

Use postpaid card, Circle No. 310

IN 1 MINUTE

WITH A

Minute Man[®]
KEYWAY BROACH
KIT



With one, you can cut a keyway in one minute for as little as one cent by hand with an arbor press. Twenty different kits available from stock for keyways from 1/16" to 1" in any bore from ½" to 3".

Save Time With
STANDARD STOCK
SQUARE BROACHES

Starting with a round pilot you can finish an accurate square hole in one pass in less than one minute. Hexagon and round broaches also available.

The duMont Corp., Greenfield, Mass.

MAIL FREE BROACH CATALOG AND PRICE LIST T describing Square, Hexagon Broaches, Production Type Keyway Broaches and Keyway Broach Kits to

duMont

Booth No. 3215, ASTME Show, M.Y. Collanum May 22-26

Use postpaid card. Circle No. 311

32. Precision Universal Drive. Bulletin describing Gyro-Drive for any power drill, showing mounting, design, and price. Glenwood Gyro-Drive, Inc., Glenwood, Minn.

33. Lathes and Milling Machines. Brochure describing South Bend lathes and milling machines with specifications, prices, and distributors. South Bend Lathe, Inc., 425 E. Madison St., South Bend 22, Ind.

34. Optical Comparators. Book and catalog 6013 on optical comparators and measuring machines with sections on basic measuring, accessories, applications, and electronic components. Jones and Lamson Machine Co., Springfield, Vt.

35. Machine Tool Motor-Generators. Booklet 3064 on General Electric's machine tool motor-generators for feed drive power-supply systems with discussion on use with nominal- and variable-voltage outputs, operating characteristics, and typical connections. Performance and designs included. General Electric Co., Schenectady 5, New York, N.Y.

36. "Barrel Finishing." Booklet 501 describes various barrel-finishing processes and equipment, with recommendations for abrasive shapes and sizes. Also practical suggestions on operation procedures. Norton Co., Worcester 6, Mass.

JIG GRINDING and JIG BORING

to your specification

At your disposal: Our sub-contract jig boring department, one of the best equipped in the East.

A. K. TOOL CO., INC.

Telephone: ADams 2-7300 Digby 9-1445, N Y C

Use postpaid card. Circle No. 312

MACHINE and TOOL BLUE BOOK






BENCO

CARBIDE PUSHER PADS

also have these important advantages
REDUCE SCRAP • CUT "DOWN TIME" when used

with BENCO MODEL "A" MASTER or

DIAL ADJUSTABLE TENSION MASTER PUSHERS



Benco Carbide Pusher Pads used in combination with Benco Master Pushers are the most economical tooling for your automatics and the most productive, too! Try them and see. Write for catalog today!



BENCO COLLET MANUFACTURING CO.

Cleveland 14, Ohio

Use postpoid card. Circle No. 313



(See Number 38)

- 37. Tool Components and Their Applications. Booklet clarifies concept of standardized tool application. Examples of tools for use with jigs, fixtures, other tools, and dies. Time-saving ideas. PIC Design Corp., 477 Atlantic Ave., East Rockaway, L.I., N.Y.
- 38. Variable-Speed Drives. Bulletin 551 on variable-speed drives showing principle of operation, traction, control, and selection. Graham Transmissions, Inc., Menomonee Falls, Wis.
- 39. A Guide to Better Centers. Brochure includes purpose, errors, measurement, correction, and requirements of centers. Common problems of centers and their solutions illustrated. High Precision Products, Westfield, N.J.
- 40. Numerical Control System. Bulletin 157-2 on Natco's numerical control system with types and specifications. National Automatic Tool Co., Richmond, Ind.



NEW! Self-Centering 5C Collet Stop Quick friction adjustment. Stays in fixed position. Will not distort collet. Will not move back. Also available for other collets and spindles. 30 Days Free Trial. Several Territorice Open for Dis-

Write for Bulletin

THE BYSTROM COMPANY 6106 Park Ave. South Minneapolis 17, Minn.

Use postpaid card. Circle No. 329

- 41. Straight Grinders. Bulletin on airpowered straight standard and heavyduty grinders and buffers. Also includes specifications on accessories. Description of internal- and external-bladed grinders. The Rotor Tool Co., 26300 Lakeland Blvd., Cleveland, Ohio.
- 42. A. S. A. Bushing Symbols. Catalog of recently adopted American Standards Assoc. drill bushing sizes, symbols, and prices, as well as ACE bushing information. ACE Drill Bushing Co., Inc., 5407 Fountain Ave., Los Angeles.

 43. Ceramic Cutting Tools. Catalog 960 describing Stupalox ceramic cutting tools, their dimensions, and prices.
- 44. Setups. Catalog 1161CJ on ways to make setups easier and quicker with specifications and prices on Universal equipment. Universal Vise and Tool Co., Parma, Mich.

Dept. BMD. The Carborundum Co.,

P.O. Box 337, Niagara Falls, N.Y.

- 45. Vapor-Spray-Vapor Degreasers. Bulletin 21 describing degreasers, including principle of operation, solvent cycles, and specifications. Phillips Mfg. Co., Inc., 3475 W. Touhy Ave., Chicago.
- 46. Groove Location and Depth Gaging. Flyer on model B1400 indicator with specifications and prices. Reli-A-Chek Corp., 2614 Industrial Way, Santa Maria Airport, Santa Maria, Calif.
- 47. Abrasive Belt Grinder. Catalog 100 on Loungway belt grinder, including operations, design, and specifications. Eastern Machine Screw Corp., New Haven 6, Conn.
- 48. Boring Head and Fly Bar. Bulletin 14 on boring head including shank models and prices. Also specifications on fly bar. Lido Tools, P.O. Box 403, Costa Mesa, Calif.
- 49. Tool Holder. Flyer on all-purpose adjustable self-aligning tool holder with specifications, sizes, and models. Nu-Screw Machine Tool Co., 1006½ E. South St., Anaheim, Calif.

50. Solid Carbide Tools. Catalog on carbide tools with types, specifications, and speed charts included. Dexco Corp., Raymac Division, 15778 Telegraph Rd., Detroit 39, Michigan.

51. Hoppers. Bulletin 34 shows features and operation of new elevator hoppers. Count-O-Matic Inc., Division of U. S. Engineering Co., 40-24 22nd St.,

Long Island City 1, N.Y.

52. Deburring and Chamfering Grinders. Two bulletins describing features and operation of deburring and chamfering grinders for spur and helical gears, as well as bevel gears. Denham and Co., 925 Book Bldg., Detroit 26, Michigan. 53. Hole Relation Gage. Bulletin M12 on "Con-Chek" gages, including models, ranges, and specifications. Mayes Tool Co., 26514 W. Seven Mile Rd., Detroit. 54. Arc Welding Stainless Steel, Bulletin explains electrodes for different stainless steels, including deposit properties. The Lincoln Electric Co., Cleveland 17, Ohio.

55. Tips and Dies. Pamphlet on fourteen multi-gun welders with methods for mass production of fabricated parts. The Federal Machine and Welder Co., Warren, Ohio.

56. Engineered Production. Brochure on Sundstrand numerically-controlled machine tools describing positions, types, and control. Production savings included. Sundstrand Machine Tool, Belvidere, Ill.

57. Carbide Cutting Tools. Brochure 3-61 showing Wesson standard and special carbide turning, milling, and boring tools. Annotation on Wesson catalog. Wesson Co., 1220 Woodward Hgts Blvd., Ferndale 20, Calif.

58. Welding, Brazing, and Soldering Alloys and Fluxes. Wall Chart covering All-State welding, brazing, and soldering alloys and fluxes for use with common base metals. Description of aluminum joining alloy. All-State Welding Alloys Co., Inc., White Plains, New Jersey.

PRECISION TOOL POST GRINDERS

Featuring the circumferentially adjustable spindle assembly—

Mount on any machine tool—In any position—For the precise finishing of any material including ceramics—



Patented circumferentially adjustable spindle mounting makes it the only Tool Post Grinder permitting use of the grinding wheel on right or left side, front or rear of the motor unit.



- . 14 Models 1/4 to 1 H.P.
- . Spindle Speeds to 50,000 RPM
- . Use Grinding Wheels 1/8" to 6"
- Permanent Lubrication

Write for new catalog

THE MCGONEGAL MFG. CO.

129 MOZART STREET
EAST RUTHERFORD, NEW JERSEY

Telephone GEneva 8-2313
Use postpoid card. Circle No. 317



(See Number 38)

- 37. Tool Components and Their Applications. Booklet clarifies concept of standardized tool application. Examples of tools for use with jigs, fixtures, other tools, and dies. Time-saving ideas. PIC Design Corp., 477 Atlantic Ave., East Rockaway, L.I., N.Y.
- 38. Variable-Speed Drives. Bulletin 551 on variable-speed drives showing principle of operation, traction, control, and selection. Graham Transmissions, Inc., Menomonee Falls, Wis.
- 39. A Guide to Better Centers. Brochure includes purpose, errors, measurement, correction, and requirements of centers. Common problems of centers and their solutions illustrated. High Precision Products, Westfield, N.J.
- 40. Numerical Control System. Bulletin 157-2 on Natco's numerical control system with types and specifications. National Automatic Tool Co., Richmond, Ind.



NEW! Self-Centering 5C Collet Stop Quick friction adjustment. Stays in fixed position. Will not distort collet. Will not move bask. Also available for other collets and spindles. 30 Days Free Trial. Several Territories Open for Distributors.

Write for Bulletin

THE BYSTROM COMPANY \$106 Park Ave. South Minneapolis 17, Minn.

Use postpaid card. Circle No. 329

- 41. Straight Grinders. Bulletin on airpowered straight standard and heavyduty grinders and buffers. Also includes specifications on accessories. Description of internal- and external-bladed grinders. The Rotor Tool Co., 26300 Lakeland Blvd., Cleveland, Ohio.
- 42. A. S. A. Bushing Symbols. Catalog of recently adopted American Standards Assoc. drill bushing sizes, symbols, and prices, as well as ACE bushing information. ACE Drill Bushing Co., Inc., 5407 Fountain Ave., Los Angeles.

 43. Ceramic Cutting Tools. Catalog 960
- 43. Ceramic Cutting Tools. Catalog 960 describing Stupalox ceramic cutting tools, their dimensions, and prices. Dept. BMD, The Carborundum Co., P.O. Box 337, Niagara Falls, N.Y.
- 44. Setups. Catalog 1161CJ on ways to make setups easier and quicker with specifications and prices on Universal equipment. Universal Vise and Tool Co., Parma, Mich.
- 45. Vapor-Spray-Vapor Degreasers. Bulletin 21 describing degreasers, including principle of operation, solvent cycles, and specifications. Phillips Mfg. Co., Inc., 3475 W. Touhy Ave., Chicago.
- 46. Groove Location and Depth Gaging. Flyer on model B1400 indicator with specifications and prices. Reli-A-Chek Corp., 2614 Industrial Way, Santa Maria Airport, Santa Maria, Calif.
- 47. Abrasive Belt Grinder, Catalog 100 on Loungway belt grinder, including operations, design, and specifications. Eastern Machine Screw Corp., New Haven 6, Conn.
- 48. Boring Head and Fly Bar. Bulletin 14 on boring head including shank models and prices. Also specifications on fly bar. Lido Tools, P.O. Box 403, Costa Mesa, Calif.
- 49. Tool Holder. Flyer on all-purpose adjustable self-aligning tool holder with specifications, sizes, and models. Nu-Screw Machine Tool Co., 1006½ E. South St., Anaheim, Calif.

50. Solid Carbide Tools. Catalog on carbide tools with types, specifications, and speed charts included. Dexco Corp., Raymac Division, 15778 Telegraph Rd., Detroit 39, Michigan.

51. Hoppers. Bulletin 34 shows features and operation of new elevator hoppers. Count-O-Matic Inc., Division of U. S. Engineering Co., 40-24 22nd St.,

Long Island City 1, N.Y.

52. Deburring and Chamfering Grinders. Two bulletins describing features and operation of deburring and chamfering grinders for spur and helical gears, as well as bevel gears. Denham and Co., 925 Book Bldg., Detroit 26, Michigan. 53. Hole Relation Gage. Bulletin M12 on "Con-Chek" gages, including models, ranges, and specifications. Mayes Tool Co., 26514 W. Seven Mile Rd., Detroit. 54. Arc Welding Stainless Steel. Bulletin explains electrodes for different stainless steels, including deposit properties. The Lincoln Electric Co., Cleveland 17, Ohio.

55. Tips and Dies. Pamphlet on fourteen multi-gun welders with methods for mass production of fabricated parts. The Federal Machine and Welder Co., Warren, Ohio.

56. Engineered Production. Brochure on Sundstrand numerically-controlled machine tools describing positions, types, and control. Production savings included. Sundstrand Machine Tool, Belvidere, Ill.

57. Carbide Cutting Tools. Brochure 3-61 showing Wesson standard and special carbide turning, milling, and boring tools. Annotation on Wesson catalog. Wesson Co., 1220 Woodward Hgts Blvd., Ferndale 20, Calif.

58. Welding, Brazing, and Soldering Alloys and Fluxes. Wall Chart covering All-State welding, brazing, and soldering alloys and fluxes for use with common base metals. Description of aluminum joining alloy. All-State Welding Alloys Co., Inc., White Plains, New Jersey.

PRECISION TOOL POST GRINDERS

Featuring the circumferentially adjustable spindle assembly—

Mount on any machine tool—In any position—For the precise finishing of any material including ceramics—



Patented circumferentially adjustable spindle mounting makes it the only Tool Post Grinder permitting use of the grinding wheel on right or left side, front or rear of the motor unit.



- . 14 Models 1/8 to 1 H.P.
- Spindle Speeds to 50,000 RPM
- · Use Grinding Wheels 1/8" to 6"
- Permanent Lubrication

Write for new catalog

THE McGONEGAL MFG. CO.

EAST RUTHERFORD, NEW JERSEY Telephone GEneva 8-2313

Use postpaid card. Circle No. 317



News of Industry

KENNEDY SPEAKS OUT FOR MODERNIZATION

"I shall propose to the Congress a new tax incentive for businesses to expand their normal investment in plant and equipment."

President John F. Kennedy

M odernization of plant facilities, replacement of productive equipment and capacity to produce are at long last occupying the attention of Washington. The President showed a commendable awareness of three major problems which must be attacked if our country is to remain strong: economic growth, plant modernization and price stability.

Before a packed house, he expressed thoughts every business held dear, and which every businessman had been trumpeting for years. "Capacity operation is the key. No matter what other arguments or stimulants are used, the incentives for investing new capital to expand manufacturing plants and

equipment are weak as long as manufacturers are operating at less than 80% of capacity. From 1950 to 1958 we put only one sixth of our total output into capital formation, while Japan, Germany, Italy, the Netherlands, Canada, and Sweden were all investing one fifth or more of their total output in capital goods. So it is not surprising that each of these and other nations over the past several years has surpassed us in average annual rate of economic growth."

In speaking of plant modernization the President said, "New plant investment not only means expansion of capacity; it means modernization as well. Gleaming new factories and headlines about automation have diverted our attention from an aging industrial plant. Obsolescence is slowing down our growth, handicapping our productivity, and worsening our competitive position abroad."

^{*}President John F. Kennedy's address to the luncheon meeting of the National Industrial Conference Board, Washington, D.C., February 13, 1961.

THE U.S. IS "FALLING BEHIND"

"Nothing can reverse our balanceof-payments deficit if American machinery and equipment cannot produce the newest products of the highest quality in the most efficient manner. The available evidence on the age of our industrial plant is unofficial and fragmentary; but the trend is unmistakable—we are falling behind.

"The average age of equipment in American factories today is about nine years. In a dynamic economy, that average should be falling, as new equipment is put into place. Instead, the available evidence suggests that it has been slowly rising. Private surveys of machine tools used by manufacturers of general industrial equipment found less than half of these tools over ten years old in 1949, but two thirds over that age in 1958. Nineteen per cent of our machine tools were found to be over twenty years old.

"Meanwhile, other countries have been lowering the average age of their fixed capital. The German example is the most spectacular: their proportion of capital equipment and plant under five years of age grew from one sixth of the total in 1948 to two fifths in 1957.

"All of these facts point in one direction: We must start now to provide additional stimulus to the modernization of America's industrial plant. Within the next few weeks, I shall propose to the Congress a new tax incentive for businesses to expand their normal investments in plant and equipment."

PRICE STABILITY AND INFLATION

The President realizes that the government is almost without "direct and enforceable powers over the central problem." He continued, "A free government in a free society has only a limited influence over prices and wages freely set and bargained for by free individuals and enterprises. And this is at it should be if we are to remain free.

"Nevertheless, the public interest in major wage and price determination is substantial. Ways must be found to bring that public interest before the parties concerned in a fair and orderly manner. For this reason, I have announced my determination to establish a Presidential advisory committee on labor-management policy, with members drawn from labor, management, and the public. I want this committee to play a major role in helping promote sound wage and price policies, productivity increases, and a betterment of America's competitive position in world markets. I will look to this committee to make an important contribution to labor-management relations, and to a wider understanding of their impact on price stability and economic health. And in this undertaking, I ask and urge the constructive co-operation of this organization and its members.

"Economic growth, plant modernization, price stability—these are all intangible and elusive goals. But they are all essential to your success, and to the success of our country. Initiative, innovation, and hard work will be required, on your part and on ours."

New! ONLY . . .

BUYS THIS COMPACT MIST COOLANT UNIT



Especially designed for small precision machinery used for drilling, tapping, sawing, grinding, etc. Up to 500% savings through increased cutting speeds and tool life. Check these quality features and write for complete details.

- -compact . . . measures 3" x 5"
- -separate air and coolant controls
- · -convenient mounting stud
- · -attaches to existing shop girline
- · -shatter-proof 8 oz. reservoir
- · -neoprene flexible coolant line
- .-magnetic nozzle holder positions anywhere
- .-controlled discharge

Larger Types and Capacities Available. SEND FOR BULLETIN 37

RICO FUSE MEG.

Use postpaid card. Circle No. 334

RODNEY DAVIS CO. MOVES

Rodney Davis Gear Co. has moved to 235 W. Dauphin St., Philadelphia. President Jon T. Moore says that \$150,000 worth of new turret lathes. saws, and other machine tools have been leased from Jones and Lamson Machine Co., Springfield, Vt.,

NEW PLANT FOR DIEBEL

Diebel Die and Manufacturing Co., formerly located on Irving Park Rd., Chicago, has begun operating in a new plant in Morton Grove, Ill. The firm, founded in 1937 in Chicago, will continue to specialize in manufacturing complex parts and mechanisms

SULLIVAN NAMED REP. ON WEST COAST

Oberg Mfg. Co., Inc., Freeport, Pa., carbide die manufacturer, has named Sullivan Assoc., Glendora, Calif., as the company's West Coast sales representative.



FREDDY FEDERAL Checks specifications every step of the way on every job! Our skilled short run stampings craftsmen and specialized equipment are geared to meet tough design problems . . . close tolerances. Whether your order is for a few pieces or in quantity -you'll receive uniform quality precision parts . delivered on time . . . right up to specil Send us your print today for a quick airmailed quotation.

3 PLANT LOCATIONS EDERAL

FEDERAL TOOL & MFG. CO.
3610 Alabama Ave. Minneapolis 10, Minn. WEst 9-7843
FEDERAL STAMPING CO.
7310 Atoli Ave., N. Hellywood Calif. TRiangle 7-0542
FEDERAL SHORT RUN STAMPING, INC
910 Lyell Ave., Rochoster 6, N.Y. Clearwater 4-9823

Use postpaid card, Circle No. 444

MACHINE and TOOL BLUE BOOK

\$10 MILLION EXPANSION AT CERRO de PASCO SUBSIDIARY

The \$10 million expansion program at Cerro de Pasco Corp.'s Fairmont Aluminum Co. in Fairmont, W.Va., is progressing, and the new facility is expected to be in operation sometime in the spring of 1961. This will make the aluminum rolling mill one of the largest of its type in the country. Coil and sheet output will be increased nearly 150% because of the expansion.

TEC ENGINEERING TO REPRESENT S-P MANUFACTURING IN INDIANA

TEC Engineering Corp., Logansport, Ind., has been named factory representative in Indiana of S-P Manufacturing Corp., Solon, Ohio, and will offer a complete line of standard air and hydraulic cylinders, high-pressure hydraulic cylinders, valves, and accessories.

ULTRASONIC INDUSTRIES MOVES


Ultrasonic Industries Inc., formerly located at Albertson, Long Island, N.Y., has relocated at Engineers Hill, Plainview, L.I. The new facility will house sales, engineering, and manufacturing departments, as well as the Robot Metalcraft Corp., a subsidiary which specializes in precision sheetmetal fabrication.

HOPE RURBER DISTRIBUTES HANNIFIN CYLINDERS, VALVES

Hope Rubber Co., Inc., 40 Commercial St., Fitchburg, Mass., has been franchised to distribute Hannifin air and hydraulic cylinders and air control valves. Hope has been an active distributor for Parker industrial tube and hose fittings as well as Crown air regulators, filters and lubricators, also Parker-Hannifin products.

CHROMALLOY CORP. BUYS SHUNK

The Chromalloy Corp., New York, has purchased Shunk Mfg. Co., Bucyrus, Ohio, maker of replaceable blades and cutting edges for earth-moving, road construction, road maintenance, and snowplow equipment.



THE MOST FOR YOUR "ROCKWELL TESTING" DOLLAR!

Clark Hardness Testers are guaranteed accurate for all "Rockwell Testing". Clark's exacting workmanship in the production of penetrators, testing blocks, anvils, and other accessories pays off in exceptional accuracy on the job. No wonder the low cost surprises our first-time customers. Clark Instrument, Inc., 10202 Ford Road, Dearborn, Michigan.


FREE REFERENCE BOOK

All information about hardness testing in easy-to-read text with many illustra-tions. Just write "Send Book" on your letterhead. Description and prices for Clark Hardness Tester and free Hardness Conversion Chart



Missile-Age Accuracy

Use postpaid card. Circle No. 318



JERED TO BUILD ELEVATOR ENGINES FOR NEW AIRCRAFT CARRIER

Pictured above is one of the aircraft elevator engines built by Jered Industries, Inc., Birmingham, Mich., for the aircraft carrier, Iwo Jima. Jered will also build four hydraulic elevator engines for the Navy's newest supercarrier, the CVA-66, a modified version of the Forrestal class. These engines will be complete with electro-

mechanical control systems for use in raising and lowering aircraft between the hangar and flight decks.

The aircraft handling equipment will be built at a total cost of approximately \$2,000,000 and each elevator is expected by the company to lift more than 350,000 lbs., which is twice the amount capable of the pictured unit.

CHEMETRON CORP. BUYS DETROIT CHEMICAL CO.

Chemetron Corp. of Chicago has purchased the Northwest Chemical Co. of Detroit. The company will become a part of the Chemical Products Division of Chemetron. Products of the 28-year-old Detroit firm include metal cleaners, acid addition agents, phosphate coatings, paint strippers, and other chemicals for conditioning ferrous and non-ferrous metals before plating, welding, enameling or painting.

Northwest Chemical Co.'s plant and offices will remain at 9310 Roselawn. Harold J. McCracken, B. F. Lewis, and Helen M. Morell, officers and founders, will retain charge of operations.

SPECIAL DIE-SET FACILITIES AT PRODUCTO PLANT IN CHICAGO

Philip R. Marsilius, executive vicepresident of **Producto Machine Co.** has announced that new manufacturing facilities for special die sets are now in operation at the company's Chicago plant.


IDEAL DRIVING CENTERS SOLD

The entire inventory of Ideal driving centers of Ideal Industries, Inc., Sycamore, Ill., has been purchasd by Power Grip, Inc., Rockfall, Conn., manufacturer of lathe and screw machine accessories. The centers will be marketed under the Power Grip name.

UNITIZED TOOLING for HOLE PUNCHING and NOTCHING



Unipunch Tooling System produces custom setups with standard units for punching and notching sheet metal. Serup units outside press; slide onto press bed; and produce parts with first stroke of rammolbing altached to press ram... mo press downtime.







Unipunch self-contained Units permanently align punches and dies—me adjustments. Units are used and reused in press and preas brake set-ups—no "dead" storage and no special capital equipment required for production of parts from shoet metal, plates, augles, channels or extrusions.

Set-up of Unipunch Series "B" Hole Punching and Notching Units on a T-slotted plate. Series "B" Units punch and notch up to 1/4" thick mild steel.



FREE CATALOGS



PUNCH PRODUCTS Corporation

386 BABCOCK ST., BUFFALO 6, N. Y.
Exclusive Canadian Licensee: Wm. F. Beatlie Associates. Hamilton, Ont.

Use postpoid card. Circle No. 319

PRATT & WHITNEY ANNOUNCES TRADE-IN PLAN ON MACHINES

"For too long, machine tool builders have ignored the needs of their customers to dispose of surplus machinery when buying new equipment," explained Paul Stanton, vice-president-marketing for Pratt & Whitney, in announcing details of a machinery trade-in plan.

Effective immediately, according to Stanton, his company will begin accepting used or surplus machine tools of any manufacture as part payment or for credit toward the purchase of new Pratt & Whitney products.

A new corporate unit of Fairbanks Whitney, P&W's parent company, has been established to handle these tradeins. It has been named the Machinery Trading Corporation. Stanton emphasized the fact that P&W is not in the used machinery business and P&W personnel would not be involved in the sale of used machinery. However, the two Fairbanks Whitney units will work closely together to give one-stop service.

WARNER ELECTRIC HAS JAPANESE SUBSIDIARY

Warner Electric Brake & Clutch Co., Beloit, Wis., has established a Japanese subsidiary, Warner (Japan) Ltd. of Tokyo. The subsidiary is 85% owned by Warner Electric and 15% owned by Shinko Electric Co., Ltd. Under the agreement, the subsidiary will license Shinko Electric to manufacture and sell Warner Electric brakes and clutches throughout the Far East.

ECLIPSE REPRESENTED IN CANADA

Alexander Tools, Ltd. at Montreal, Quebec, and Barmac Supplies, Ltd. at Toronto, Ontario, have been appointed Canadian representatives for Eclipse Counterbore Co., Detroit, producer of end cutting tools.

SANDVIK HAS NEW CHICAGO OFFICES

Sandvik Steel, Inc., Fair Lawn, N.J., has moved its Chicago branch office to the company's new building at 7520 N. Long Ave., Skokie, Ill. The office will continue to sell and service Sandvik specialty cold-rolled spring steels, Coromant carbide tooling, steel-belt conveyors, power springs, hand saws and tools.

NEW GEAR RESEARCH BUILDING

Philadelphia Gear Corp., King of Prussia, Pa., manufacturer of precision gears, industrial gears and power transmissions, has begun construction of a new gear research building and pattern shop.

NEW UNIT FOR SHARON STEEL

Sharon Steel Corp., Sharon, Pa., has broken ground for a new vacuum stream droplet degassing unit which company officials say will give customers high quality steel in all sizes and grades.



HEPPENSTALL GETS AWARD

Robert B. Heppenstall, president of the Medvale-Heppenstall Co., Philadelphia, has been awarded the William Hunt Eisenman Medal for service, devotion, and foresight in the metals industry by the American Society for Metals.

LEVINS NAMES REPRESENTATIVES

Russell-Holbrook and Henderson, New York, have agreed to be exclusive representatives in New England for Louis Levin and Son, Inc., Culver City, Calif., manufacturer of high precision lathes and micro-drilling equipment.

NEW CENTER FOR CARPENTER

Carpenter Steel Co., Reading, Pa., has opened a new \$300,000 mill-branch warehouse and specialty steel service center in Los Angeles, thus tripling service to that area.

DORSEY GAGE CO. COMPLETES PLANT ADDITION

The Dorsey Gage Co., Inc., Hyde Park, N.Y., manufacturers of precision gages, measuring instruments, and related products, has completed an addition that will double its facilities and manufacturing space. Allen Linderholm will be in charge of engineering and research, as well as the development of new products. He comes to the firm with approximately 20 years' experience in gage engineering design and production background.

MATTICKS NAMED AS ELGIN WHOLESALER

Abrasives Division of Elgin National Watch Co., Elgin, Ill., has appointed the Matticks Co., 4176 E. Pacific Way, Los Angeles, as western wholesaler for Golden solid carbide tools.

FAST, CLEAN, ECONOMICAL HEAT

Provides high, fast heat for metal bending, metal forging, occasional heat treating, metal forming and preheating. Clean, efficient, equipped with four burners. Two end burners have separate shutoff valves, may be turned off for smaller jobs. Operates economically on any type of gas. Convenient gas-air adjustment panel. Adjustable swinging refractory lid. Adjustable front rack to support long pieces and hold tools. Solenoid safety valve turns gas off automatically when blowers are turned off. High temperature, insulated firebox, 5½" by 7½" by 27". Maximum 425,000 BTU input.

JOHNSON

NO. 133 FORGE FURNACE

WRITE TODAY FOR FREE

JOHNSON CATALOG

Johnson

Gas Appliance

Company

570 E Avenue

N.W.

Cedar Rapids,

lowa

Use postpaid card. Circle No. 232

F.O.B. Factory \$246.00.

Appointments and Promotions

Personnel Changes . . . Executive and Production



C. S. Beshore



R. R. Winn



J. S. Howey



J. K. Rye

The Yoder Co., Cleveland, has named Eugene L. Mackey vice-president in charge of engineering . . . Norton D. Skinner was appointed manager of technical services, and Albert R. Mc-Callum was made special automotive consultant for the Clearing division of U. S. Industries, Inc., Chicago . . . The Yale and Towne Mfg. Co., Philadelphia, named Charles S. Beshore manager of the Materials Handling division . . . Robert C. Jacobs was promoted to general manager of the Automotive Gears division of Eaton Mfg. Co., Cleveland . . . National Twist Drill and Tool Co.. Rochester, Mich., appointed Rex F. Supernaw, chief metallurgist . . . Henry L. Burghoff was made director of research and development for Chase Brass and Copper Co., Waterbury, Conn. . . . Birdsboro Corp., Birdsboro, Pa., appointed Harold C. Sproule manager of the Hydraulic division of the Reading, Pa. plant . . . Donal R. Whitney was named quality-control manager for Whitney Chain Co., Hartford, Conn. . . . Ex-Cell-O Corp., Detroit, appointed Henry Lapeza controller and Frank J. Rogers to head its internal audit department. Russell D. Hughes was made assistant general manager of the company's Cadillac Gage division at Costa Mesa, Calif. . . . John S. Howey and Edgar E. Jones were appointed factory representatives for Rotor Tool Co., Cleveland . . . Bendix Corp., Detroit, named Roy R. Winn Great Lakes regional manager of the Industrial Controls section . . . Bernard Kardon was appointed director of engineering at Ultrasonic Industries, Inc., Plainview, N.Y. . . . Rotor Tool Co., Cleveland made Thomas L. Whitehouse field engineer . . . R. C. Dublin was elected secretary of the High Speed Hammer Co., Inc., Rochester, N.Y. He succeeds R. F. Ahlheim who has retired . . . Also



Donal R. Whitney



E. E. Jones



T. L. Whitehouse



K. R. Beardslee



"645" BETTER SIX WAYS



In EVERY category than ANY machine in its class • 25½" of ram travel • Spindle to table and spindle to column—Range greatly exceeds competitive machines, PLUS many other dimension advantages.

• GREATER ACCURACY-

Ground lead screws • Hand scraped ways • Overrin stays in one plane • Locks without distortion • ool room accuracy in manufacture of components.

GREATER VERSATILITY—

Head tilts 45° forward and back, rotates 360° on ram
• Turret rotates 360° on column • Power assembly rotates 360° around spindle • Many other features.

• GREATER EFFICIENCY-

Convenient controls • 9 spindle speeds, 3 power spindle feeds (up or down) • 4-way head handles any compound work angle • Greater work area.

• GREATER DURABILITY-

Index quality throughout for long trouble-free life.

PROVEN ACCESSORIES AND EXTRA EQUIPMENT—

Ask for catalog and prices.

WRITE FOR YOUR COPIES OF 4-PAGE DESCRIPTIVE BROCHURES PACKED WITH FACTS ON NEW MODEL "645" HEAVY DUTY "53" VERTICAL MILL AND

MODEL "60" HORIZONTAL MILL.

INDEX

MACHINE COMPANY 540 N. MECHANIC ST. PHONE ST 2-6737 JACKSON, MICHIGAN



balance ROTATING PARTS faster... easier...

Supersensitive Anderson Balancing Ways (Stand or Pillow Block Type) will static-balance rotating parts easier, faster, more accurately. No setup, no leveling, no centering. Glass-hard spindles and bearings prevent wear or ball-bearing indentations when balancing heavy work. Superior accuracy lasts throughout long life. Proved and preferred over 40 years.



Anderson Hand Scrapers are: (1) faster cutting, (2) easier to use, (3) just the right spring, (4) palm fitting grip, (5) 18" - 20" - 22"

lengths. Saves costly regrinding.

\$6.75 (18") with high speed blades

\$9.85 (18") with carbidetipped blades

\$1.75 for rubber bumper shown below



Write for Bulletin 4-5
ANDERSON BROS.
MFG. CO.

Rockford, III.

Use postpaid card. Circle No. 326








T. W. Clork

retiring is Kenneth R. Beardslee as consultant to the metallurgical products department of General Electric Co., Detroit . . . USI Robodyne division of U. S. Industries, Inc., Silver Spring, Md., announces the appointment of John D. Goodell as president and general manager . . . John K. Rye has been elected president of F. Jos. Lamb Co., Detroit . . . The Braeburn Alloy Steel Corp., Pittsburgh, appointed Charles W. Schuck executive vice-president . . . Thomas W. Clark has been named president and general manager of the Threadwell Tap and Die Co., Greenfield, Mass. Electric Autolite Co. has appointed J. B. Driscoll manager of production at its Decatur. Ala., plant . . . John D. Goodall has been made general manager of Ball division of Industrial Tectonics, Inc., Ann Arbor, Michigan.



J. D. Goodall

Size Control Co., a division of American Gage and Machine Co., Chicago, appointed Peter J. Sommer vice-president and general manager, and Thomas



TAP GAUGE PERFECT PARTS Everytime!

NEW LEAD SCREW TAPPER with PUSH BUTTON CONTROL

Now you can tap any quantity of practically any material, with absolute precision, without rejects, without stripped threads or distortion. Tests have shown it produces parts that pass 100% inspection -100% acceptable! The secret is in the tap control mechanism which feeds the tap automatically without any pressure. The Lead Screw controls the tap and guides it steadily through each cycle, guaranteeing supreme accuracy. In addition, it offers convenient 5-way operation, pushbutton and foot control for complete cycle or jog, automatic (without foot or hand controls) or with switch fixture for full cycle. Either way, you get uniformity, speed and precision that's unparalleled!

SEND FOR FREE BROCHURES

giving the full story on this amazing new tapping unit and the complete line of regular tappers. See how you can enjoy higher quality tapping, less tap breakage, parts spoilage and increase tapping efficiency—for less cost! Write today!



Procunier --

PROCUNIER SAFETY CHUCK CO. 14 S. Clinton St., Chicago 6, III.

Gentlemen: Please rush me your FREE brochures on the new Lead Screw Tapping Attachment and your line of regular tappers.

Name

Zone_

Use postpaid card. Circle No. 322

Address



blind screw holes—make savings in "wage-dollars-per hour" of your expensive honds on every job. A die-and-tool maker's tool with many other applications for die makers and machinists. A set of 6 Hardened Screws nested in combination holder and wrench—no other tools needed. Get more work now—save money tool

HEIMANN MFG. CO. . URBANA, OHIO

Use postpaid card. Circle No. 327

J. Owen vice-president of manufacturing . . . Roland C. Crans was promoted to assistant chief engineer of Holcroft and Co., Detroit . . . J. Algot Johnson has been named vice-president of research and engineering of the Nylok Corp., Paramus, N.J. The position had been formerly held by J. E. Johnson

who is now president of Aerospace Nylok Corp. . . . Consolidated, Diesel Electric Corp., Stamford, Conn., named Jack Greenberg assistant chief engineer of the Power Equipment division . . . J. Stewart Cruickshank has been promoted manager of International Harvester Co., Milwaukee division

Makes any drill press a HIGH

IN 11 SIZES

N.C. in all S.A.E. sizes



PRODUCTION TOOL in minutes!

With a MULTI-DRILL, you can go from hole-at-a-time drilling to real production in a matter of minutes! That's all the time it takes to mount any one of the many standard MULTI-DRILL adjustable multiple spindle drill press attachments on any drill press and put you into time and money-saving multiple drilling. Every MULTI-DRILL is quickly adjustable to drill a variety of hole patterns. Every MULTI-DRILL is designed for high production work. To learn how you can profit with a MULTI-DRILL, ask your nearby Commander Distributor to show and demonstrate the unit that meets your job requirements.



Write for the Production Tool Catalog

Commander MFG. CO.
4227 WEST KINZIE • CHICAGO 24, ILLINOIS

SEE US AT BOOTH 3209 ASTME SHOW, NEW YORK COLISEUM
Use postpaid card, Circle No. 328

MUSIF GO EVENT

THE MOST IMPORTANT FIVE DAYS OF THE YEAR FOR EVERYONE CONNECTED WITH MANUFACTURING



This is the national show that gives you twice as much for your money—everything that's new and important in manufacturing, production, engineering, research and development—plus fabulous New York City, too.

You'll see the very latest in all types of manufacturing equipment. '... you'll see improvements in current techniques and procedures... you'll see developments set resh from the drawing boards that you're virtually looking at longings... and you'll see display after display of equipment and parts and techniques... all designed to help you meet and conquer the challenges of both today—and tomorrow.

You'll sit in an conferences and symposia designed to give you the Intest technical and solution information—and you'll rub shouldors with America's top management, engineering, production; purchasing and sales people.

Sh Sign up NOW for 1961's BIG Show in the BIG City

1961 TOOL EXPOSI

M.Y. COLISEUM

OVER 400 EXHIBITS 6,000 PRODUCTS

ION & CONFERENCE

MAY

thru 26

Got a design problem? . . . worried about how to work the "wonder" metals? . . . looking for a new type machine? . . . or a new process? . . . or an entirely new manufacturing concept?

Providing the answers to these and other allied problems is the reason that, year-after-year, the annual meeting of the American Society of Tool and Manufacturing Engineers is the best attended of all American trade exhibits.

Don't wait another minute . . . fill in that registration form . . . plan to be one of the 50,000 satisfied visitors to the 1961 Engineering Conference and Tool Exposition.

*

'61

INFORMATION & INSPIRATION

Just take a look at the typical information-packed conferences and symposia scheduled below, and we think you'll agree . . . you can't help but find here the information and inspiration you and your top people need to successfully meet today's conditions, tomorrow's challenges.

Surface Metrology Seminar

Surface Specifications, Measurement Techniques, Predictions of Future Requirements and Developments

Material Removal Symposium

Ultra High Speed, Electrolytic and Electron Beam Machining

Manufacturing with Numerical Control Systems

Use of Computers in Manufacturing Operations Management

Application of Explosives in Metal Forming

Workhold Developments

Electrostatic chucking and Fiberglas reinforced Plastic Clamping

Numerically Controlled Machining Operations

Operations Research . . . Process Planning

Machining Malleable Iron and Cast Iron

Press Tooling and Die Design

Heat Treating Instruments

Metal Cutting Carbides

Work Simplification

Precision Grinding

FOR ADVANCE REGISTRATION and all the advantages it brings just fill in the form below and mail it NOW, with registration fee to the American Society of Tool and Manufacturing Engineers, 10700 Puritan Ave., Detroit 38, Mich. If you mail before May 1st you will receive, FREE, a \$10,000 ACCIDENTAL DEATH and DISMEMBERMENT POLICY covering you. 24 hours a day, from the time you leave home until you return . . . plus a time-saver Guest Badge that eliminates waiting in line at the Coliseum. After May 1st, bring your filled out registration card with you . . . save the time of filling it out at the Show.



ADVANCE REGISTRATION CARD

ASTME 1961 CONVENTION
NEW YORK COLISEUM . MAY 22 THRU 26

Fill in COMPLETELY and LEGIBLY and mail, with registration fee, to

MAIL PRIOR TO MAY 1st FOR FULL ADVANCE REGISTRATION BENEFITS

YOUR NAME TITLE

COMPANY ADDRESS

CITY______ZONE___STATE

COMPANY'S BUSINESS OR PRODUCT

BENEFICIARY'S NAME

Check one

Mamber's (Fee \$1)

| Hon-member (Fee \$2

American Society of Tool and Manufacturing Engineers 10700 Puritan Ave. Detroit 38, Michigan

- over 400 EXHIBITS
- . 21 TECHNICAL SESSIONS
- 12 PLANT TOURS
- . 6 SPECIAL EVENTS

EXHIBIT HOURS

Monday and Tuesday 1:00 pm to 9:00 pm

Wednesday thru Friday 9:00 am to 5:00 pm William C. Adamson was named works manager of Thor Power Tool Co. in Aurora, Ill. . . . Yale and Towne Mfg. Co. has appointed Walter R. Saunders north midwest regional manager for their Yale Materials Handling division . . . Frank G. Miller was promoted to plant manager at Climas Molybdenum Co., Langeloth, Pa. . . . William A. Kerr was elected vice-president of Bausch and Lomb Inc. and will be located in the Los Angeles area . . . Miniature Precision Bearings, Inc., Keene, N.H. has a new director in Ralph F. Gow, president of Norton Co., Worcester. Mass. . . . Joseph C. Mogavero was appointed manager of metal production operations of Metallurgical Products Dept., General Electric Co., Detroit . . . Chicago Pneumatic Tool Co. announced the appointment of G. A. May to the post of executive vice-president and general manager of the Allen Mfg. Co., Bloomfield, Conn. . .

PERSONNEL CHANGES SALES & SERVICE

Raymond G. Sloan, Jr. has been appointed sales manager of Magnetic Steel Products division of Armco Steel Corp., Middletown, Ohio . . . The Yoder Co., Cleveland, has appointed Elmer A. Koenig vice-president in charge of sales and Theodore R. Stroomer sales manager . . . Edward P. Fisher was named manager of finishing machine sales for the Osborn Mfg. Co., Cleveland . . . Woodruff and Stokes Co., Hingham, Mass., manufacturer of small precision tools, has appointed Roy Bent, Jr. sales manager . . . Named managers of marketing at Sharon Steel Corp., Sharon, Pa., were: James W. Byrne, hot rolled products; Rollin E. Douglas, special coated steels; Walter A. Garrett, Brainard strapping; and Donald W. Meyer, cold finished and coated products . . . Thomas L. Mayes, Jr., was named sales manager of original-equipment manufacturing at the General Electric Co., Bloomington, Ill. . . . Leland-Gifford



CLAMP-ABILITY

BECAUSE there's a De-Sta-Co clamp immediately available with just the holding power you need for any job—large or small.





Use postpoid card. Circle No. 323

Cooley

ELECTRIC

HEAT TREATING

FURNACES

41 Models-with and without

Controlled Atmosphere

RECIRCULATING OVENS

for drying, baking, etc. 3 Types— 650° F., 850° F., and 1000° F. Wide range of sizes.



INDUSTRIAL BOX FURNACE

for general heat treating to 2000 °F. Highly efficient with low maintenance; quick repair with small down time; sturdy; reliable.



WRITE for

complete information on these and the

- . New GA Atmosphere Box Furnace
- . Recirculating Air Draw
- Bench Types
- . 2500° F Box Furnace

Cooley ELECTRIC MFG. CORP.
36 S. SHELBY ST.
INDIANAPOLIS 7. INDIANA









R. E. Jones

Co., Worcester, Mass., made John Ratermann sales manager in the Indiana-Ohio-Kentucky area . . . The Matthews Corp., Hawthorne, Calif., promoted Raymond E. Jones from general sales manager to vice-president of sales

... Frank D. Sullivan has been named southwest sales manager for the Service Products division of Johnson's Wax, Racine, Wis., and will headquarter in Dallas . . . National Twist Drill and Tool Co. Rochester, Mich. has announced that William E. Atchley has been elected vice-president in charge of sales. Fred D. Lamb, Jr. has been named general sales manager, and Howard M. Easton assistant general sales manager . . . Richard P. Taugner has been appointed to the sales and service department of Wesson Co.'s Midcontinent District office in Elmhurst, Ill. . . . Leo Reierstad has been named general sales manager of the Permanent Mold Die Co., Inc., Hazel Park, Mich. . . . Robert M. Miller has been promoted to assistant sales manager of the Machine Tool division of DeVlieg Machine Co., Royal Oak, Mich.



R. M. Miller

Josef H. Buerger, Jr., has been appointed sales director of the Crucible Steel Co., Pittsburgh . . . Standard Steel Works, a division of Baldwin-Lima-Hamilton Corp., Burnham, Pa., named Donald Lade general sales manager. Mayor S. Silvey was named contract sales manager for Pratt and Whitney Co., Inc., West Hartford, Conn.

Frank J. Vlasaty was named sales manager of Size Control Co., Chicago ... Charles L. Foley was appointed to represent Newark Wire Cloth Co., Newark, N.J., in the central New England States . . .

Eliminate Sharpening and Blade Adjusting





Wetmore Indexable In-sert Milling Cutters are available in a wide range of standard types and sizes. Write for completely descriptive Catalog No. 06-D.

with Wetmore Indexable Insert Milling Cutters

Simply unclamp and index the carbide inserts to renew the cutting edges eight sharp edges per insert. Two-piece body construction permits precision grinding of insert seats during manufacture and insures perfect alignment of inserts after indexing.

Inexpensive replacement cost of indexable carbide inserts and their much greater convenience in milling operations lead to unprecedented economies. Wetmore designs utilize precision ground insert blanks that are standard with leading manufacturers and are readily available from local suppliers' stocks.

Wetmore Tool & Engineering Co. Phone: TWX: LA 2085 5320 E. Washington * Los Angeles 22, California

Wetmore Tools

Core End Mills Port Contour Drills Routers

Form Cutters

Milling Cutters

Cutters

For

8-STATION PRODUCTION MACHINING 11/2" BAR AND COLLET WORK CHUCKING SINGLE POINT THREADING

Costs

rd equipment

This is an all new 11/2" bar capacity ram type turret lathe with power feeds to all 8 working stations . . . that in addition to bar and collet work also has the versatility to do chucking, and when needed, single point threading. Powered by a 5 h.p., two-speed, geared motor, the new Sheldon 3 R turret lathe provides 16 spindle speeds, 60 different feeds to the carriage and cross-slide, and 180 different feeds to the ram turret.

accurately machined to provide close tolerance indexing. And for complete ease of operation, it is put under power by simply pressing a push button on the control panel.

The turret itself is ruggedly built and

This new 3 R Sheldon is completely equipped with two-speed motor and electrical controls, coolant system and splash guards, LO spindle nose, large satin chrome dials and hardened bed ways. It also provides an additional cost saving feature-each turret face is drilled and tapped for your standard flange type tooling as well as being bored for your standard 11/2" shank type tooling.

For versatile, accurate machining in either long or short runs, the new Sheldon 3 R provides the answer to low investment cost with high profit operation.




Builders of 10", 11", 13", 15" Sheldon lathes, Sheldon Milling Machines, Sheldon Shapers and Sebastian Geared Head Lathes

See us at Booth 1250 ASTME Show, New York Coliseum. Use postpaid card. Circle No. 325

What's New in Metalworking



14



This 35-ton Niagara automatic OBI press operates at speeds up to 1000 spm.

AUTOMATIC OBI PRESSES FOR HIGH-SPEED, SHORT-STROKE WORK

Niagara's new line of automatic, ultra-high speed OBI presses has been designed to boost production and reduce costs on short-stroke stamping jobs. These Series M presses feature an extra-rugged, welded, all-steel frame, low-inertia slide and connection, and non-metallic ways.


The line includes both non-geared and single-geared presses in 22-, 35-, 45-, and 60-ton capacities. Shaft diameters range from $2\frac{1}{2}$ " to 4".

The slide is designed specifically to meet the requirements of high-speed, precision stamping work: unusually long and rigid guiding; more mounting space; and symmetrical around-point-of-load application, for solid support and longer die life. Fully enclosed drives provide safer, cleaner operation as well as improved appearance.

Niagara Machine & Tool Works, 683 Northland Ave.,

Buffalo 11, N.Y.

Use postpaid card. Circle No. 59



VERTICAL MILLING MACHINE PROVES VERSATILE

A 28" vertical Hydro-Tel milling machine, for general purpose manually controlled milling, die sinking, automatic profile milling and multiple spindle production milling, has been announced by Cincinnati Milling's Milling Machine Division.

Use postpaid eard. Circle No. 66

LEMPCO HYDRAULIC PRESS BRAKES

A line of hydraulic press brakes for sheet metal and plate fabricators is being offered by Lempco Industrial, Inc.

The machines range from 75 to 100 ton capacity and incorporate a new

mechanical-hydraulic valving device, which eliminates the former electronic servo control.

Lempco Industrial, Inc., 5490 Dunham Rd., Bedford, Ohio.

FLOATING AIR PLATFORM SAVES WEAR AND TEAR

A jig and fixture platform that floats the work on a thin film of air can now be obtained in one of two standard sizes in the Mighty Midget line.

The Flying Carpet floating air platform is an alloy-iron plate, ground parallel, with tiny orifices drilled in the bottom of it. These control a metered amount of air, thus lifting the load a few thousandths of an inch above the machine table or surface plate. Or, the platform may be inverted and the work floated over it.

The platforms are available in 6" and 10" lengths x $5\frac{7}{8}$ " wide.

Sperman Metal Specialties, 2199 E. 21 St., Brooklyn 29, N.Y.

Use postpaid card. Circle No. 62



Measures the exact BORE or blind hole size! Reading .0001" Size: 3/16" to 4"

Takes accurate measurements of blind holes. No master — measures directly—by .0001". Automatic alignment, rectangular contact points guarantee extreme accuracy even when fully extended. Immediately detects out of round holes; with extensions measures holes up to 30" deep. Hardened contact points exert minimum pressure — will not damage fragile work.


Easy to read, deep graduations on a large diameter thimble. Dull chrome plated. Furnished in English or Metric graduations, individually or in sets.

WRITE FOR CATALOG on complete line of precision measuring instruments: VERNIER CALIPERS, MICROMETERS, DIAL INDICATORS.



INA CORPORATION

122 East Second St., Mineola, L. I., N. Y.



SLIP SPINDLE DRILLING MACHINE FEATURES QUICK CONVERSION

The 4-station, shuttle type, slip spindle machine shown here is one of twelve machines, built by the Lamb Co., that form a segmented production line for processing cast iron, V-8 or six cylinder truck engine heads.

The machine column, column base,

way type shuttle, drill head and universal housing are Lamb standard building blocks. The machine has 16 slip spindles but the drill head is equipped with 24 drives to accommodate hole pattern changes and/or additional holes in future workpieces. All machines in the line are equipped with extra drives. The spindle plate can be changed without disassembly of the head or universal housing.

A 2-position shuttle carries two fixtures that are hand loaded and clamped. The machining cycle is automatic. After operations are performed at Station No. 1, the slide shuttles to Station No. 2, then returns and stops. The operator removes the part, repositions it, and loads the second fixture. A new part is loaded into the first fixture. Heavy plugging bars align the head and fixtures at both shuttle positions.

The drill head and shuttle are actuated hydraulically. Machining operations are performed dry. Hardened and ground tool steel ways are used for the drill head and shuttle.

F. Jos. Lamb Co., 5663 E. Nine Mile Rd., Detroit 34, Mich.


Use postpaid card. Circle No. 63

FINISHING LATHE HALVES OPERATING TIME

A dual-spindle, low-cost lathe, which handles polishing, buffing, deburring, and brushing jobs in half the normal time, is now available from Murray-Way. This lathe (Model L12) is claimed to be able to cut fixture costs, because only one semi-automatic part-positioning machine is needed instead of the usual two.

The L12 employs two separate motordriven spindle assemblies which are mounted on one base. Each spindle is adjustable to compensate for wheel wear. The speeds of the wheels may be varied by a change of motor sheaves.

Murray-Way Corp., P. O. Box 180, Birmingham, Mich.



SPINDLES FOR ELECTROLYTIC GRINDING COVER WIDE RANGE

Pope Machinery's line of motorized and belt driven spindles arranged for electrolytic grinding now covers the broad range between 50 amps. and 3000 amps.

Insulation is built in and the spindles are equipped with a new, fork type brush assembly for cool operation.

Pope Machinery Co., 261 River St., Haverhill, Mass.



Use pestpaid eard. Circle No. 65

TAKE THE OUCH OUT OF TURRET DRILL COSTS with



DRILL, REAM, TAP, COUNTERSINK AND COUNTERBORE ON A COMMON TOOL AXIS.

QUADRILL4&5 SPINDLE TURRET DRILLING HEADS

CONVERT YOUR STANDARD DRILL PRESSES INTO PRECISION TURRET DRILLING MACHINES—one quadrill mounted on your drill press will...

- Save you up to 70% in direct labor costs over in-line, single gang drill setups.
- Save you up to 350% in capital investment costs (other turret machines cost several hundred to thousands of dollars more).
- Do the work of 4 or 5 single drill presses—all work done at single hole location (increase production 50%, cut rejects, save floor space).

Ideal for both long and short runs . . . fast setups . . . simple tooling.

WRITE TODAY FOR BROCHURE

CHICAGO QUADRILL

1846 BUSSE HIGHWAY DES PLAINES, ILLINOIS
Use postpaid card. Circle No. 335

Toughest, hardest, strongest ... none finer at any price!




Premium Quality High Speed Steel Carbide Tipped and Solid Carbide

Call your local distributor today—or write Ace direct for latest catalog and price information.



ORIGINATORS OF "GROUND-FROM-THE-SOLID" DRILLS
Use postpoid card. Circle No. 336



C-FRAME PRESS HAS TILTING TOP PLATEN

A 2½-ton, all-welded, air-operated C-frame Acroplate press announced by Lake Erie features a top platen which tilts as it opens, giving 10½" of clearance at the front and 5" at the back. This feature simplifies and speeds the loading, inspection, and unloading of the work.

It can be furnished with aluminum drilled plates for the circulation of steam or hot oil for heating, or water for cooling. If desired, the drilled plates can be replaced with electric heating plates.

The general design of this press makes it well suited for a variety of pre-heating or chilling operations as well as low pressure molding or laminating.

Lake Erie Machinery Corp., P. O. Box 68, Buffalo 17, N.Y.

AIR ACTUATORS SPEED COLLET AND CHUCKING OPERATIONS

Wil-Numat announces a line of air actuators for use on all hollow spindle machines to actuate either push or pull collets, expanding mandrels, rubberflex collets or power chucks. Use of the hole through the spindle is retained for feeding coolant to work, feeding bar stock or reaching back of workpiece for various purposes.

The actuators operate off the shop air supply, multiplying gripping power at the jaws up to 80 times line pressure. Gripping power is adjusted by an air pressure regulator and a positive, uniform grip is maintained even when variations in stock diameter exist. eliminating slippage, scrap and possible tool damage.

Wil-Numat Corp., 411 South Hindry, Inglewood 1, Calif.

Use postpaid card. Circle No. 67

UNISORB MACHINE MOUNTS

Easy-to-install machine mounts that provide precise leveling of equipment weighing as much as 1/2 ton have been developed by Unisorb. Designated the Series LR500, these mounts can be supplied with either 3" or 4" leveling bolts. Especially recommended for lathes. grinders, and other precision machine tools.

Unisorb Division, The Felters Co., 210 South St., Boston, Mass.

Use postpaid card. Circle No. 68

USE SAWS? HACK . BAND . CIRCULAR

KEEP THEM SHARP!

Automatically . Economically Learn How - Write Today!



Use postpoid card. Circle No. 337



FOR A Quality TYPE HOLDER

> with no sacrifice of durability for eavy-duty, straight-line marking. Made of Safety Steel to



M. E. CUNNINGHAM CO.

1048 CHATEAU STREET, PITTSBURGH 31, PA. Use postpaid card. Circle No. 339





- · Saves 80% time in finish sizing holes
- · Repeat to .0001" in 30 seconds, No backlash
 - · Hardened and ground parts
- Improves quality

• 100% guaranteed with

KA•BOR OFFSET BORING HEADS!

Precision Tool & Mfg. Co. of Illinois 1305 S. Laramie Avenue . Cicero 50, Illinois CLIP THIS AD to your letterhead!



AC-DC WELDER USES SINGLE PHASE

Offered in 300, 400, and 500 amp sizes, the Miller MD welder is claimed to be versatile and modestly priced. It has a continuous current control, an open circuit of 80 volts in both ac and dc, plus two welding currents in each, and straight or reverse dc polarity.

Miller Electric Mfg. Co., Appleton, Wisconsin.

Use postpaid card, Circle No. 69

HYDRAULIC PRESSURE CONTROL



Low price and high quality make FULFLO piston-type hydraulic valves a natural O. E. M. choice. The service they deliver . . . quiet, dependable and trouble-free . . . makes them ideal from the equipment users' viewpoint.

- . Screw or flange models ... to 500 lbs. ... for pipe sizes to 3"
- · Steel, cast iron or brass bodies . . . brass, steel or stainless trim
- · Fast shipment of standards . . . special to your requirements

FOR EXTRA CONTROL CONVENIENCE

Where frequent pressure setting is needed, install a FULFLO Hand Wheel Valve; available in a wide range of types.

Request complete catalog from:

The FULFLO SPECIALTIES CO., Inc.

417 Fancy Ave. Blanchester, Ohio




UNCOILER WITH TENSION CONTROL

This Seco uncoiler can provide precisely controlled tension on light-gage slitting or processing lines, and features an enclosed, oil-tight gear drive and a drag-generator unit.

A hydraulic cylinder positions the

Steel Equipment Co., 20805 Aurora Rd., Cleveland 22, Ohio.

Use postpaid card. Circle No. 70





On PINES Model 660 End Finishing Machine


Designed especially for simultaneous inside-outside deburring, chamfering and facing operations on tube, rod and pipe ends, this *bigh production* machine features:

- EASIER OPERATION . . . with simplified controls.
- CLOSE TOLERANCE WORK AND FASTER FEEDS.
- 3-MINUTE CHANGEOVER . . . with interchangeable tooling and fast selection from 8 spindle speeds.
- HIGH PRODUCTION... to 1500 ends an hour in stock to 2"O.D.

BOTH MANUAL AND AIR OPERATED UNITS AVAILABLE LARGER MACHINES ACCOMMODATE STOCK SIZES TO 5" O.D.

WRITE FOR NEW FREE CATALOG





PUT COMPONENTS TOGETHER TO BUILD CUSTOM GRINDER

The internal-external grinder shown here was designed to meet special requirements of an industrial component manufacturer. The machine also illustrates the versatility of Standard Electrical Tool's building-block line of spindles, grinder heads, slides, feeds and accessories.

The grinding wheel head is powered by a ½ hp motor and permits rapid

DIAMOND TOOL

Lazzara Co. in Houston has designed a diamond tool called the Block Diamond Wheel Dresser. Alternate layers of 21 and 22 diamonds set in tungsten powders are in the face for dressing the wheel. Face of the tool is ½" x ½".

Lazzara Co., 112 Meyerland Plaza, Houston 35, Texas.

Use postpaid card. Circle No. 72

interchange of the 6" wheel external spindle for an internal spindle.

The head stock in this instance is equipped with collet chuck having an automatic air cylinder controlled by foot pedal switch.

Horizontal traverse is powered by a hydraulically controlled air cylinder.

The Standard Electrical Tool Co., 2486 River Rd., Cincinnati 4, Ohio.

LUBRICANT PUMPING SYSTEM


Constant-feed or re-circulating lubrication of bearings and journals on large machinery is provided by the Graymills pumping unit. It consists of a 5-gal. container and a gear-type pump driven by a 1/8 hp motor. Pressure relief-valve can be set to 75 psi.

Graymills Corp., 3705 N. Lincoln Ave., Chicago 13, Ill.

Why Dickerman punch press feed users-



Efficiently feeds stock you can practically see through.



H. E. DICKERMAN MFG. CO. 321-114 Albany Street • Springfield, Mass.

The Dickerman 21/2" Hitch Feed®, one of the bantams of the line, feeds stock as fine as 003". in thickness, in widths up to 21/2".

The Dickerman 12" Rol-Di-Feed, largest in the line, feeds stock up to 3/16" thick and in any width up to 2 lbs. per linear foot.


There are 15 "standard" feeds in the complete. versatile Dickerman line.

They all feed as fast as it is wise to run the tooling . . . and a hundred-million pieces, without major maintenance is routine.

You can gently feed a small fraction of an inch with a "Hitch Feed" or you can accurately position big, rugged strip stock up to 12" per press stroke with the Rol-Di-Feed.

Versatile, Dependable Production Savings are the reasons for specifying Dickerman Feeds. Prove it to yourself.

Send for literature and prices



55-TON PRESS-RITE PRESS

A power press which combines speed and versatility has been announced by Havir. Named the Model 55 Press-Rite, it features an extra-heavy and fast-operating ram slide with a long full V-ram to maintain precision alignment under loads. Full lubrication is insured whether the press is upright or inclined. Other features include an air-friction clutch, non-repeat single-stroke safety mechanism, and automatic cam actuated brake.

Havir Mfg. Co., 444 Cleveland Ave., St. Paul, Minn.

Use pestpaid card. Circle No. 74

DRILLING AND TAPPING HEAD


Only 32" long, 10-15/16" wide, and 22½" high, this unit is used for multiple-station arrangements on fixed and indexing tables. It has a 6" maximum spindle travel, and built-in electrical relays for automatic or manual cycling. Each unit is provided with a control panel, and takes up to a 10-hp motor.

Johnson Drill Head Co., Rockford, Ill.
Use postpaid card. Circle No. 75

5 WAYS.....











TO MAKE SET-UPS EASIER ... QUICKER

THESE DISTRIBUTORS WILL GIVE YOU QUICK DELIVERY ON UNIVERSAL TOOLS FROM STOCK

Ā			

Scott Supply Co. ST 5,1179 Birmingham

ARIZONA

Industrial Tool & Supply Co. MA 3-2581

CALIFORNIA

Almquist Tool & Equipment Co. LU 9-6688 Los Angeles Machinists' Tool & Supply Co., RA 3-6731 Los Angeles Marshall Tool & Supply Corp., Los Angeles AN 3-6121 Joseph C. Fletcher Co., Son Francisco UN 1-2991 Acme Tool and Supply San Diego BR 7-8550

COLORADO

Overgard Machine Tool Co., Denver MA 3-3141

CONNECTICUT

Silliter-Holden, Inc. AD 2-4433 Hartford

FLORIDA

Florida Machinery Corp., FR 9-0647

GEORGIA

Fulton Supply Co., Atlanta MU 8-3400

ILLINOIS

Chicago Supply & Tool Co., EV 4-3933 Chicago Crown Supply Co., SP 7-1200 Harry Lee & Sons Chicago CA 7-5500

INDIANA

Indiana Manufacturers Supply Co. Indianapolis ME 5-2451 South Bend Supply Co., South Bend

Allen Supply Co., Cedar Rapids 3-3533

KENTUCKY

Louisville Machinery Sales EM 6-1438

LOUISIANA

Richards & Holmes Machinery RA 7281

MASSACHUSETTS

Chandler & Farguhar Co. LO 6-7800 Atlantic Industrial Supply Co., Cambridge TR 6-3211 Berkshire Machinery Co., PL 7-5475 Worcester

MICHIGAN

Royall, Inc., WO 5-7148 Ann Arbor Production Tool Supply Co. JE 9-1660 Detroit (Warren) Sterling Supply Co., JO 6-0700 Detroit (Ferndale) LI 6-3200 Gransden-Hall & Co., CE 4-6672 Flint F. P. Miller Co., Jackson ST 4-0525 Gransden-Hall & Co., Saginaw PL 4-2431

MINNESOTA

Satterlee Co., Duluth RA 7-8454 Satterlee Co., FE 3-5264 Minneapolis

MISSOURI

Bossert Co., Kansas City BA 1-9033 Production Tool & Supply Co., OL 2-5800 St. Louis

NEBRASKA

Fuchs Machinery & Supply Co. 34 1-7050 Omaha

NEW JERSEY

Tool Specialties Co., MU 6-8700 Hillside Schultz & Anderson Co., MA 2-4318 Newark Monufacturers Selling Co., Trenton EX 6-8286

NEW YORK

Beals, McCarthy & Rogers, Inc., Buffalo TL 4-4900 Machinists' Tools, Inc., Buffalo TT 4-5397 Gierston Tool Co., RE 3-7191 Oakland Supply Corp., Hempstead (L.I.) IV 9-0511 Gierston Tool Co., Electra Industrial Dist. Inc., GL 2-9000 Poughkeepsie

Steeves Machine Tool Sales HU 2-0600 Rochester Clark Witbeck Co., FR 4-4141 Schenectady A. V. Wiggins Co.,

GR 1,9141

Syracuse OHIO

Strong, Carlisle & Hammond Canton GL 4-8071 E. A. Kinsey Co., Cincinnati PA 1-8030 Strong, Carlisle & Ham Cleveland CL 2-4000 George Whalley Co., Cleveland UT 1-7676 E. A. Kinsey Co., Columbus AX 1-4683 E. A. Kinsey Co., BA 3-9185 Dayton A. M. Schmit Co. GR 4-1141 Toledo

OKLAHOMA

Industrial Equipment Co., Tulsa LU 5-1111

PENNSYLVANIA

H. P. Weller Erie GL 2-1401 Harris Pump & Supply Co. HU 1-4400 Pittsburgh

RHODE ISLAND

Reynolds, Inc., Providence ST 1-3010

TENNESSEE

Tool Crib Knoxville 5-6195

Bill Lindsley Machinery Co RI 7-1521 Dallas Tools, Inc., Houston OX 4-2353

VIRGINIA

Associated Sales Co., Richmond MI 8-7448

WASHINGTON

Aronson's Hardware Seattle SE 1777

WISCONSIN

Herlache Industrial Supply Co., Green Bay HE 2-8669 Triplex Supply Co., BR 1-7566 Milwaukee

ASK YOUR DISTRIBUTOR OR WRITE FACTORY DIRECT FOR YOUR 24 PAGE CATALOG OF UNIVERSAL TOOLS.

VISE & TOOL CO.



wind your own springs FAST, EASY, ACCURATE

- · Winds one or hundreds of any spring
- Makes any length springs
- Winds flat, round, square and rectangular wire
- Forms any gauge wire to 1/4" diameter
- Moves easily to any location. 30 lb.
 23½"x8½". Bench or vise mounted.

See your Di-Acro dealer or write for information and prices.



DI-ACRO CORPORATION

formerly O'Neil-Irwin Mfg. Co. 604 W. Eighth Ave. . Lake City, Minn.

Use postpaid card, Circle No. 331



INCLINED RAM POWER SHEAR HAS SPLIT-SECOND CYCLING

Cutting action that takes place in one-fifth of a second is featured on a No. 48 high-speed power shear introduced by O'Neil Irwin Mfg. Co. It can cut ferrous and nonferrous material up to 50" wide and as heavy as 16 gage mild steel at a rate of 160 spm. The speed of the machine makes it adaptable for use on conveyor or run-out

Di-Acro Corp., Lake City, Minn. Use postpaid card, Circle No. 76

MACHINE PRODUCTS PRECISION EQUIPMENT

- INCREASES ACCURACY
- REDUCES REJECTS
- SPEEDS SETUPS
- **CUTS COSTS**

You'll hold closer tolerances and increase efficiency, too, when you use Machine Products precision surfaces. Because the combination of superior materials, skilled craftsmanship and rigid quality controls in the manufacture of Machine Products equipment assures you of the precise dimensional accuracies you require. A complete line of plates and accessories is available, so send for your free catalog today.



MACHINE PRODUCTS CORPORATION

6771 E. McNichols Rd.

Detroit 12, Michigan

THREE- AND FOUR-WAY AIR VALVES

Bimba Mfg. Co. is marketing threeand four-way air valves with full 1/4" ports. These valves contain 1/2 NPT air connects. They are base-mounted and 1-13/16" high. The three-way valve is designed to be used with singleacting air cylinders, while the four-way valve operates with the double-acting cylinders.

Bimba Mfg. Co., 101 Main St., Monee, Illinois.

Use postpaid card. Circle No. 77





PRODUCT 46 VICTOR AVE., DIV. 22 DETROIT 3, MICHIGAN



LOAD-INDICATING PLIERS

An industrial plier which permits repeated application of a predetermined clamping force, regardless of the work thickness, has been announced by Lapeer. It is available in four models as well as a C-clamp series which has a maximum clamping force of 1,200 lbs. The adjusting spindle is set for the desired force by trial clamping. Duplication of an established clamping force on any other work thickness can be made by turning the adjusting spindle so that only the load indicating washer moves after clamping.

General Sales Offices, Lapeer Mfg. Co., 1150 Baltimore W., Detroit 2, Mich. Use postuaid eard. Circle No. 78



VISIT HARIG BOOTH 1514 (A.S.T.E. Show)

NEW ULTRASONIC TESTING INSTRUMENT

A Model 424D Immerscope has been designed for ultrasonic nondestructive testing of plates, ingots, pipes, tubing, forgings, castings, and welds. Inspection is not limited to metal objects, since other reasonably elastic materials such as glass, hard rubber, and ceramics can also be inspected.

Princeton Division, Curtiss-Wright Corp., P.O. Box 110, Princeton, N.J.

Use postpaid eard, Circle No. 79



TORIT



Torit Cyclone Separator Medel. High efficiency collection of all types of dust, chips and shavings. Up to 95% of the dust is removed from the air, drawn into the top of cone by centrifugal force, and settled to the dust reservoir below. Clean air is exhausted outside the building or indoors through after filters.

Self contained, compact, portable steel units. End mounted motor and blower mounted in free air for cool operation, is detachable for servicing or relocation of outlet. Cones can be rotated for proper inlet location. Dust reservoir has pull-out drawer for easy cleaning. Individual capacities range up to 6500 cubic feet per minute. Larger units are built on special order.

Prices start at \$335.

DUST COLLECTORS STOP LOSSES CAUSED BY DUST

- machine wear
- absenteeism
- product damage

With a Torit Dust Collector, machines stay clean, hold close tolerance up to 80% longer. Dust is kept off bedways, slides, and bearing surfaces. There are fewer accidents because work areas are clean and safe. Employees work more efficiently in clean air, their health protected. And there is no dust in the air to harm fine product finishes.

For a FREE handbook detailing specifications and performance data of Torit Dust Collectors and applications, write Dept. 630.

TORIT

MANUFACTURING CO.


HIGH SPEED PRECISION LATHE

The new improved Model HLV-H high speed precision lathe combines all the good features of the HLV series, plus many new ones. The lathe is designed to fill the gap between the plain precision bench lathe and the heavy duty engine lathe.

Lathe has an 11" swing over the bed, infinitely variable speeds of 125 to 3000 rpm, with push button controlled electrically actuated variable speed drive.

The larger headstock frame and large super-precision preloaded ball bearings provide maximum precision for sustaining operation at full speed. The headstock spindle has a through collet capacity of 1-1/16", and step chuck capacity of 6".

Built-in automatic thread length control and quick-acting compound slide for threading are standard equipment. The lead screw is used for threading only, as a separate electric motor provides the feed for carriage and cross



Built-in automatic thread length control and quick-acting compound slide for threading are standard equipment.

slide. Feed rates are easily changed by simply turning a knob on control box at right-hand end of bed.

Hardinge Brothers, Inc., Elmira, N.Y.
Use postpaid card. Circle No. 80

BRINEY invites your inquiry-

for precision tools requiring split-tenth adjustments without loosening or tightening screws

Precision Boring and Turning Tools Stocked standards and specials

Diamond Dressing Arm Another special application using the Briney Principle of Precision Adjustment

and Anti-Friction Support and Pilot Bearings Stocked standards and specials

SEND FOR COMPLETE BRINEY TOOL LITERATURE TODAY

BRINEY MFG. CO.

Use postpoid card, Circle No. 349

P.O. Box 208 Pontiac, Michigan Phone: FEderal 4-2552

BREAKDOWN MILL ROLLS FERROUS AND NON-FERROUS STRIP

A new addition to the Western Electric Co.'s Hawthorne Works in Chicago, where Bell System dial telephone equipment is manufactured, is a new Bliss breakdown mill which converts slabs into strip. At Hawthorne, Western Electric casts its own alloys and then rolls them into strip, using some 30 million pounds of fer-

rous and non-ferrous metals and alloys every year. Among the metals handled are brass, nickel, silver, phosphor bronze and the special ferrous material, Permalloy.

Bliss' slab and coil handling auxiliaries include a 50' entry table, air-




13" x 27" x 18" cold breakdown mill.

operated pivot type upender, coil box entry belt conveyor, etc. The equipment handles 500-lb. slabs and 2000-lb. coils. The mill can roll strip as fine as .060".

E. W. Bliss Co., Rolling Mill Division, Salem. Ohio.

Use postpaid card. Circle No. 81

FRICTION CUTTING



Connecticut


friction BAND SAWS offer these advantages:

- Conventional saw cutting and friction cutting on the same machine.
- Especially valuable to fabricators of stainless steel and tough, heat resistant, materials.
- Better guides, more accurate cutting, longer blade life.
- Reasonably priced, selected features tailored to your requirements.

Write for a Detailed Brochure

W. WHITNEY STUECK Inc.

P. O. BOX 355B OLD SAYBROOK, CONN., U.S.A.



BALANCER GIVES READINGS WITHOUT TRIAL RUNS

A force-measuring balance machine, which automatically indicates the amount of unbalance in a workpiece and the exact angular location without the need of trial calibrations, runs, or test weights, has been introduced by American Trebel.

The centrifugal forces which are exerted by the unbalanced workpiece

Big Job, Little Job BALCRANK CAN HANDLE IT!

HAND WHEELS

Best quality, fine grain cost iron. Rim and handles polished to high luster. Handles are revolving, solid or omitted. Available in standard sizes 4" to 12" dia, with plating, broaching ar other machining to your specification.



MACHINE HANDLES

Revolving handles turn on HARDENED steel spindle with permanent graphite grease lubrication permitting FASTER, EASIER adjustment by user. Machined from quality BAR STEEL ground and POLISHED to a smooth, high luster.







STRAIGHT

WRITE FOR FREE CATALOG AND PRICE LISTS TODAY!

Machine Tool Division BALCRANK

16 DISNEY ST. . CINCINNATI 9, OHIO . U.S.A.

are measured directly by a pressuresensitive transducer, and thereby eliminates the need of converting the unbalance force into vibrations before measurement.

Equally suitable for piece work as well as for production runs, the Trebel Model F may be operated by relatively unskilled personnel. No set-up calibrations are required on this balancer and the operator can shift from one type of work to another without the need of calibration charts or a set-up man.

American Trebel Division, Kurt Orban Co., Inc., 87 Greenwich Ave., Greenwich, Conn.

Use postpaid card. Circle No. 82



EMPCO HAS HYDRAULIC FEEDER

A hydraulic feed unit for simplified control of complex machining operations has been announced by Enterprise Corp. This attachment operates independently or in conjunction with other hydraulic equipment such as clamps, indexing mechanisms, or other feeders. It has a flexible range of operational cycles, and can be used in a variety of production operations including reaming, counterboring, grooving, and tapping.

According to the company, the new hydraulic unit sets up easily, and bearings, seals, piston rings, cylinder sleeves, and other components are readily replaceable.

Enterprise Machine-Parts Corp., 2732 Jerome St., Detroit 12, Mich.

Use postpaid card. Circle No. 83



KENTRALL Hardness Testers Are Motorized

By removing major test loads automatically, the new motorized Kentralls reduce operator error, increase reproducibility of test results, and raise the productive capacity of the machine—for the same price as hand operated testers.

The motorized Kentralls are available in Combination Testers which provide both Regular and Superficial Rockwell Hardness Testing in a single machine. For those applications that do not require the additional range, Kentrall also makes single purpose testers for either Regular or Superficial testing alone.

For complete information write for Bulletin CRS-60.

KENTRALL THE TORSION BALANCE COMPANY

Main Office and Factory: CLIFTON, NEW JERSEY

TB-IM

Sales Offices: Chi., Ill., San Mateo, Cal.
Use postpoid cord. Circle No. 353



ASSEMBLY MACHINE DIRECTED FROM ONE CAMSHAFT

The Bodine Corp. announces the addition of a Model 60 assembly machine to its line of dial type multiple

operation machines. The Model 60 combines the 360° of tooling availability, made possible by the center column construction, with mechanical actuation.

The indexing and tooling motions are all controlled from one central camshaft. Power pick-offs from the central camshaft provide auxiliary camshafts and sprockets to actuate tooling all timed directly with the main camshaft.

The Model 60 is suited for the assembly of a large number of components combined with the "in-process" inspection of the assembly, stage by stage. Coining, staking, crimping and inserting operations are performed from the moving tooling platform without any auxiliary power source. Tooling can be mounted inside, outside, above and below the indexing work table with power take-offs in all tooling areas.

The Bodine Corp., 317 Mountain Grove St., Bridgeport 5, Conn.

Use postpaid card, Circle No. 84



STEEL

TYPE HOLDERS

to stamp metal products

Hand or Press Style. Type can be easily, quickly loaded and unloaded. Simplest construction . . . just a sturdy pin holds the type securely. No screws nor springs. Super-quality steel type made in various sizes: 1/32" up to 1/2" figures and letters. Write for Bulletin BB-23H.

STEEL TYPE & BOX

Indexed Sectional Type Box with separate compartment for each character. Two sizes for small and large type. We can also make steel type with round face characters.

NUMBERALL STAMP & TOOL CO. HUGUENOT PARK STATEN ISLAND 12, N. Y.




SPEEDING SPOTTING-IN TIME

Spotting-in time on dies and molds now can be safely speeded up to 70% with the Tilt-A-Die, according to its manufacturer, Sanders Tool and Production Co. Its rising and lowering bed and platen design eliminates damage to dies and molds caused by mechanical failure, which may occur from a vertically falling crown and upper platen. More than one person can work

on spotting-in at the same time. Tilt-A-Die is designed for die casting, trim, blanking, form, and drop forge dies; and glass and plastic-mold spotting-in operations.

It can also be used as a heavy-duty



arbor press; a piercing, blanking, forming press; a production trim press; or a tryout press for trim dies.

Sanders Tool and Production Co., 4030 Fitch Rd., Toledo 13, Ohio.

Use postpaid card. Circle No. 85

Perfect Alignment! Maximum Accuracy!


Your guarantee when you order

ROOFE HEAVY-DUTY BULL NOSE Centers

Make sure your next Heavy-Duty Centers are ROOFE "Bull Nose." Two double rows of bearings in the large and small ends of the nose allow perfect positive alignment on any type of work. Two shank sizes provide diameters from ½" to 7½" for a wide range of work with a single center. Write today for catalog.



HOUSTON GRINDING & MFG. CO., Inc.



PORTABLE DRAFTING MACHINE

Drafto has added Model 112M to its line of portable drafting machines for 12" by 18" drawing sheets. The complete machine consists of a board, parallel arm assembly, and protractor with scales.

Drafting Equipment Co., 540 Randolph St., Meadville, Pa.

Use postpaid eard. Circle No. 86



Nobody, but nobody, tends your die set needs with such dispatch as Danly. Whether you want a new Precision Pilot Guide Post for extra ease in die set assembly . . . or a fast order placed for a special die set, you can depend on your nearby Danly man for quick, effective action. Like all 23 Danly branches and distributor assembly plants, he stocks a wide selection of die sets and diemakers' supplies for immediate delivery. Next time you need die set service, call your Danly man. He's as close as your phone — and at your service 'round the clock.



NEW INSULATED Demountable Bushings, designed for use in machining mounted dies by electrical discharge, are fully described in new, fact-filled bulletin. Write for your copy.



PRECISION PRESSES, DIE SETS AND DIEMAKERS' SUPPLIES

DANLY


DANLY MACHINE SPECIALTIES, INC. 2100 South Laramie Ave., Chicago 50, Illinois

POLISHING ARM FOR BUFFING LATHES

An arm that can be installed on adjustable buffing lathes adapts them to abrasive-belt polishing operations. This lightweight attachment can be mounted on the spindle housing. Belts are spring-loaded between a contact wheel and an idler pulley.

Acme Mfg. Co., 140 E. Nine Mile Rd., Detroit 20, Michigan.

Use postpaid eard, Circle No. 87







FEEDER FOR LIGHT COILS

A Ses-Matic Junior air feed has been designed to feed light coiled material into punch presses at speeds up to 250 spm with a positioning accuracy of .002".

This feed can handle materials 4" wide and .060" thick. Stroke lengths can be adjusted 4". No adjustment is necessary for stock thickness.

The Junior can be mounted to a press to feed material from any direction. It can be moved from press to press in a matter of minutes.

Ses-Matic Press Equipment, division of Special Engineering Services, Inc.,

7631 Wyoming, Dearborn, Mich.

Use postpaid eard. Circle No. 88



No. 9180 Toolmaker's Knee, 3" x 21/2" x 4"



No. 9192 Universal Right Angle Iron, 5" x 41/2" x 8"



No. 9201 Measuring Iron, 6" x 21/3" x 121/2"



ANGLE IRONS

with 6 precise

Working Faces

All faces are precision ground square or parallel within tenths. Clamp work to any face for multiple machining and inspection set-ups without relocating work. Add locating pins, stops, keyways, clamps and you have quickly-built special work staging fixtures.

Complete range of standard sizes available from stock. Special extralarge sizes to order from stock patterns. Write for Catalog 511.

TAKE IT TO

TAFT-PEIRCE



7 MECHANIC AVENUE, WOONSOCKET, RHODE ISLAND Use postpaid cord. Circle No. 358

PARTS FEEDER

This Elk-O-Matic vibratory parts feeder for oriented position feeding has an instantaneous rate-of-flow control, and is designed to give maximum part delivery. The vibrations prevent production interruptions by keeping an oriented line of parts ready for discharge.

Elk Engineering Works, St. Marys, Pennsylvania.

Use postpaid card. Circle No. 80



The New WELLS MODEL 58-B

A CONVERTIBLE BAND SAW



COMPACTLY BUILT . MODESTLY PRICED

Here's the all new Wells Model 58-B...a metal saw designed and built for double duty—double value. It's a compact, rugged, well guarded, extremely versatile unit...economically priced. As a horizontal cut-off saw, Model 58-B features quick-action vise (swivels to 45°); automatic shut-off; adjustable guides. Capacity: 6" x 10" rectangular shapes; 6" dia. rounds. For vertical use, swing head to upright position and install work table. Optional wheel-handle unit provides complete mobility. Write for complete information.



The Pioneers of Horizontal

METAL CUTTING

WELLS MANUFACTURING CORPORATION

707 Coolidge Ave., Three Rivers, Mich. Use postpaid card. Circle No. 359

REPLACE SOLID BUSHINGS with JERGENS ADJUSTABLE BEARINGS



JERGENS "LIVE" BUSHINGS


- Increase Speeds, Feeds, 200%
 Reduce Tool Breakage
 Eliminate Bushing Wear
 Use Economical Carbide Cutters
- Provide Greater Precision
 Available for ½" to 6½" Shafts
 Will stand greater sidewall pressures

Get time, tool, and money-saving advantages by replacing solid bushings with Jergens adjustable roller bearing units. Available for ½" to 6" shafts or with straight roller bearings where space is a factor in ½" to 2" shaft size. Write for information.

DONLEY PRODUCTS, INC.

Dept. MT-4 . 11106 Aven Ave. . Cleveland 5. Ohio


Use postpoid card, Circle No. 347



Use postpaid card, Circle No. 351

Supply your machinists with HLEN NO-BOUNCE HAMMERS

CONTROLLED BLOW PROFITS are yours with TAHLENS



WRITE for folder, prices and nearest Distributor Dept. M-4 TANLEM HAMMER CO. 1729 1st South, Seattle 4, Washington

Use postpoid card, Circle No. 360

IMPORTANCE OF CONTROLLED MICROSTRUCTURE

A consistent and uniform microstructure in a casting assures consistent and reproducible behavior from the standpoint of machinability. Castings having an abrasive outer skin, which may include oxide, minute imperfections, or surface decarbonization, cause rapid initial tool wear and reduce machining efficiency.

By specifying Meehanite metal, the production engineer can expect to obtain maximum life from cutting tools. The free machining qualities of Meehanite castings are the result of control in the process of manufacture and the achievement of structural uniformity in the finished

For a free guide to machining Mechanite metal, write to: Mechanite Metal Corporation, 714 North Avenue, New Rochelle, New York.



MFFHANITE CASTINGS ARE MADE ONLY BY MEEHANITE FOUNDRIES.

SOLID CARBIDE DRILL FOR HIGH TENSILE ALLOYS

The Atrax Co. announces a series of solid carbide drills for heavy duty drilling of high tensile alloys and steels.



Known as the Series 1806 "Hi-Ten." the design features straight shanks. two straight flutes and right hand rotation. The drills will be available from stock in 29 fractional sizes from 1/16" to 1/6".

The manufacturer recommends the drills for drilling hardened steel up to 65 Rockwell C and for production applications on exotic metals, high tensile and high alloys through 56 Rockwell C.

The Atrax Co., Newington 11, Conn. Use nestpaid eard, Circle No. 30

DRILL FEED UNITS




for drilling, tapping, milling, boring. Cam, hydraulic, or lead screw. Many sizes. 1/2 to 15 hp. Avev Division, Motch & Merryweather Cincinnati 1, Ohio

aveu

Use postpaid card. Circle No. 362

DURANT HEADED PINS



All tool steel Rockwell C 58/60 - honed finish, no pickup - h left soft and are guaranteed uniform. Attractively priced at \$12. to \$19. per C. We manufacture 103 and stock 103 sizes for immediate delivery.

Available through our distributor or order direct.

Write for complete prices and details

DURANT TOOL CO. 17 THURBERS AVENUE PROVIDENCE S RHODE ISLAND

Use postpaid card. Circle No. 363

Reduce wheel dressing costs with

Victory Diamond Dressers are made of selected African diamonds, skillfully set by diamond tool craftsmen to eliminate breakage. Yet you will find our prices unusually low, enabling you to get two or more tools from us for the same price you now pay for one, in some cases.

CTORY DIAMOND DRESSERS

Victory Diamond Dresser Prices

Carat	1/4	1/3	1/2	3/4	1	1 1/2	2	2 1/2	3
Price	\$2.75	3.50	5.00	7.30	10.00	14.80	18.50	23.00	27.50

Stock sizes: 7/16 x 6: 3/8 x 6: 7/16 x 2: 3/8 x 2. No charge for other mountings.

THIS MONTH'S SPECIAL

Reject Thread Grinder Diamonds For Many Different Uses In Any Shop.

1/4" x 1"; 1/4" x 11/4"; 3/4" x 13/4"; \$2.00 per tool. Six tools minimum order.

Dept. M., P.O. Box 348, East Orange, N.J. - Tel. ORange 4-4874

Export inquiries invited.

DIAMOND TOOL OMPANY, Inc.

VICTORY

Prompt resetting service.



HIGH-SPEED PARTS FEEDER

This unit is used for feeding, orienting, and counting a large variety of objects at high speeds. Items such as washers, blanks, nuts, bushings, discs, and bearings can be handled at speeds up to 3000 parts per minute.

Count-O-Matic Inc., Division of U.S. Engineering Co., 40-24 22nd St., Long

Island City 1. N.Y.

Use postpaid eard. Circle No. 91

DIXIE CARBIDE ROUT-O-MILLS



EFFICIENTLY ROUT, MILL AND TRIM THE HARDEST, MOST ABRASIVE PLASTICS



Custom designed Dixie Carbide Rout-O-Mills rout, mill and trim "hi-hard" plastics such as reinforced fibreglass, melamine, Plexiglas, Expoxys and laminated plastics. Exclusive tooth designs provide much faster cutting speeds and considerably longer tool life.

Carbide Rout-O-Mills are available in ½ to 1½ inch diameters... and tooth designs in many contours are available. Send for Rout-O-Mill Bulletin.

Contact Dixie Tool Industries for machining and engineering assistance in plastics fabrication.

Complete Carbide Tool catalog available upon request.

Dixie Tool Industries, Inc. Bridgeport 2, Michigan.



100

SPEED REDUCER HAS 100 TO 1 RATIO

Abart now has a heavy-duty fractional horsepower speed reducer which will provide 100 to 1 ratio. Handling inputs of ¼ to 2 hp. at 1800 rpm, and 1/6 to 1-1/2 hp at 1200 rpm, this unit has a right-angle drive and is fully enclosed when mounted in all positions. It can be furnished with input or output shafts projecting from either or both sides of the housing.

Abart Gear and Machine Co., 4834-36 W. 16th St., Chicago 50, Ill.

Use postpaid card. Circle No. 92



COMPACT ... ONLY 2" WIDE! DRILLS 5/16" IN STEEL!



PRECISE AUTODRILL

It takes little space (just 2" wide, 12" long, 7" high) — mounts in any vertical or horizontal position on 2-inch centers — has 5/16" drilling capacity in steel! Precise Autodrill is a fully automatic drill unit with depth accuracy to .001". It's electrically operated, has air controlled advance and retract with continuously variable hydraulic infeed. Maximum stroke is $1\frac{1}{2}$ ". Spindle speeds range up to 6000 rpm. Compact, modular design permits single or multiple setups — an electric and pneumatic interlock is provided for automated setups. Two compact tapping heads are available — handle up to #10, and 5/16" taps.



Grinder-Millers, Power Quills, Jig Grinders,
Milling Machines, Automatic Drill Units,
Cutting Tools, Vapor-Lub Cooling,
Sklero Hardness Tester
Quality and Precision Since 1882

PRECISE AUTODRILL CORPORATION

3731 Blue River Road, Racine, Wisconsin, U.S.A. Branch Plants Precise, G. m. b. H., Duesseldorf, Germany

franklin adv. P103

Spraymist

PRECISION MIST CONTROL

Only Spraymist provides these exclusive features

- Mist forms at the Jet Tip... not in the unit, preventing loss of coolant due to condensation—yielding high efficiency and economy in operation. Needle Valve at each jet tip conveniently controls uniform, continuous mist—from superfine to heavy spray permits multiple jet operation. Easily replaced jet tips.
- Compact Unit Design—Includes ALL necessary controls: Trap-Filters—Regulator—Gauge—Solenoid Valve—Reservoir.
- Automatic Operation—Mist starts and stops automatically as it is tied in the operation of your machine.
- Built to Last—Sturdy construction—Choice of 18 ounce, 1 gallon or 5 gallon units.

Write today for Bulletin F-8.

LUBRICATING CORPORATION
159 West Passaic St. • Rochelle Park, N. J.



SLACK GRANITE LAPPING PLATE

A noncontaminating hand lapping plate to produce finishes on nonferrous metals and nylon is now available from DoAll.

This plate has diameters of 12" or 18" and is 3" thick. Lapping surfaces have \(\frac{1}{6}\)" deep serrations spaced \(\frac{1}{2}\)" apart. According to the manufacturer, the advantages of such a plate are finer surface finish, better appearance, and elimination of the danger of a con-



taminator causing malfunctioning of the lapped part.

The DoAll Co., Des Plaines, Ill.
Use postpaid card. Circle No. 93

REPCO Time-Saving Tools

ADJUSTABLE V-BLOCK DRILL JIG

Saves Set-Up Time— Increases Output

Here Is a versatile and occurate V-Black that makes center and off-center drilling, tapping, and reaming easy and precise. Four-way V-black adjustment simplifies handling a wide range of wark. Fast, easy pasitioning and clamping speed production. A centering locator plug and T-slots in the mounting surface plates assure fest, easy, en-center adjustment. Drill capacity #80 to ½" diameter. Handles stock from ½" to 2" diameter.



TRUE-CENTER ADJUSTABLE



The REPCO Adjustable Holder is a precision-built tool, having two-piece construction which provides fast adjustment of the main body to compensate for as much as "ja" machine mis alligament, Cuts down on tool wear, brookage, and scrap.



Save time with this versatile 2-Piece Machine Vise Set, Use as general-purpose vise, angle-black, or separate clamping device. Opening limited only to length of machine have Light coverable have all and 8".

CHUCK JAW TRUING-RING SET



This Ring Set soves time, cuts cost of boring jaws. With correct sizenstar rings at head, you gain hours of productive time. Plotted rings range from 1" to 4" by ½" logrements. Handy pagnyes rack keeps rings

COMBINATION LIVE-CENTER SET Heavy-duty live con-





With his complete information—Exclusive agent territories one



ROCKFORD ENGINEERED PRODUCTS CO.

2332-23rd Avenue . . Rockford, Illineis



Use postpaid eard. Circle No. 94

HEAVY-DUTY UTILITY VISES

A 640 line of utility vises has been designed specifically for rugged use, according to its manufacturer, Wilton Tool Co. No. 643½ has a jaw width of 3½", an opening of 4", and a jaw depth of 3". No. 645 has a jaw width of 5", an opening of 5½", and a jaw depth of 3¾".

Wilton Tool Mfg. Co., Inc., 9525 Irving Park Rd., Schiller Park, Ill.



PRESSES





Press Brakes · Straight-Side-Type Presses · Press Brake Dies Hand and Power Bending Brakes · Special Metal-Forming Machines

DREIS & KRUMP

7440 South Loomis Boulevard, Chicago 36, Illinois
Use postpoid card. Circle No. 369

HIGH-TEMPERATURE BOLT

Internal wrenching bolts for temperature applications to 1800° F. are now being produced by Mercury. They are made of high-temperature material, AMS 5735, 19-9DL, Inconel X, M-252, titanium, or other heat-resistant alloys. Heads are designed to accept standard Allen wrenches and can be supplied with drilled holes for lockwire installations.

Mercury Air Parts Co., Inc., 9310 W. Jefferson Blvd., Culver City, Calif.



Use postpaid eard. Circle No. 98

NEW

SPEEDLAP 12" LAP-GRINDER

EXTRA BONUS features:

- Stainless Steel Construction
- 2-in-1 Reversible SPEEDALLOY Lap Plate
- Positive Flatness Control
- Rapid Foolproof Abrasive Change
- Ultra Quality Production Engineered



100% More Lapping Production Per Dollar
Over 50% Greater Production Capacity
30% Less Cost

Write for Complete Descriptive Bulletin No. 461C



SPEEDLAP CORPORATION

632 W. OAKTON STREET . SKOKIE, ILLINOIS

Phone: ORchard 6-1500





STANDARD AIR GAGES

Standard Gage Co. has introduced a new line of air gages which have adjustable magnifications for 35:1 to 28,000:1, and a choice of twenty-six stock dials.

Standard Gage Co., Inc., Poughkeepsie, N.Y.

Use postpaid card. Circle No. 96

CAMS

Complete Facilities For CAM MILLING and CAM GRINDING

To Your Specifications M SERVICES CO.

DIVISION OF HIMOFF MACHINE CO. 23-22 44th ROAD LONG ISLAND CITY, N.Y.


Use postpaid card. Circle No. 346

AUTOSONICS HAS AUTOMATIC TOTE-BOX CLEANER

A machine designed to automatically load, ultrasonically clean and degrease, dry, and unload tote-box loads of metal parts, has been announced by Autosonics, Inc. Called the AutoSonex V-72, it is particularly efficient for delicate assemblies and parts that cannot tolerate impingement or tumbling. Loads are immersed in a degreasing solution, rinsed with pure distillate spray and vapor, drained, and dried before discharging. The tote-box is cleaned at the same time as its contents.

Autosonics, Inc., 4217 Chestnut St., Philadelphia 4, Pa.

Use postpaid card, Circle No. 97





All hinges shown can be furnished with special holes, cutouts and bends to blue-print in metals to suit the job.

THREE-FOURTHS OFFSET

AUTO MOULDING & MFG. CO. 1110 E. 87TH ST. CHICAGO 19, ILL. SPECIFICATIONS

Open width 7/6" to 6" Gage Material .040 to .187" Pin Diameter .093" to 1/2" Lengths to 120".

SEMI-OFFSET

MARKING AND LAYOUT TOOL


This Model 360 marking and layout tool was designed to scribe straight lines and circles on sheet metal and other flat surfaces. Marked rods, which fit into the main body, are interchangeable. They are slotted for 1/4" measurements and finer spacings can be made with the adjusting wheel on the barrel.

Inventions Future, Inc., 918 Blackhawk Blvd., Rockton, Ill.

Use postpaid card. Circle No. 98



HAVIR 85 TON PRESS-RITE **INCREASES OUTPUT...SAVES DIES**



Havir 85 Ton OBI with built-in TIE RODS gives you additional frame strength for greater output.

Saves time and money because Tie Rods and Ram Rigidity minimize deflection . . . die life is increased by as much as 50%.

Get the complete story on Havir's full line 2 to 85 tons. Write:

HAVIR MANUFACTURING CO.

438 Cleveland Ave. • St. Paul, Minnesota





RADIUS DRESSER is a precision on gineered tool that will dress either a convex or a concave radius from .015" to 1.750" on all wheels up to 10" and it may be set to the exact radii desired. Graduated stops allow you to dress only desired portion of a radius. The spring tension journal insures chatter free operation. Price \$80.50



Price \$87.50

THE G-2 ANGLE DRESSER AND TOOL HOLDER

is actually two tools in one, having an easy to read vernier scale 0° to 180° giving occuracy within 2" of 1°; an excellent time saver to set up jobs to be milled, drilled, tapped and any desired angle.



\$149.50

(including case and both tools with diamonds)


FREE STORAGE CASE

of light-weight steel, with a hinged top, heavy duty latch and a blocked interior to insure the safety of the dressers when carried.

OUR FIXTURES

will dress most radii and angles tangent each other, similar to those shown below.


Distributorship available in select territories



BOX 2694 ELMWOOD STATION

PROVIDENCE 7, R. I

Use postpaid card. Circle No. 372



BENCH MODEL METLMASTR

Lennox has added a Bench Model TE-100 Methmastr to its line of shearing, forming and piercing machines. Edge cutting capacity of the machine is up to 12 ga. in mild steel plate, and 16 ga. in stainless steel,



Use postpoid card, Circle No. 373



Use postpaid card. Circle No. 374

MACHINE and TOOL BLUE BOOK

The bench model has a variable stroke length that can be adjusted from .022" infinitely through .110" without stopping the ½ hp motor.

Strokes per minute, cutting from 1750 to 3500, are automatically regulated to material thickness when the operator sets the stroke pointer. It cuts from 8' to 15' of material per minute.

The manufacturer points out that all of the production and safety features of the firm's three larger floor models are built into the bench model.

Lennox Tool and Machine Builders, Div. of Lennox Industries, Inc., Lima, Ohio.

Use postpaid eard. Circle No. 100

CUT-OFF MACHINES FEATURES INCREASED CAPACITY

A considerable increase in power and capacity over the previous model, plus a hollow arbor mist coolant and a retractable size gage are features of

PERMANENT BRAND NEW MAGNETIC CHUCKS

Eliminates clumsy fixtures and jigs a Retains helding newer indefinitely a Non-Magnetic steel base gives greater stability a Insensible to shock and the effects of cooling fluids a No need of electricity as the danger of short circuits is eliminated.



- Precision made
 Fully guaranteed
- Imported

1	RECT	TYPE		
	lize nches)	Height (inches)	OUR
4	X	6	2%	\$ 66.00

OUR PRICE \$ 66.00 \$ 77.00 \$ 88.00 \$130.00 \$205.00 \$358.00

CIRCULAR TYPE

Dia. OUR
(inches) PRICE

4 \$ 54.00
6 \$ 88.00
8 \$121.00

For tremendous savings, write for free circular

MANHATTAN SUPPLY COMPANY
The Cytting Tool Discount House
151-A Grand St., New York 13 • CAnal 6 4992

Use postpaid card. Circle No. 375

KNURLMASTER Hand Knurler

FOR 1/8" TO 1" STOCK Without Distortion!

For small production runs on 1/6" to 1" stock, Exclusive screw design gives perfect knurl pattern. Furnished with 3 hardened straight or diamond pattern knurls of standard 1/2" dia. Forged steel frame is self-centering. Write for illustrated folder.



80-C MAGNOLIA AVE. WESTBURY L.I., N.Y.

Use postpaid card. Circle No. 376



Multiford BENDER CUTTER

CUTS, BENDS, PUNCHES

Available in hand, air and hydraulic models, the MULTIFORM is shipped complete with full assortment of dies and mandrels to punch, bend, and cut round or flat brass, branze, aluminum, steel, etc., up to 1/2" x 8".

J. A. RICHARDS CO.

MODEL C



Delta's latest swinging arbor 12" cutoff machine.

This model can handle 1½" diameter solid round bar steel on a production basis. The company reports its new cut-off unit will cut all bar stock and angles usually used in plant maintenance work.

Get the straight

DOPEL

You can count on Tamms quality Blue Layout Dope. Won't chip, crack, or flake. Drys fast, highly oil resistant. Get the straight dope.

get Tamms!

WRITE FOR SAMPLE!

Tamms INDUSTRIES CO.

228 North La Salle Street, Chicago 1, Illinois

WHERE YOUR BUSINESS IS APPRECIATED!
Use postpoid card. Circle No. 378

The machine, with an abrasive wheel, can cut to a tolerance of less than .005", according to the manufacturer. This accuracy is achieved by a combination of power (5 hp) and surface speed (over 12,500 sfpm), plus a size gage that compensates for heat expansion created during cutting of ferrous pieces.

Rockwell Mfg. Co., Delta Power Tool Div., 486 N. Lexington Ave., Pittsburgh 8. Pennsylvania.

Use postpaid card. Circle No. 161


HIGH SPEED 14 SPINDLE TAPPER

A high speed multiple spindle tapping machine, capable of performing up to 60 cpm at 1600 rpm, has been announced by Precision Tool and Mfg. Known as the Deka • Drill No. HST-714, the machine is suited for automated type jigs and fixtures.

The 14 spindles are adjustable in any pattern within a head area of 7¾" x 12¼". A template cluster box with slip spindles can also be provided.

A specially built reversing motor, capable of 240 empty plug reversals a minute, drives the tapper.

The table is hydraulically operated, and can be set for various depths



MACHINE and TOOL BLUE BOOK

within a 6" stroke. The stroke can be held at the top of the cycle to permit manual lowering when desired. The table and knee assembly can be adjusted over a 14" distance. Use mostnaid eard, Circle No. 102

GRIND AND POLISH IN ONE OPERATION

A new portable abrasive belt grinder combines the backstand idler principle of abrasive grinding with power and portability for better grinding and finishing. Are reports that the new tool grinds and finishes in one operation, because the abrasive belt method leaves a smooth, straight line finish, with no gouges or swirls left in the work to require further finishing. The belt runs at 7000 sfpm speeds. Resilient rubber contact wheel eliminates chattering even when working on rough surfaces.

Medium, hard or extra hard wheels are available.

Aro Equipment Corp., Industrial Div., Bryan, Ohio.

Use postpaid card. Circle No. 103





Model 3CH Wet Cut 63/4" x 63/4"

Rugged construction, built-in coolant tank & pump, foot lift to saw frame. Complete with motor, ready-to-go.

Ask your Industrial Distributor or write.

A SIZES Sales Service Mig. Co. 10 MODELS

2361 University Ave. St. Paul 14B, Minnesota Use postpaid card. Circle No. 379



Accuracy ± .0003 Over 120 stock sizes "Jet-Fast" delivery

The standardized ROSSPUNCH is stocked in tool steel and high speed tool steel. Let us supply you at one-third the cost of making them yourself-a 60% saving! Complete satisfaction guaranteed.

20 655

specifications, stock

and price lists are

yours upon request.

Write us today ort saving

morrow

Equipment co. inc. EGE AVENUE, ROCHESTER 7. N. Y.

!NEV! QUICK-ACTING HAND KNOBS







CATALOG INSERT

NEW 16 PAGE CATALOG

> CATALOG INCLUDES TRACING TEMPLATES

ALUMINUM

CAST IRON

JIG AND FIXTURE COMPONENTS

Latch Bolts
Cast Iron Hand Knobs
Aluminum Hand Knobs
Quarter Turn Screws
Shoulder Screws

Jig Feet (3 Types) Spherical Washers Fixture Keys Knurled Head Screws Toggle Shee Clamps & V-Pads

HOLD DOWN AND CLAMPING TOOLS

T-Nut & Stud Sets Step Block & Clamp Sets Flanged Nuts Cut Thread Studs Tee Nuts Coupling Nuts Adjustable Step Blocks Strap Clamps (Plain & Step Type)



Horthwestern

118 HOLLIER AVE.

-WRITE TODAY-

DAYTON 3. OHIO

Use postpaid card. Circle No. 381

Leitz

FOR ULTIMATE PROJECTION ACCURACY

8" OPTICAL COMPARATOR PLUS

GAGE Deep-Etch

STANDARD OR SPECIAL CHARTS



OPTO-METRIC TOOLS, INC.
137 BBYARICK STREET • NEW YORK 13, N.Y.

COMPARATOR has:

- Vertical light beam
- . 3 selective filters
- Indexing lens turret for 10, 20 & 50x
- · Retractable Vertical Illuminator
- . Circular Protractor screen
- 2-dimensional horizontal stage
- Distortion guaranteed within less than 1/2 % (per mil.)

DEEP-ETCH CHART SERVICE MEANS:

- · Precision plastic
- Unbreakable
- Scratch-proof
- Selection of Standard
 - Stock Charts
- Facilities for developing
 Special Charts

Request 8-page catalog TP200

HYDRAULIC ACCUMULATOR

Three functions are performed by this oil-hydraulic accumulator: Its power-storage chamber enables a lowvolume pump to supply a large amount of energy for a brief moment; a pressure compensator maintains a constant pressure so holding cylinders do not lose their grip; and surges and vibration are eliminated.

A hollow aluminum piston is proportioned to dispense a maximum



amount of fluid with a minimum gas charge and no danger of pressure lock. Six models are offered with 3000 psi, four with 3500.

Crescent Hydraulic Co., 1303 Otsego Rd., Allegan, Mich.

Use postpaid eard. Circle No. 105

What's Your Toughest Surface Measurement Problem—

	Measuring roughness of parts that are						
	☐ Extra-smooth?	☐ Inside small ID's?					
	☐ Short or narrow?	☐ Remotely located?					
	☐ Concave or convex?	☐ Of critical importance?					
	Measuring height and wid other widely-spaced irregu	th of waves, bows, steps and larities?					
	Measuring individual pits,	, flaws, scratches?					
	Measuring waviness aroun	nd surfaces of rotation?					
	Other:						
	Check and return this, and on standard or special P Microcorder® or Wavometer	Profilometer®, Proficorder®,					
NA	AME	TITLE					
CC	OMPANY	DEPT.					
AJ	DDRESS						
-							



CAN YOU — IN YOUR SHOP — MAKE UP A WELD JOINT?



In less than 2 minutes?

CAN YOU THEN WITH NO DIE CHANGE MAKE THIS SET-UP?...



. . . and have both done in less than 4 minutes?

HOW WOULD YOU MAKE THIS ONE?



You could have made all 3 joints shown in less than 15 minutes with your

"De Witt Weld Joint Making Unit"!

You should have onel investigate! "How simple!" one customer said.

Ask for Ed De Witt



Phone me todayi
Call me collect!
BUCKINGHAM 1-7000

My job is to make your job of weld joint preparation ensier.

Or . . . write for a sample.
(Tell me what joints you make)

WALLACE

SUPPLIES MFG. COMPANY

3605 N. Ravenswood Ave. Chicago 13, Illinois

Use postpoid card. Circle No. 385

ROUNDNESS MEASURING INSTRUMENT HANDLES LARGE, HEAVY COMPONENTS

Talyrond's new Model 2 roundness measuring instrument has a work table designed to carry components weighing up to 1000 lbs. and shafts measuring up to 50". When necessary, the work table can be removed to provide additional work capacity.



Measurements of roundness, concentricity, squareness and interrupted circular shapes are permanently recorded on an inkless polar chart.

Engis Equipment Co., Div. of Engr. and Scientific Instr., 431 S. Dearborn St., Chicago 5, Ill.



Clipper Diamond Products

diamond wheels ... using Natural, Man-Made or SND diamonds, with improved bonds in Resin.

CLIPPER DIAMOND TOOL CO. INC

345 Hudson Street, New York 14, N. Y.

Use postpaid card, Circle No. 386

RADIUS-ANGLE

QUICKLY on your SURFACE GRINDER

RADIUS DRESSER \$44.00

Diamond \$8.00

ORDER DIRECT on our 10 day money back guarantee

ANGLE DRESSER & ANGLE PLATE

\$49.00 DIAMOND \$8.00

Chatter Resistant, Spring Loaded Spindle

Hardened shaft-bearing adjustable for wear. Diamond always perfectly centered. Easily set adjustable 180° stops. All surfaces ground true from hole.
CAPACITY—1½" Convex to 4" concave

10" Wheel size for DoALL and NORTON Grinders—\$49.00. Diamond \$8.00.

14". 20" & 24" in stock, low cost.

CHATTER RESISTANT, SPRING LOADED, DUST SEALED, HARD-ENED SLIDE.

BALL THRUST BEARING.

PRECISION REMOVABLE ANGLE PLATE, GROUND 6 SIDES.

EASILY SET WITH PROTRACTOR OR SINE

ALL SURFACES PRECISION GROUND OR

ADAPTERS fit your RADIUS DRESSER to Cylindrical and Universal Grinders. LARGE RANGE, LOW COST.

The "Mighty Midget" Line

SPERMAN METAL SPECIALTIES . 2197 E. 2181 ST. . BROOKLYN 29. N. Y

Use postpaid card, Circle No. 387



EL BLUE

8-os. can fitted with Bakelite cap holding soft-hair

Popular package

Stops Lodden at bench; metal surface ready for layout in a few min-making Dies and utes. The dark blue background utes. The Templates sharp relief, prevents metal glare. Increases efficiency and accuracy.

Write for sample on company letterhead THE BYKEM COMPANY 2301G North 11th St. . St. Louis 6, M



Queen City

GRINDERS • DISC GRINDERS and BUFFERS
We know what goes into these Grinders
and Buffers! That's why we can make
this offer.

Point for point — you just can't beat QUEEN CITY Heavy Duty Disc Grinders and Buffers. Built to stand up under hardest use . . . heavy duty motors deliver full horsepower. Wheels, guards, switches, cords, eyeshields are of highest quality . . . selected to deliver long, trouble-free service.

Choose from a complete line of floor or bench types . . . in sizes from % to 10 H.P. and buy them for 20 to 30% under competing makes. Try them for 30 days on money-back guarantee!



write for FREE CATALOG TODAY!

3912 KELLOGG AVE. Cincinnati 26, Ohio "Known for Quality for Over 50 Years"

Use postpaid card. Circle No. 389



SIDE CUTTING ACTION OFFERED ON ABRASIVE CUT-OFF WHEEL

A cut-off wheel that features cutting action on both sides as well as the face of the wheel is currently being manufactured by American Emery Wheel Works, Richmond Sq., P.O. 1475, Providence 1, R.I.

Use postpaid eard. Circle No. 107



20 to 200 D.P.

Send your prints for quotations

- SPURS
- . HELICALS
- WORM AND
- STRAIGHT BEVELS
 LEAD SCREWS
- . RATCHETS
- . CLUSTER GEARS
- e RACKS
- . INTERNALS
- . ODD SHAPES



Use postpaid card. Circle No. 390

MACHINE and TOOL BLUE BOOK

THREAD DEPTH GAGE HANDLE

A universal adjustable depth gage handle which permits gaging both size and depth of all drilled and tapped holes in one operation is being made by Heli-Coil Corp.

The adjustable handle feature provides economy of operation by dispensing with the need for grinding a step on the go-nib for each thread size and depth.

The adjustable handles are available



in four sizes and may be used with American Standard thread gages for measuring standard tapped holes, and with a pin gage for measuring drilled holes, in addition to the firm's line of thread gages.

Heli-Coil Corp., Shelter Rock Lane,

Danbury, Conn.

Use pestnaid eard. Circle No. 108



The Lucifer Furnaces, Inc., Series 4055 furnaces are manufactured in ten standard models with 800° F. or 1250° F. maximum operating temperatures. These

The Lucifer Furnaces, Inc., Series 4055 furnaces are manufactured in ten standard models with 800° F. or 1250° F. maximum operating temperatures. These furnaces are designed for tempering, drawing, heat treating aluminum, and glass annealing. Each furnace is a complete unit . . . controls included. They are equipped with a large fan and motor to force circulation of air in the working chamber to insure maximum uniformity of temperature.

All electric heat treating furnaces by Lucifer feature • low initial cost • low upkeep

 top production performance
 minimum replacement downtime. For free engineering advice, parts, or product information . . . write, wire or call . . .

LUCIFER FURNACES, INC. Neshaminy 1, Pennsylvania Diamond 3-0411

VIBRO-GRAVER INDENTIFIES SHOP ITEMS

Permanent identification of tools, machinery, and work is quickly provided with the portable electric Vibro-Graver. A carbide point writes at a speed of 7200 vibrations per minute. The unit is encased in plastic and has a control-wheel adjustment for fine, medium, or coarse strokes on metals, marble, tile, glass, plastics, leather, ceramics, and hard rubber.

Burgess Vibrocrafters, Inc., Commercial Products Division, Grayslake, Ill.




Use postpaid card. Circle No. 109

INSERT IS DOUBLE-LOCKED TO PREVENT PULL OUT

A profiling tool with double-locked carbide insert and a dial for adjustment of the chip breaker has been announced by Kennametal. Principal features of the tool are positive locking of the insert (1) against two walls of the tool recess by an eccentric or campin through a center hole in the insert, and (2) in its seat by a top clamp held by a socket head cap screw. The insert will not be pulled out while back facing or contouring.

New to this type of tool also is easy and precise adjustment of the chip

.UCIFER




breaker with Kennametal's "Dial-A-Breaker." To simplify changing, indexing or inverting the insert, the chip breaker is raised by a spring plunger when the clamp is released.

Diamond-shaped inserts have a 55-deg. nose angle and are set in the holder at a 5-deg. negative side and back rake to provide four cutting points.

Three styles of holders that meet most machine tool requirements are available. Kennametal Inc., Lloyd Ave., Latrobe, Pa.

Use pestpaid card. Circle No. 110



"J. D. is our best account. Henry is showing him the town."

THE BEST

PORTABLE ELEVATING TABLE

YOU CAN BUY . . .

(Eliminates Cranking)



2000 LBS. OR *1000 LBS. CAPACITIES

A precision made MIDWEST TABLE Costs no more!

- It's hydraulic . . . positions work or feeds at desired height without use of hands
- Rigid cast construction
- ► Top turns 360° and clamps
- Foot release valve to lower
- Machined top surface can be used as work table
- Roller bearing casters with ball bearing swivels
- Floor clamping available extra

Write today . . . specials on request

MIDWEST

112 WERSTER ST., DAYTON 2, OHIO

← Chandler-Duplex → ADJUSTABLE BALL CENTER



Save Time— Insure Accuracy

Perfect Alignment
in Seconds

The introduction of the first live ball bearing center was a definite improvement over the old dead center. Now our added feature of adjustability further improves it and rounds out its usefulness.

A precision product fully guaranteed for quality and performance by the Manufacturers of the CHANDLER DUPLEX Boring and Facing Tool Heads.

For Complete Details Write to:

CHANDLER TOOL CO., Muncie, Indiana

Use postpaid card, Circle No. 394

SHEARS CLEAN TO ACCURATE LENGTHS





With each press stroke, unit accurately cuts off tubing and shapes into lengths of ½" ±.010", or more. The ends are cut clean with a minimum of burr or distortion . . . Shearing blades make thousands of

blades make thousands of cuts before resharpening.



No. 12 unit cuts up to ¾" O.D. x 3/32" wall.
No. 2 unit cuts up to 2" O.D. x ¼" wall.
No. 3 unit cuts up to 3" O.D. x 3/16" wall,
or up to 3½" O.D. x ½" wall.

Odd shapes handled in sizes equivalent to unit's O.D. capacity.

OGEL TOOL & DIE CORPORATION

1827 NORTH 32ND AVENUE, STONE PARK, ILLINOIS

REDESIGNED RADIAL DRILLS

Morris Machine has announced a price cut in its Mor-Speed line of heavy duty radial drills—now available for \$7,225. The machine has also been redesigned to incorporate the latest advances in machine tool design and engineering.

Providing 12 spindle speeds, 6 spindle feeds, and 12 inch spindle travel, the radials feature completely centralized controls, fully enclosed elevating mechanism, with electric column clamp, on 11" models and roller bearing mounted head. External electrical conduit has been eliminated, and column clamp control buttons are flush mounted as is a 110 volt accessory receptacle. Total vision lighting assures complete illumination of the workpiece and elimination of operator blind spots. A new positive displacement lubrication system provides maximum lubricating efficiency.

The Morris Machine Co., 2019 Eastern Ave., Cincinnati 2, Ohio.

Use postpaid eard. Circle No. 111





Use postpaid card. Circle No. 396

TAP GRINDER

Sharpens Chamfers, Flutes and Spiral Points



Model 1100

 Capacities No. 0 Machine Screw to 2½" Hand Taps.
 Write for catalog

HENRY P. BOGGIS COMPANY

710 E. 163rd Street, Cleveland 10, Ohio

Use postpoid card. Circle No. 447

CERROTECHNICS

in chucking irregular workpieces



*T.M. Cerro Corp.

CERROTECHNICS is the practice of using low-temperature-molting CERRO* ALLOYS to expedite many industrial operations.

Fer instance: an accurately fitting pair of chuck laws is quickly made by casting CERROMATRIX against the workpiece. Write for further information.

See us at the ASTME Show, Coliseum, N.Y. May 22-26

CERRO SALES CORPORATION

Room 1505, 300 Park Avenue, New York 22, N.Y.



Gaertner 2"x 4" toolmaker's microscope for measurement to 0.0001" and 1 minute of arc

You'll find the Gaertner Toolmaker's Microscope as part of the standard inspection equipment in the ideally-equipped shop or lab. It will do the work of many single-purpose measuring and inspection instruments with greater convenience and accuracy.

Full 2" precision lead screws permit measurements over 2" x 2" of the instrument's range without the use of

gage blocks or rods.

Independent and combined rotation of the cross hairs in the protractor ocular speed up measurements and simplify measuring procedure. The instrument's versatility may be increased through the addition of such accessories as thread and radius templates, camera and spotting attachments, fine motion focus, direct-reading counters, and interchangeable optics for varying magnification and field.


Write for Bulletin 147-56

Use Postpoid Card, Circle No. 398 1221 Wrightwood Ave., Chicago 14, III., BU 1-5335

Gaertner SCIENTIFIC CORPORATION

AIR-HYDRAULIC RIVETER CUTS COSTS, AVOIDS PUMP SPACE

This Model 211 riveter has a 12" throat depth and is designed to automatically feed and set either of two lengths of rivets up to 5/16" diameter. Operating on 80 psi air pressure, its hydraulic booster and cylinder (not shown) deliver a setting force of approximately 10,000 lbs. This force is applied only during the last downward ½" travel of the spindle. The first 3½" of down stroke and the retract stroke uses low-pressure oil.



Selection of rivet length is done automatically when a section of the workpiece contacts a micro switch mounted on a work-support bracket. Air, controlled by a foot valve, raises the anvil pin and floats the rivet past obstructions.

Tubular Rivet & Stud Co., Quincy 70, Massachusetts.

Use postpaid eard. Circle No. 112

END MILL SHARPENING FIXTURE'S SPINDLE FLOATS ON FILM OF AIR

Harig Mfg. Corp. has introduced a sensitive end-mill and milling cutter

sharpening fixture featuring a spindle that floats on less than a .00015" film of air.

The flow of air to the spindle inhibits the entrance of grinding dust. Its smooth action permits the sharpening of tiny tools as small as 1/32" up to 1¼" shank capacity. Milling cutter sharpening range is thru 6" diameter.

Other features include graduated swivel base, fine blade-rest adjustment, hard chromium inlay, indexes and components to grind tapered, as well as straight, end-mills.



Harig Mfg. Corp., 5757 W. Howard St., Chicago 31, Ill.

MOST Value-Packed GRINDER MADE!





CARBIDE TOOL GRINDER



Model 153-6". Reversible ½ HP motor, 3450 RPM. 1½" wide wheels. Every part oversize for rugged, long-lasting use. Just \$201,80

BALDOR

MODEL 153-8"

Feature for feature, no other grinder offers so much for so little. Compare HP rating, wheel size, shaft diameter, bearing size with any other similar-type grinder. You'll quickly see why you get more with Baldor!

- Big ½ HP motor; won't burnout even if repeatedly overloaded!
- Wide-clearance design provides maximum working room!
- Large 8" first grade wheels!
- Heavier ¾" arbor; larger ball-bearings!
- Dynamically-balanced rotor extra smooth operation!
- Exhaust-type guards!

Write today for Bulletin 321N on complete line of Baldor Grinders and Buffers!

BALDOR ELECTRIC CO.

4353 DUNCAN AVE.

ST. LOUIS 10, MO.



DUAL TORQUE WRENCH

A Twin-Torq wrench offering two different torque limits without the need for dials or adjustment has been developed to meet the need for a single tool with dual purposes. The manufacturer claims it can make fast and positive inspection of torque tolerances

of previously tightened assemblies. It is equipped with two opposing drive tangs, and each torque value is set for a specific limit and sealed to prevent undetected tampering.

The wrench also permits accurate assembly of castellated nuts to facilitate cotter-pin and hole alignment

without overstressing.

Jo-Line Tools, Inc., 8442 Otis St., South Gate, Calif.

Use postpaid eard. Circle No. 114



NEW 1:1 Ratio SPINDLE MOUNTED CONTOUR WHEEL DRESSER



TRACAFORM solves your wheel dressing problems:

- · Complex Shapes to "tenths" accuracy!
- . Low in Cost (appr. 1/5 cost of other spindle-mounted dressers)
- · High in performance and quality!
- Dresses wheels from 7" dia.by 4"wide-down to the smallest diameter mounted wheel!
- Unnecessary to use costly lapped diamonds!
- Stylus easily ground to exact shape of diamond! Diamond wear easily corrected!
- Intricate forms can be dressed into the wheel repeatedly without losing location or disturbing work being ground.
- Fits most surface grinder spindles using 7" dia. or less grinding wheels!

TRACAFORM CORPORATION



11380 KALTZ - WARREN, MICH.



This new shatter-proof Electro-Lock Shield, due to its interlocked power and light circuits, will not permit a machine to be operated when the Shield is not in a full protective position.

Write for complete information today.

Junkin Safety Appliance Co.

3121 MILLERS LANE . LOUISVILLE 16, KY.

Use postpaid card, Circle No. 400





MICROMETER OFFSET ADJUSTMENT SAFETY-STOP ROUND CONTOUR

GROUND AFTER HARDENING

> HOLDS TOOL **VERTICALLY**

SAFETY ROUND TOOL BLOCK

HOLDS TOOL HORIZONTALLY

LEADING NAME IN BORING HEADS FOR 40 YEARS 19 MODELS Write for catalog

FLYNN MANUFACTURING CO.

Use postpaid card. Circle No. 401



Use postpoid card. Circle No. 402






We specialize in precision, stainless steel Pins, Dowels, Shafts. Quantity production of standard sizes includes miniature, instrument type pins, as small as .020 dia. For prompt quotations on your blueprints . . .

WRITE TODAY TO

THE PEASLEE METAL PRODUCTS INC. Tolland St. • East Hartford 8, Conn.

Use postpoid card. Circle No. 404



AMERICAN DRILL BUSHING ADDS TUNGSTEN CARBIDE LINE

A complete line of tungsten carbide drill bushings has been announced by American Drill Bushing Co. The bushings have approximately 50 times the wear life of ordinary steel bushings, according to the company. Several types are available including head and headless press fit, fixed, and slip renewable. The complete line is available in a variety of American Standard sizes.

American Drill Bushing Co., 5107 Pacific Blvd., Los Angeles 58, Calif.


Capacity of six 3/8" taps...the new ANOKA. Multiple lead screw tapping machine now yours for \$1,485


Operate Any Position! Adjustable
Highest capacity, most rugged tapping machine ever
offered at this price! Powerful enclosed 2 hp motor.
Operate in any position. Work 2 or more machines from
different sides in one operation with built-in auxiliary
switch, or work in clusters with other apparatus. Six
spindles are adjustable to any pattern . . . handles
6 N.C. %" taps in free cutting steel.

Special adaptors for mounting on drill press columns. Lead screws of fatigue-proof steel with tensile strength of 140,000 psi; Brinnell hardness of 280 Rockwell C. Min. stroke: ¾, max.: 3*. Precise depth control. Here's real high production massiveness! Shop-tested for 2 years on production runs.

Write for full details

COLUMBIA TOOL & DIE WORKS 716 39th Ave. N.E., Dept. B, Minneapolis 21, Minn.





ROTATING MIRROR MODULATES LIGHT BEAM

These devices stop machines automatically when any part of a person's body enters a danger area. The units are designed for direct mounting on presses and other industrial equipment such as shears and brakes.

This "Curtain of Light" consists of a wide-beam modulated light projector, a photoelectric receiver, and a control unit. The projector and receiver can be mounted up to 15' apart. Highly sensitive to partial obstruction, the




control units operate when 2" or more of the light curtain is obstructed.

The Clark Controller Co., 1146 E. 152nd St., Cleveland 10, Ohio.

Use postpaid card. Circle No. 116

KNEE-TYPE GUN DRILL WITH CHOICE OF FEED UNITS

Designed to facilitate drilling deep holes in ferrous or non-ferrous materials, using carbide tipped drills, this knee-type gun drill is offered by Leland-Gifford Co., with either self-





BY A QUICK, EASY, INEXPENSIVE METHOD Your business letterhead will bring literature WATTS BROS. TOOL WORKS Wilmerding, Pa.

Use postpaid card. Circle No. 407



Put Muscles In Your Lubricants

ANTI-FRICTION COMPOUND

A clean white powder. Improves cutting oils. Dies last longer. Solves tough lubrica-tion problems. Ask for free sample. SCIENTIFIC LUBRICANTS CO.

Chicago 13, III. 3469 N. Clark St. Serving Industry Since 1914

Use postpaid card. Circle No. 408



gear is custom-made

SPUR, SPIRAL, BEVEL, HELICAL, INTERNAL, WORM, RACK, SPROCKET, ETC.

We deliver to your exact specifications

Abart carries no stocks . . . every gear is precisioncut to order. Any type of gear . . . from any material, in any quantity, 96 D. P. to 5/7 D. P.-1/4" P. D. to 18" P. D.

Send B/P and specs or sample for estimate

WRITE FOR ABART GEAR BULLETIN

4829 WEST 16th STREET

CHICAGO SO, ILLINOIS

Use postpaid card, Circle No. 409

contained hydraulic feed or lead screw feed gun drilling unit.

Recommended for drilling accurate holes up to %" diameter by 7" deep, the self-contained hydraulic feed unit offers the advantages of uniform feed rate with simple feed rate changing. Pump and spindle are independently powered with a 11/2 hp spindle motor driving through a timing belt drive.

For holes having depth greater than 7", the Leland-Gifford No. 24C electromechanical gun drilling unit can be furnished with 12", 24" or 36" stroke. Driven by a 11/2 hp Dynabrake motor through a non-slip timing belt, the spindle can be run at speeds from 720 to 12,000 rpm with a 3600 rpm motor or at 360 to 6000 rpm with an 1800 rpm motor. Feed is actuated by and synchronized to the spindle speed and can

Buy safe "SHUR-GRIP"

drop forged HANDLES

Designed to hold 3 to 6 th, lead hammer heads more firmly — will not slip — keeps hammer head in shape longer — makes remolding outler, quicker, surer, less aspen-Write for circular and prices

COOK LEAD HAMMER SERVICE 67 MASSASOIT AVE., EAST PROVIDENCE, R. I.

Use postpaid card. Circle No. 410



MILLING SPACERS

The COLOR tells the THICKNESS ARTUS Spacers

made of plastic in various colors identify 14 thicknesses at a glance! .0005, .001, .0015, .002, .003, .005, .0075, .010-030. Speed up accurate fitting at low cost.



Illustrated Literature Free. THE ARTUS CORPORATION 201 South Dean St., Englewood, N. J. LOwell 7 0900


Use postpaid card, Circle No. 411

MACHINE and TOOL BLUE BOOK

be changed through pick-off gears from a minimum of .00019" per rev. to a maximum of .0015" in increments of .000015" if desired. A separate ½ hp Dynabrake motor powers the lead screw for rapid approach, set-up and rapid return.

This gun drilling equipment can be furnished as a complete machine, or as drilling units only. Leland-Gifford Co., 1003 Southbridge St., Worcester 1, Massachusetts.

Use postpaid eard. Circle No. 117



Could an

E-X-P-A-N-D-I-N-G PLUG GAGE

solve a gaging problem for you?

The Comtorplug expansion principle is unique... and proven. Hundreds of U. S. precision-production programs use it, including several of the very largest. The unique expansion plug gives true 2-point gaging. You see actual diameter in a fixed reading to fraction of .0001". You measure front or back taper exactly, also ovality, bell mouth, etc. Centering, alignment and pressure are automatic, allowing accurate use by all types of personnel.




"We've reduced rejects since using Comtorplug"

If you produce precision holes in volume

SEND FOR BULLETIN 50
COMTOR COMPANY, 62 FARWELL ST., WALTHAM 54, MASS

COMTORPLUG





Standard ZAGAR Gearless



Drill Heads

DRILL ANY NUMBER OF HOLES . . . IN ANY PATTERN . . . IN ANY MATERIAL ... ON ALL CENTERS!

Drill a maximum number of holes in one pass—as close as twice drill diameter. Zagar heads are built as a complete unit or may be adapted to any standard drill press.

Get more information in Bulletin B-4

ZAGAR, INCORPORATED 23900 Lakeland Blvd., Cleveland 23, Ohio



TOOLS FOR INDUSTRY SPECIAL MACHINER

Use postpoid card. Circle No. 413

EASIER SET-UP FEATURED ON AUTOMATIC THREAD ROLLER

An automatic thread rolling machine introduced by Hartford Special Machinery is capable of producing 135 to 400 pieces per minute. Thread lengths may be rolled from 1/8" through 11/2" and can be extended through 3" with special dies. Screw capacity is from No. 2 through No. 10 on the automatic model (400-R) and No. 0 through No. 10 on a manual model (400-M).

Simplified design makes for faster, easier set-up, as well as reduced maintenance time. Adjustable starter fingers are featured in which the height and stroke can be varied. A simple eccentric cam adjustment controls the relative position of the moving die for easy die matching.


The new models feature straight line feed rails. A simple mechanical type feed rail vibrator assures uninterrupted feeding of blanks.

The Hartford Special Machinery Co., Simsbury, Conn.

TOOL POST AND TOOL ADAPTERS FOR EVERY LATHE OPERATION

Kirkelie's line of lathe tool holders is designed to cover all models and all sizes of engine and turret lathes—even up to 60" swing.

On a production run, it is necessary only to have the proper tool adapter ready for each cut. Then, in any desired sequence, the tool adapters can be quickly set, positively locked and



designed to collect dust from single machines portable easily installed DUSTKOP Stops oust Self-contained Dust, top models like the '520," are practical and effective in collecting dust from single machines. They're designed specifically for

grinders, officers and other small wheel equipment.

These units are also easy to install

— are actually portable—and
very combined to operate.

We will be illustrated from the combined to operate.

GET manufacturing company

1402 E. Church Street, Adrian, Michigan

DUSTKOP AUTO SHAKE

ask for details

grinders tool and cut-



New \$300 precision cut-off saw paid for itself in 15 minutes

Navkut*, the new precision cutoff saw, cut production costs of "spacers" substantially at Unicorn Engineering Inc. (now owned by Computer Measurements Co., Sylmar, Calif.) The cost of spacers was reduced from \$8 to 80c each by Navkut's simple cut-off operation. During every 15-minute production run, the Navkut saw paid for itself. Such results aren't unusual with Navkut, the saw that can cut parallel tolerances to within .002" in ferrous, nonferrous, wood, and plastic materials with only two types of blades. Usually the cut finish and accuracy will be so precise there is no need for milling or grinding. All this, yet the Navkut saw costs only \$300. See for yourself how it can save you money. Write today for a free 15-minute demonstration in your shop.

Navkut saw is another product marketed by:



NAVAN PRODUCTS INC.

Subsidiary of North American Aviation, Inc. 960/F North Sepulveda El Segundo, California then easily lifted from the tool post after the cut is made.

Clamping or locking of the tool post

Clamping or locking of the tool post is spring-actuated to allow rapid interchange of tool adapters.

George E. Kirkelie Co., 8717 Darby St., Northridge, Calif.

Use postpaid card, Circle No. 119

PROFILER HAS TILTING TABLE

Rice Pump & Machine's redeveloped line of profile grinders extends the range of precision grinding to include grinding of die clearances, cams and contours plus a wide variety of finish grinding work. Some of the newly added features include a hinged access door to facilitate interior maintenance and a larger serrated table of 12" x 13½" with a 4-way tilt.

The center-line of the table coincides with the center-line of spindle so that grinding wheels always operate in the center of the table hole at all working angles. Spindle speeds are available in 20,000, 30,000 and 35,000 rpm ranges for the single speed machines and in 20,000-30,000 and 20,000-35,000 rpm for two speed machines. ½ hp, 3450 rpm motors are standard; ¾ hp motors are optional. These grinders are basically the bench type, but may be mounted on a pedestal or four-legged floor stand which the manufacturer provides.

Rice Pump & Machine Co., Belgium, Wisconsin.

Use postpaid eard, Circle No. 120



COMPACT, SELF-CONTAINED ULTRASONIC CLEANER

Both the generator and cleaning tank of this ultrasonic cleaner are housed in a one-piece stainless steel wrap-around cabinet. Only simple controls are needed to operate this 250-watt unit. Specifications: capacity of 3 gal.; and a 10" by 14" by 6" cleaning compartment.

National Ultrasonic Corp., 111 Montgomery Ave., Irvington 11, N.J.

Use postpaid eard. Circle No. 121



A NEW ELECTRIC HAND GRINDER



in the manufacture of die-casting, stamping and tooling. Grinding applications are unlimited with this Swiss precision-made tool.

For complete information, see your dealer or write:

GE/USL 33/1

VICTOR J. KRIEG, INC.
Precision-made power tools of unsurpassed performance
P. O. BOX 7, 1 DEPOT PLAZA, MAMARONECK, N. Y.

Weighs only 31/4 lbs. Power input: 250 Watts continuous. Spindle speed: 25,000 r.p.m., no load.



MULTIPLE SPINDLE HEAD USES DRILL PATTERN PLATES

Flexibility is stressed in describing a multiple spindle drill head now offered by United States Drill Head Co. called the Adjustafix, this head is actually a fixed center type which can be easily changed to different hole patterns. It is readily installed on standard or special machines now in use, and affords great flexibility for drilling, tapping, reaming, spotfacing, boring, counterboring, and milling operations.

Basic design provides a main drive box and a demountable pattern plate. A complete engineering changeover may be quickly made, leaving as much as 90% of the head intact! When changing to another job, only the pattern plate is changed and the spindles and idlers are relocated on the new pattern plate to conform to the new design. Spindle and idler construction are entirely separate self-contained assemblies so that tool speed required for a given job is obtained without any change of gearing in the main drive box.


United States Drill Head Co., 5298 River Rd., Cincinnati 33, Ohio.

FLAT BLANK FEEDER

A fully automatic, high-speed stacktop feeding machine for flat metal blanks of all sizes and shapes, and in small or large lots is now being built by Clark. It has a one-at-a-time magnetic pick-up of blank from the top of the workstack. Powered, magnetic rolls and magnetic belt transfer the blanks from pick-up to operating machine.



J. R. REICH MFG. CO. P.O. BOX 2152 DAYTON 29, OHIO



This self-contained caster-mounted unit permits quick removal for die change or shift from one operating machine to another. The feeder has operating speeds up to 100 parts per minute.

Clark Industries, Delaware, Ohio.

COMPACT PUNCH & DIE SHARPENER IS PORTABLE

Simplicity of design and operation are features of a portable, bench-type grinder from Punch Products. The grinder provides a convenient method for sharpening most makes and types of standard and special punches and dies.

Outstanding features include: convenient handle to swing punches and dies across the grinding wheel; precision machined vee holder at 90° to wheel; knurled feed handle to aid fine feeding of work to wheel; and increments of .500" are scribed on handle

Another

VICTOR VALUE

TOP QUALITY-LOWEST PRICES

Our Special Import

WHEEL DRESSERS

Made of selected, full individual stones, mounted in 7/16" diameter x 6" long cold rolled shank.

Korat	Regular Price	New Price
1/4	\$ 6.00	\$ 2.85
1/2	12.00	5.00
3/4	21.00	7.50
1	30.00	10.25
11/2	54.00	15.00
2	75.00	20.00
31/2	102.00	26.00
3	130.00	32.00

These diamonds can be set in any shank to your specifications for \$1.00 each extra.

Order Today-Immediate Shipment from

VICTOR MACHINERY EXCHANGE, INC.

Dealers in Tool Room Equipment

New York 13, N.Y. Tel.: CAnal 6-5576

Use postpoid cord. Circle No. 417

MASTER WORKMANSHIP REQUIRES



MASTERHEADS

BORING - TURNING - RECESSING - UNDERCUTTING - TAPER CUTTING



WOHLHAUPTER UNIVERSAL FACING AND BORING HEADS FEATURE:

- Automatic Feeds and End Release
- 9 Sizes to 36 1/4"
- 12 Feeds in 0.0008" Increments

Increase the capacity of any machine without facing facilities.

- WRITE FOR COMPLETE CATALOG

Sole Agent KARL A. NEISE, Inc. 404 4th Ave., New York 16, N.Y. • MU 3-0481

MODERSTOOLS

PRECISION

RAISE GRINDING PRODUCTION



FOR \$2.70



A typical Desmond Huntington grinding wheel dresser costs about \$2.70 from your distributor, yet it substantially increases grinding production, makes wheels cut better, and lowers grinding costs. By dressing all your grinding wheels regularly you remove inefficient dull particles and loaded metal, expose a fresh new grinding surface. Your Desmond distributor can furnish the exact model you require. Ask his advice.

The only complete line of grinding wheel dressers and cutters

Desmond

The Desmond-Stephan Mfg. Co. Urbana, Ohio

Use postpoid cord. Circle No. 419



hub for accurate control of feeding. The grinder has a ½ hp, 3450 rpm motor.

Punch Products Corp., 370 Babcock St., Buffalo 6, N.Y.

Use postpaid eard. Circle No. 124

LOW-COST MILL FOR HYDRAULIC DUPLICATING

A special vertical milling machine for hydraulic duplicating has been developed by U.S. Burke Machine Tool Co. Built from the company's standard components, the mill is built to sell for less than similar machines used for hydraulic duplicating, according to the builder.

Extra rigidity is acquired by raising and lowering the knee to follow the contours of the master rather than actuating the quill. The heavy knee cylinder is mounted in place of a conventional vertical feed screw, and



"Qualifications? Well, I've always been rather mechanical minded."


manual vertical knee feed is retained to facilitate set-up.

Air hydraulic longitudinal feed to the table is available with either manual or automatic air-operated and mechanically controlled in-feed. In the case of air operation, the table is fed in automatically the pre-determined amount at the conclusion of each longitudinal stroke.

Table sizes are available from 10" x 36" to 10" x 54" in 6" increments.

U.S. Burke Machine Tool Co., Cincinnati 27, Ohio.

Use pestpaid eard. Circle No. 125



WORK-HOLDING JIG PNEUMATICALLY OPERATED

An automatic self-centering work-holding device that operates from a shop air line has been announced by Heuser. This "Sure-Center" is claimed to be ideal for drilling, tapping, milling, counterboring, and reaming, as well as screw machine secondary operations on round, hex, or square stock, standard or odd-shaped smooth or rough castings.

It has two movable gibbed master jaws, working from levers connected to a cam which will repeatedly center a piece part within .0015" or better.

Heuser Mfg. Co., 1638 N. Paulina St., Chicago 22, Ill.

Use postpaid card. Circle No. 126

LINLEY JIG BORERS



Give You Maximum Utility—At Low Cost

The improved Linley lig Borers are more elicient than ever. Accurate and fast in operation—easy to set up. Made for the exacting requirements of small part precision work. Using Linley lig Borers allows larger capacity borers to be used where intended, on heavier jobs. Once you've installed a Linley, you'll wonder how you got along without it in your shop.

Table Size: 7" x 171/2"
Table Travel: 61/2"x10"
Send for Complete
details.

LINLEY BROTHERS CO.

JIG BORERS - RIVET SPINNERS 663 State St. Ext., Bridgeport 1, Conn.

Use postpaid card. Circle No. 420

BAR and TUBE PRINTER for hand or conveyor use



Rolled by hand along rounds or flats, or mounted over conveyor rolls, this printer provides simple, economical identification code printing. Guide rolls adjust and center printing wheel for clear marking on metal or plastic ½" diameter up.

Wheel accepts E-Z Set rubber type in single type characters or complete legend in one strip. Easily pressed into place, or stripped off for quick change.

Sponge rubber ink roll holds enough ink for 8 hours; easily interchanged for color code change.

Lightweight magnesium frame, rugged construction; weight 7½ lbs. Write for literature, Model T-55.

PANNIER MASTER MARKERS

264 Pannier Bldg., Pittsburgh 12, Pa.



DRILL WITH 32-SPINDLE TURRET IS DIRECTED BY NUMERICAL CONTROL

A numerically controlled Fosmatic turret drill, with a single complement of tools in its 32-spindle turret, is reportedly able to perform about 90% of all the drilling-tapping jobs in the average shop.

The drill's 32 spindles can store drills, reamers, taps, milling cutters, and counterbores needed for hundreds of different jobs. Positioning and turret selection are controlled by a General Electric system providing system accuracy of plus or minus .001".

The Fosmatic turret drill features 3 hp, enough to handle a 1½" drill in cast iron and still is capable of tapping a No. 2-56 thread. The spindles have 8 feed rates from .001"/rev. to .030"/rev., and 16 speeds ranging from 65 to 2500 rpm. Spindles available are drilling spindles, lead screw tapping spindles and heavy duty spindles for milling.

The table is 18" x 34" and has 18" x 24" of travel. Table top to spindle nose

is 23". Zero offset permits positioning the workpiece at any location on the table.

The Fosdick Machine Tool Co., Cincinnati, Ohio.


Use postpaid card. Circle No. 127

"SHOCKPROOF" NYLON DRILL

The new No. 1144 ¼" Safe-T-Drill is said to have the advantages of greatly increased safety through double insulation, double protection and strength through insulated chuck and Nylon housing, and light weight.

The drill serves as a power unit for a complete 14-tool power workshop with a motor rated at a full 2.7 amperes. Drill turns into many other useful power tools with on-and-off-in-seconds Quik-Change attachments. It drives easily attachments such as a 5½" circular saw, hedge trimmer and finish sander. Other units include a portable and bench sabre saw, bench grinder, etc.

Millers Falls Co., Greenfield, Mass.
Use postpaid eard. Circle No. 128



Use postpaid card. Circle No. 422



COMBINED DRILLS and COUNTERSINKS

e Both old and new series carried in stock for immediate delivery. Finest high speed steel. Ground spiral flutes. New standard simplifies and improves size progression. New comparison chart mailed on request. Shows new standard sizes—both plain and bell type. Specials to your blue prints. We also stock Keyseat Cutters, Arbor Type Cutters, Center Reamers, Lathe Mandrols. T-Siot Cutters and Long Series Combined Drills.

KEO CUTTERS, INC.

25040 Easy St., Warren, Mich. Warehouse: 1300 S. Soto St., Los Angeles 23, Calif.

Use postpaid card. Circle No. 423


INDEXING MACHINERY — CAMS — GENEVA GEARS — TURNTABLES

EISLER MAKES OVER 300
DIFFERENT TYPES OF
INDEXING TURNTABLES
SPECIAL MADE TO YOUR
SPECS. WRITE FOR CATALOG.





Dr. Charles Eisler Me. Founder Charles Eisler, Jr. Pres.
EISLER ENGINEERING CO., INC.
762 SOUTH 13th STREET



INSERT BORING TOOL HOLDERS COME IN WIDE RANGE OF SIZES

Users of DeVlieg Microbore units can now use the hardest grades of carbide if they use either the clamp-on or screw-on style holders for throwaway inserts now available. Ceramic inserts can also be held.

Two styles are produced, type S in which a button head screw seats and holds the insert and shim assembly; and type C in which a clamp-on arrangement is used to release the shim.

chip breaker and insert for fast indexing.

The former is for general purpose precision boring operations in the smaller hole sizes down to 15/16" diameter. The latter for large bore sizes for light, medium and heavy machining. Both styles are furnished for either angular or straight mounting.

DeVlieg Machine Co., Microbore Div., Fair St., Royal Oak, Mich.

AC-DC INERT-GAS WELDERS

Two all-purpose welders have been announced by Hobart. Model AD1-2641 is rated at 200 amps., and AD1-3641 at 300. Both can be used for manual, automatic, tig, inert-gas spot, or mig welding.

Inert-gas facilities are built in, but a hinged top permits easy access to spark gap and timers of the high frequency stabilizer. Both models are geared with an automatic contactor opening feature, hand switch for remote control, adjustable post flow timer, automatic high-frequency control, power-factor correction, and a ballast resistor.

Hobart Brothers Co., Troy, Ohio.



Use postpaid eard. Circle No. 138

HUPPERT

Floor Model Furnaces **Built in 28 Standard Sizes**

- . Continuous operation to 1850°F.—intermittent to 1950°F.-for 2300°F. on special order
- . Complete with indicating electronic controller.
- · Tight-sealing, wedge-type door.
- . Standard for 220 V. AC, single or 3 phase operation-110 V. or 440 V. on special order.
- · Multi-insulation for maximum efficiency.

Request literature on complete line of Huppert Furnaces



Inside Dimensions 12" W. x 8" H. x 18" D. \$1050.00 complete

Model No. 16 Illustrated

K. H. HUPPERT CO. Manufacturers of Electric Furnaces and Ovens

6845 Cottage Grove Ave., Chicago 37, Illinois

Use postpaid card, Circle No. 425



ANGING MACHINES and CIRCLE SHEARS

- No. 1 10 Ga. Cirele Shear and Flanger.
- 1/4" Cap. Flanger for flat heads.
- 36" Can. Flanger for No. 4 flat and dished heads.
- 1/2" Cap. Flanger for No. 5 flat and dished heads.
- No. 6 %" Cap. Flanger fer flat and dished heads.
- No. 56 Medel 3/16" Cap. El-
- No. 60 %" capacity circle shear with a 23"
- No. 40 1/4" capacity circle shear with a 151/2"



Above machine a No. 7, $\frac{9}{4}$ " capacity. Shown with a $\frac{9}{4}$ " x 9' 6" dia, stainless steel head with a $\frac{6}{4}$ " knuckle radius. Can ge up to as high as an 8" knuckled radius.


Road KANSAS CITY 26, MO. Truman

TUNGSTEN INERT GAS SHIELDED TORCH WELDS AND CUTS

Linde Company's standard line of tungsten inertgas-shielded torches can now be used for both welding and cutting. Cutting is accomplished by increasing current density above good welding conditions while using argon-hydrogen mixtures. Normal gas flow rates (40 to 60 cfh) transfer energy across arc and displace the molten metal.

DC power equipment, with a 70-volt open circuit can be used for metals \(\frac{1}{2} \) to \(\frac{1}{2} \)" thick. Cutting speeds are 40 to 60 ipm on \(\frac{1}{2} \)" stainless steel. Linde's mechanized Con-

stricted Arc cutting method continues to be recommended for applications where high-speed and quality are critical in materials up to 4" thick.



Linde Corp., Div. of Union Carbide Corp., 270 Park Ave., New York 17.

Use postpaid card. Circle No. 131



WRITE FOR CATALOG ON LIVE CENTERS

- Use postpaid card, Circle No. 427

COMPARATOR SPEEDS SETTING TOOLS IN HOLDERS

An optical tool setting comparator developed by Pratt & Whitney is designed to meet the need for a gage





to set tool position in adapters for use in numerically controlled machines or other machines using pre-set tooling.

Primarily used to set tool depth and diameter, the comparator also is capable of checking tool run-out and cutting edge condition.

The instrument is a combination comparator and direct setting device. It uses a set of gage blocks and end measures for even inch settings. Increments of an inch are set by micrometer head. Tool point positioning is observed through a microscope with exact positioning made by fine micrometer adjustments.

Maximum depth and diameter capacities are 12" and 6" respectively.

Pratt & Whitney Co., Inc., West Hartford 1. Conn.

Use postpaid card. Circle No. 133

New American Standard's PRECISION SURFACE GAGE


PATENT PENDING

The exceptionally smooth fine adjustment is in a vertical plane and all backlash is virtually eliminated. Working range is from Zero to 20"

in height. With the use of an extension red any height may be measured.

A sturdy well built tool. Weight 6 ibs. Even extended to 20" in height, you will be able to work with confidence and repe tition with a .0001 Indicator.

PRICE \$20.00 Without Indicator



AMERICAN STANDARD COMPANY

PLANTSVILLE, CONNECTICUT

Use postpaid card, Circle No. 428



In Stock-Immediate Delivery

Gears, speed reducers, sprock-ets, thrust bearings, flexible couplings, pulleys, etc. A complete line is carried in our Chicago stock. Can also quote on special gears of any kind. Send in your blueprints and inquiries

Send for Complete Catalog No. 18a CHICAGO GEAR WORKS 440-50 N. Oakley Blvd., Chicago 12, III.

Use postpaid card. Circle No. 429



SPELLMACO "SPOTTERS"

A matched set of transfer punches for toolmakers, machinists & tool cribs

Used for transferring location of threaded, drilled and reamed holes, slugs, blanks, etc.

Precision made of finest tool stacl-Carefully heat treated and tempered for long life-0025 undersize to facilitate use-Black exide finish Set No. 3-17, 28 punches with indexed stand—size 3/32" to 1/2", by 1/64"—plus handy 17/32" size. Longth 4-7/8" ONLY \$19.40

Single sizes available

L. SPELLMAN CO. - URBANA, OHIO

FOR

MAXIMUM PRECISION IN TOOLROOM OR PRODUCTION GRINDING



MODEL F HYDRAULIC FEED SURFACE GRINDER a production type with cross stiding head, built in sizes ranging from 12" x 18" x 48" to 30" x 25" x 120". Heavy, powerful grinder with maximum table speed of 150' per minute. Motor mounted directly on grinding wheel spindle to assure full power is transmitted directly to wheel. Automatic feeds in increments from .0001" to .001" per reversal available.

NO. 380 HYDRAULIC FEED SURFACE GRINDER. A precision toolroom type which offers absolute accuracy with microinch finish at production speeds. One-piece column and base, infinite longitudinal table speeds from 3° to 120' per minute, variable speed cross feed. Available with new incrematic downfeed with automatic spark-out after preset stock removal.





NO. 10 UNIVERSAL CUTTER AND TOOL GRIMDER built to meet the need for a high grade machine of medium capacity at a moderate price. Combines rigidity with maximum convenience of operation. Head swivels 360°, locks in any setting; table swivels 90°. Hand operated longitudinal movement. Two spindle speeds.

FIVE NEW GRADES OF CEMENTED CARBIDES

Newcomer Products, Inc., Latrobe, Pa., has announced the development of five new grades of cemented carbides, called NewBide, with a Rockwell (A) hardness ranging from 91.2 to 93.0 and with transverse rupture strengths from 225,000 to 325,000 psi.

N-20 is a fine grain, high tensile general purpose grade for machining cast iron and non-ferrous materials. It has added greater crater resistance for the alloy types of cast iron, according to the company, than comparable standard grades.

N-50 is recommended for heavy cuts on steel and as a premium general purpose grade—an extended range carbide with excellent resistance to mechanical and thermal shock as well as good wear resistance.

N-60 is specially designed for general purpose machining of steel under normal conditions. It is described as having less shock resistance, but greater wear resistance than the N-50 grade.

N-70 is a general purpose finishing grade for moderate cuts at relatively high speeds, and N-80 is a premium high speed finishing and precision boring grade offering extreme wear, crater and thermal shock resistance.

Use postpaid card. Circle No. 134

PILOT CONTROL REGULATES INACCESSIBLE AIR LINES

Remote regulation of inaccessible air lines is possible with Hannifin Crown's pilot-controlled regulator. A column of air replaces adjusting screw and spring.

The regulator can control air flow in large pipes, provide different pressures to a single tool or cylinder, and maintain stability in downstream pressure-sensing systems.

GRAND RAPIDS

Hannifin Co., Dept. 130, 501 S. Wolf Rd., Des Plaines, Ill.

Use postpaid card. Circle No. 135



GRADUATING MACHINE MARKS CALIBRATIONS ON METAL TUBING

The No. 598 manually operated graduating machine marks accurate calibrations on aluminum, brass, and other metal tubing. A single rotation of the 8" diameter marking wheel provides fractional graduations on a 24" tube. The operating handle is balanced to hold in any position. All operating parts are safely covered, but are easily reached for changing the marking wheel or other servicing.

Dimensions of the easily-operated machine are 48" left to right x 16" high

x 10" thick.

The Acromark Co., 15 Morrell St., Elizabeth, N. J.

Use postpaid card. Circle No. 136

IMPROVED SINE-LINE LEAD CHECKER

The Model 1218-A lead checker incorporates optical instrumentation for setting both the universal sine bar and an angular dividing head. Angles can

YOU

CAN FIND THE RIGHT MACHINE FOR YOUR NEEDS ON THESE PAGES

NO. 60 UNIVERSAL CUTTER AND TOOL CRINDER offers precision sharpening, fast set-ups and low maintenance. Designed for maximum convenience of operation, with work weight carried directly over base, permitting operator to stand close to work. Master hand wheel provides three speeds of longitudinal table travel.





NO. 20 HAND FEED SURFACE GRINDER has hand wheels for vertical and longitudinal table movement to assure toolroom precision and exceptionally fine finish. One-piece column and base, greased-for-life ball bearing spindle. Available with portable, motor driven coolant system.

NO. 1230 HYDRAULIC FEED O. D. & I. D. GRINDER meets the needs of users requiring a machine that does both internal and cylindrical grinding. It is a rugged, precision tool capable of taking rough cuts as well as producing the finest finish. Has a host of controls and adjustments for maximum convenience and versatility of operation.




A note on your letterhead will bring full details. Please specify the type of grinder you are most interested in.

GALLMEYER & LIVINGSTON CO. 405 Straight Ave., S. W., Grand Rapids, Mich.

POINTEDC GALLMEY

GRINDERS





be set within 0.001" degree without use of gage blocks.

With new components incorporated in this lead checker, it is possible to do conventional continuous checking, or increment checking through use of the scale on the tailstock. Leads of external or internal helical, spur and herringbone gears, and worms can be checked from zero to infinity. Tooth spacing can also be checked with the dividing head.

Gears with pitch diameters up to 18" can be checked with repeatable accuracy of 0.0001". Maximum distance between centers is 24".

Michigan Tool Co., 7171 E. McNichols Rd., Detroit 12, Mich.

Use postpaid card. Circle No. 137

REDESIGNED LAPPING MACHINE

The 24" Lapmaster features a new abrasive distribution system which maintains constant mixture of compound to vehicle. Adjustable flow control assures uniform deposit at lapping stations. Air lifts speed loading and unloading of small- and medium-sized parts. A sensing head detects whether lap plate is convex, flat or concave, and registers on a control panel.

Open-faced models, without pneumatic lifts, are available with or without the sensing head equipment.

Crane Packing Co., Dept. MB-3, 6400 Oakton St., Morton Grove, Ill.

EDGCOMB VERNIER SCALE ATTACHMENT

Accuracy within .0002" in positioning and relocating points on milling machines, lathes, and similar equipment is provided with the Edgcomb Evertrue vernier scale attachment. It enables close tolerances to be held on older machines by providing the means to overcome errors due to backlash and worn lead screws.

This attachment is available for table lengths from 1" to 15" and is adaptable for 1-, 2-, or 3-axis operations. Prices start at \$220.

Edgcomb Engineering and Engraving Co., 1105 N. Hollywood Way, Burbank, California.

Use postpaid card. Circle No. 200


MILLING SPINDLE'S TORQUE INCREASES AS SPEED DECREASES

Compactness and variable spindle speeds at constant horsepower are features of Colonial Broach & Machine's new line of Hydraulic Constant Horsepower Milling Spindles.

The manufacturer points out that the spindles obtain time saving results because maximum chip loads per tooth can be used regardless of spindle speeds or cutter diameter.

The "standard" spindles offered range from 10 to 50 HP. Larger and smaller units are also available. A 15





Our Mandrels are made with exclusive high vacuum bond.

V.R.C. Mandrels contain a high concentration of diamond powder completely through to center. Ours are **not** of the standard single layer plated type. This process results in a greater economy through longer wheel wear. Enables extremely free cutting.

Applications:

Internal grinding, jig grinding of carbide dies, hardened steel, ceramics. Suitable for Pratt & Whitney, Moore, Dumore and similar types of equipment.

Sizes—1/16" to 1/2". Shank size to your specifications.

Write for catalog containing data and prices.

Distributors and export inquiries invited.

Vacuum Research Corp.

Mfg. of Industrial Diamond Tools 70 Austin St., Forest Hills, N.Y. Telephone: BO 1-5687

Use postpoid card. Circle No. 433 April. 1961

Announcing the

EM 605

PRODUCTION Drill Press

at new

LOW PRICE!

- EXCLUSIVE E-M DRILL-MATERIAL CHART
- FINGERTIP SPEED SELECTOR DIAL
- INSTANT-SET QUILL
 DEPTH STOP
- . BUILT-IN MOTOR
- HEAVY
 CONSTRUCTION



Designed especially for those production jobs requiring a wide range of work plus accuracy and speed. Includes many features of the popular T-M Tool Room Model. 600 to 4,000 RPM. Table and Bench Models.

Write for FREE Literature

THE ELECTRO-MECHANO CO. 263 E. Erie Street, Milwaukee 2, Wisconsin

MAGNETIC Sine Plates



COMPOUND AND SINGLE ANGLE

New Duol Field permanent mag netic chucks with extra holding power, Positive lock on each axis.

The new Dual Field permanent magnetic chucks with a center T slot, allow either side to be magnetized independently. All models are accurate to .0002" in dimensions and parallelism. A .2000" recess is provided

for small angles. OTHER MODELS include 5" and 10" sine

bars and plates, single and compound angle, plain and magnetic.



Write for eatalog and economical prices on full line. BALD EAGLE PRODUCTS DIV.

356 Cedar St. . St. Paul 1, Minn. For Quality - Specify Bald Eagle

Use postpaid card. Circle No. 435



Base Tool Holder

Magnetie

11 ermanent fagnets— Various

indicator Heider — V_e" dia.
non-magnetic stainless stool
red complete with S/16" and
3/" 0.D. bushings. Fine precision adjustment identical to
surface gage. Hardenad hall
secket setting permits universal positioning. Pawerful
50-19, pull magnetic base insures firm grip on any
ferrous surfaces curved or flat.

Write for Cotation We 955.C.

Write for Catalog No. 958-C

CULLEN MFG. CO., INC. 1603 Washington Ave.

Racine, Wis.

Use postpaid eard. Circle No. 436

areenerd ARBOR FRE

Use 3B (simple lever type) or 3 BR (ratchet type) Presses for work up to 33" diameter. Maximum 3 Tons Pressure and 12" Daylight. Write for Catalog 8-42 or see your dealer for

REAMER BUSHINGS

Mueller Industries has developed a line of reamer bushings to provide greater accuracy for stub screw machine reamers. The design corrects for out-of-parallelism of turret and spindle, indexing inaccuracies, and hole runout in the workpiece.

Mueller Industries, 510 E. Rand Rd., Mt. Prospect, Ill.

Use postpaid card. Circle No. 139

CARBON-DIOXIDE SHIELD FOR WELDING STEEL

Air Reduction Sales Co. has introduced a welding process which uses carbon dioxide and low-alloy steel welding wire to join mild steel, called Aircomatic CO2 Sprayarc. Sound welds can be made with direct current or straight polarity, using CO2 shielding gas. About 32 volts are recommended for most work.

Air Reduction Sales Co. a division of Air Reduction Co., Inc., 150 E. 42nd St., New York 17, N.Y.

Use postpaid eard. Circle No. 140

MAGNETIC TOOLS

Use postpaid card. Circle No. 437 MACHINE and TOOL BLUE BOOK

more specifications.

The MARKET PLACE

Advertisements acceptable in THE MARKET PLACE include those for employment, sales services, production facilities, representation and related needs. Rates: \$28 per column inch per insertion. Maximum size advertisement accepted in this section is three inches.

Copy should reach us by the first of the month for wext month's issue.

MACHINE and TOOL BLUE BOOK

A Hitchcock Publication

Wheaton, IIL

HEAVY DUTY DOVETAIL SLIDES

These slides are built to take steady use. All are fitted with tapered gibs. Available in 2, 3, 4, 5, 6 and 8 inch widths.

Biddle Engineering Co.
P.O. Bex 98 Warrendale, Pa.

JET-WEAR

Carbide Tipped Centerless Grinder Work Rest Blades All Standard Sizes and Specials—2 Week Delivery. Write for Catalog of Standard Blades including full engineering data.

LUND MFG. CO.

366 Elm Street

Biddeford, Maine


TOOL HOLDER FOR SINGLE-, MULTIPLE-SPINDLE SCREW MACHINES

A floating tool holder with a single adjustment point has been developed for use on single- and multiple-spindle screw machines and turret lathes. It is designed to compensate for misalignment between spindle and workpiece.

Known as the Aline-X floating tool holder, it is available in shank sizes ranging from 5%" to 1½". The holder has nine parts and features a single adjustment point that makes the tool easier to use and is said to provide longer life for the holder.

Allied Metal Products, Inc., 1082 Farmington Ave., Kensington, Conn.





What some folks won't do to use a

CONWAY CLUTCH



CONWAY CLUTCHES

and those which wish they were Conways.

Evidence the fact that the Conway STATIONAIRE (illustrated) has been copied. Oh well, imitation is the sincerest form of flattery.

Tsk, tsk . . . don't tell our competitors but STATIONAIRE has gone HYDRAULIC! Really, we don't know what the clutch industry would do without us.

WRITE FOR BULLETIN

The World's Most Respected Name in Clutches for over a Half-Century

The CONWAY CLUTCH COMPANY

1105 MARSHALL ST.

CINCINNATI 25, OHIO

A

Abrasive Belt Machines, 221
Abrasive Cloth, Paper, Discs,
Wheels, Stones, Belts, etc.,
78, 90
Abrasive Cut-Off Machines, 92, 95
Abrasive Cut-Off Wheels, 226
Accumulators, 223
Actuators, 187
Adapters, 10
Air Control Equipment, 49
Air-Operated Equipment, 36
Angle Dressers, 218, 225
Angle Irons, 206
Assembly Machines, 202

B

Balancing Machines, 200
Balancing Tools, 174
Bearings, 208
Bearings, outer support, 198, 208
Bending Machines & Equipment, 219
Blades, cut-off, 15
Blanks, 185
Blanks, 40vetail, 32
Bolts, 215
Boring Bars and Tools, 74, 145
Boring, Drilling, Tapping
Machines, Inside Back Cover
Boring Heads, 6, 151, 187, 235, 245
Boring Tools, 198, 212, 250
Broaches, keyway, 160
Bushings, 52, 236

C

Bushings, drill jig, 52, 60, 236

Bushings, Reamer, 258

Cam Grinding, 216
Cam Milling, 216
Cams, 216, 249
Carbide Tools, 41, 74, 209, 218, 228
Casting Materials, 208
Cemented Carbides, 254

Center Laps. 244 Centers, bullnose, 203 Centers, live, 18, 213, 230 Centers, motorized, 159 Chuck Jaws, truing-rings, 213 Chucks, collet, 12, 64a Chucks, compensating, 89, 98 Chucks, drill, 55 Chucks, magnetic, 40, 58, 219 Clamps, 4, 62, 177 Clamps, "C", 4, 62 Clamps, toggle, 177 Cleaner, 216, 243 Clutches, 260 Collet Closer, 187 Collet Stop, 162 Collets, 12, 64a Comparators, optical, 222 Contour Units. 23, 31 Coolant Systems, 166, 212 Coolants, 37, 134 Counterbores, 1, 69 Countersinks, 21, 205, 249 Cut-Off Blades, 15 Cut-Off Machines, 21, 70, 84, 92, 219, 230, 242 Cut-Off Tools, 66 Cutters, 69 Cutters, disc, 205 Cutting Fluid, Oils, 37 Cylinders, hydraulic, pneumatic, 36

D

Decoilers, 189
Deburring Machines, Tools, 21, 205
Details, 64a
Diamond Dressers, 190, 198, 209, 225, 244
Diamond Wheels, 225
Die Buttons, 47
Die Filers, 31, 235
Die Heads, 93
Die Makers' Supplies, 204
Dies, 28
Dovetail Slides, 259

Drafting Machines, 204 Dressing Cutters, electrode, 205 Dressers, diamond, 190, 198, 209 225, 244, 245 Dressers, wheel, 218, 225, 234, 245, 246 Drill Guides, 238 Drill Heads, 159, 185, 192, 209, 240, 244 Drill Heads, multiple spindle, 176, 244 Drilling Attachments, 238 Drilling Machines, 238, 267 Drilling Machines, gun, 237 Drilling Machines, heavy duty, **267** Drilling Machines, multiple spindle, 184 **Drilling Machines Numerically** Controlled, 13, 45, 53, 248 Drilling Machines, portable electric, 248 Drilling Machines, press, 30, 257
Drilling Machines, radial, 231
Drilling Machines, sensitive, 75, 79
Drilling Machines, turret, 13, 248 Drilling Units, 209, 211 Drills, 186, 249 Drills, carbide, 209 Drills, center, 21 Drills, core. 69 Drills, diamond, 225 Drills, gun, 237 Dust Collectors, 197, 241

E

End Finishers, 84, 189 End Mills, 65, 77, 205 Engravers, 33

=

Feed Units, 201, 209
Feed Fingers, 161
Feeders, parts, 20, 207, 210, 244
Feeds, 20
Feeds, air, 206

NOTE: Bold face indicates products which are described in advertisement in this issue.

Files, rotary, 41 Filing Machines, 31, 235 Finishing Machines, 67, 184, 189, 221

Fixtures, 191, 208
Flanging Machines, 251
Forming Machines, 218
Furnaces, electrical, 178, 251, 228
Furnaces, gas, 171
Furnaces, heat-treating, 171, 178,

G

Gage Handles, Blanks, 227

Gages, 96a, 239 Gages, air, 22, 216 Gages, dial, 22 Gages, height, 253 Gages, internal, 239 Gages, plug, 239 Gages, squareness, 25 Gages, surface finish, 253 Gages, thread, 227 Gear Hobbers, 43 Gear Measuring Equipment, 255 Gear Shapers, **38-39** Gears, 226, 238, 253 Gears, Geneva, 249 Grinders, abrasive belt, 205, 221 Grinders, bench. 233, 245 Grinders, centerless, 259
Grinders, cylindrical, 8-9, 190
Grinders, disc, 226 Grinders, external, 190, 255 Grinders, internal, 255 Grinders, pedestal, 226 Grinders, portable air, 195 Grinders, portable electric, 243, 245 Grinders, profile, 242, 249 Grinders, punch & die, 245 Grinders, surface, 64h, 68, 73, 85, 254, 255 Grinders, tap, 231 Grinders, tool & cutter, 254, 255

Grinders, tool post, 163 Grinding Attachments, 73, 83, 85, .

Hammers, hard faced, 208
Hammers, lead, 218, 238
Hammers, plastic, 208
Hand Wheels, 200
Hardness Testing Equipment, 167, 201
Hinges, 216
Hobbing Machines, 43
Hoist Hooks, 63
Holders, tool, 213, 250
Holding Fixtures, power, 247
Holding Tools, 247
Honing Machines, 64, 71

1

Index Fixtures & Tools, 208
Indexing Machines, 249
Inserts, throwaway, 74
Inspection & Measuring Devices, 22, 125, 194, 218, 255

J

Jig Borers, **247** Jig and Fixture Base, 183 Jigs & Fixtures, **194, 206, 213,** 247

κ

Keyseaters, **91** Knobs, machine, **222** Knurling Tools, **219**

L

Lapping Machines, 14, 215, 256

Lapping Plates, 213
Laps, 266
Lathes, automatic, 11
Lathes, engine, toolroom, 5, 46 57, 100, 198, Inside Front Cover
Lathes, general purpose, 46
Lathes, extension bed & gap, 7
Lathes, speed, 184
Lathes, "I"', 7
Lathes, turret, 16-17, 188
Layout Dye, 19, 228, 225
Layout Tools, 217
Lifts, 227

Lifts, magnet, 26

M

Machine Knobs, 200 Machine Tools, 96a Magnetic Tools, 258 Mandrels, 257 Marking Devices, Stamps, 187, 202, 255, 228 Measuring, Checking Equipment, 125, 223, 224, 232 Metallizing, 157 Micrometers, internal, 183 Milling Cutters, 21, 65, 147, 179. 199, 232, 266 Milling Machine Attachments, 238 Milling Machines, turret, 7 Milling Machines, vertical, 7, 173, 182, 246 Mills, 199, 266 Mist Generators, 166, 212 Mounting Pads, 187

N

Nibbling Machines, 42 Notching Units, 7, 42, 61, 169

0

Optical Inspection Devices, 222, 232

P

Pantographs, 33 Perforators, 209, 221 Pins. 209, 221 Pins, dowel, 236 Plastic Tooling, 231 Pliers, Plungers, index, 196 Pneumatic Tools, 195 Press Brakes, 182 Presses, air, 96 Presses, arbor, 258 Presses, bolster, 154 Presses, bench, 96 Presses, bending, 72 Presses, C-frame, 29, 186 Presses, eccentric, 154 Presses, extrusion, 154 Presses, gap type, 214, 231 Presses, knuckle-joint, 154 Presses, O.B.I., 51, 54, 82, 88, 154, 181, 192, 217, 231 Presses, power, 192, 231 Presses, punch. 7, 42, 61

NOTE: Bold face indicates products which are described in advertisement in this issue.

218, 225, 232

Grinding Wheels, 98

Grinding Spindles, 85, 86

BOOKS YOU CAN USE...

Put the latest know-how and techniques at at your fingertips with these new books.

*MACHINERY'S HANDBOOK plus companion book "THE USE OF HANDBOOK TABLES AND FORMULAS".

New, revised enlarged 16th edition combines all the features of earlier editions with most recent data. Acknowledged authority of the metalworking industries—indispensable reference book for designers and builders of mechanical products. 2104 pages bound in rugged, durable Sturdite. Price \$12.50

*BESIGN OF WORM AND SPIRAL GEARS

By Earle Buckingham. Completely new book on getting better results from worm gear units. Numerous diagrams, tables, and worked-out examples show how superior worm gears can be designed. 480 pages; price \$15.00.

DIMENSIONS AND TOLERANCES FOR MASS PRODUCTION

By Earle Buckingham. Presents new, practical approach to the problem of how to dimension with tolerances in relation to production design, tool design, gage design, production and inspection. It suggests definite methods and practices to eliminate uncertainties in present-day practice. 164 pages, 179 illustrations; price \$8.00.

Bill my company.

HANDBOOK OF BARREL FINISHING

By Ralph F. Enyedy. Covers every phase of barrel finishing, including over 150 complete specification sheets and latest developments. 263 pages; price \$8.25.

CHIPLESS MACHINING

By Charles Wick. Is a new how-to volume on chipless machining, shaping metal parts without the production of chips. A basic, technical guide describing and illustrating in detail newer methods of cold forming and giving data on economics resulting from savings in time and materials. 502 pages, 326 illustrations; price \$10.00.

ORDER NOW!

TAKE ADVANTAGE OF 10 DAY FREE EXAMINATION OFFER.

Use this convenient order form. Send remittance and save shipping charges—or mark "Bill me."

ZONE___STATE

NEW BOOKS	BOOK DIVISION HITCHCOCK PUBLISHING COMPANY DEPT. BB-40, WHEATON, ILLINOIS
	Please send me prepaid the book(s) indicated below;
	copies of MACHINERY'S HANDBOOK and USE OF TABLES @ \$12.50copies of DESIGN OF WORM AND SPIRAL GEARS @ \$15.00copies of DIMENSIONS AND TOLERANCES FOR MASS PRODUCTION @ \$8.00
	copies of HANDBOOK OF BARREL FINISHING @ \$8.25
	Check or mensy order NAME COMPANY
	☐ Bill me. STREET

Presses, straight side double crank, 214
Presses, toggle, 154
Presses, turret punch, 48
Printers, 247
Profiling Machines, 242
Pumps, coolant & lubricant, 97, 190
Punches, 50, 133, 169
Punches & Dies, 47, 133
Punching Equipment, 169
Pusher Pads, carbide, 161
Pushers, 64a

R

Reamers, 59, 186, 205 Reamers, center, 21 Regulators, 254 Riveting Machines, 232, 235

S

Safety Devices, 235, 237 Saw Blades, band, 23, 34, 146, 153, Saw Blades, circular, 34, 187 Saw Blades, hack, 24, 27, 34, 35, 146, 187 Sawing Machines, band, 23, 76, 87, 199, 207, Back Cover Sawing Machines, cut-off, 87, 221, 242 Sawing Machines, hack, 221 Saws, slitting & slotting, 21 Scalers, 256 Scrapers, hand, 174 Screw Machines, hand, 2 Screw Sets, transfer, 176 Screws, cap, set, socket and machine, 94 Services: Boring, Grinding, Lapping, Milling, Repairing, etc., 56, 160, Sharpeners, Punch & Die, 245 Shearing Machines, 7, 61, 218, 230 Shears, power squaring, 194 Shears, punch, coper, 7 Sine Plates, 258 Sine Bars, 255 Sine Chucks, 40 Sine Plates, 40 Slide Feeds, 44 Sockets, 63

Spindles, 185
Spindles, grinding, 185
Spindles, milling, 272, 256
Spotters, 203, 253
Spring Coilers, 194
Stampings, 166
Superfinishers, 11
Surface Finish Indicators, 223
Swaging Machines, 3

T

Tables, elevating, adjustable, 229
Tables, rotary, index, 192
Tappers, 55, 220
Tappers, automatic reverse, 220
Tapping Attachments, 55
Tapping Machines, 13, 236
Tapping Units, 175, 236
Taps, 94, 269
Taps, 10dicators, 218
Testing Instruments, ultrasonic, 197
Thread Rolling Machines, 138, 240

Threading Machines, 138
Threading Tools, 93
Tool Holders, 74, 228, 241, 250, 259
Tool Steel, 80-81
Turn Tables, 249
Turning Heads, 245
Type Holders, 187, 202, 245

V

Valves, 49, 188 Valves, air, 195 Vibration Control, 187 Vise-Set, 213 Vises, bench and machine, 192-193, 196, 214

W

Welding Equipment & Supplies, 188, 224, 245, 250, 252, 258 Wheel Dressers, 190, 218, 234, 246 Wrenches, 62, 63 Wrenches, torque, 234



NOTE: Bold face indicates products which are described in advertisement in this issue.

Speed Reducers, 55, 211

Index to Advertisers

B

A

A. K. Tool Company, Inc160
Aaron Machinery Company
Abart Gear & Machine Company238
Ace Drill Corporation
Acme Industrial Company 60
Aget Manufacturing Company24
Aling Corporation
Allen Collet Manufacturing Company64-I
Allen Industries, Alva
Allied Products Corporation
(Richard Bros. Punch Division)
American Chain & Cable Company 92
(Allison Campbell Division)
American Society of Tool Engineers
176-A-B-C-I
American Standard Company25
American Tool Works CoInside Back Cover
Anderson Bros. Manufacturing Company17
Armstrong-Blum Manufacturing Company 2
Armstrong Bros. Tool Company
Artus Corporation23
Atlas Press Company 3
Auto Moulding and Mig. Co21
Avey Division20
(Motch & Merryweather Mchy. Co.)

-

Balcrank, Inc.	200
Bald Eagle Corporation	258
Baldor Electric Company	233
Barnes Company, Inc., W. O	153
Beaver Gear Works	
Beaver Pipe Tools, Inc.	
Bellows-Valvair	
Benco Collet Manufacturing Company	
Biddle Engineering Company	
Bijur Lubricating Corporation	212
Blanchard Machine Company	90
Bliss Company, E. W.	
Blue Valley Manufacturing Company	251
Boggis Company, Henry P.	221
Bokum Tool Company	
Boyar-Schultz Corporation	85
Brightboy Industrial Division	78
(Walder Paherte Pubher Company)	/0
(Weldon Roberts Rubber Company) Briney Manufacturing Company	100
Briney Manufacturing Company	130
Brown and Sharpe Manufacturing Co	
Buffalo Forge Company	61
Burgmaster Corporation	
Bystrom Company	162

C

	216
(Division Himoff Machine Company)	
Cerro Sales Corporation	23
Chandler Tool Company	230
Chicago Gear Works	253
Chicago Latrobe	. 59

Chicago Quadrill Company185
Cincinnati Lathe & Tool Company 45
Cincinnati Milling Machine Company 37
(Cincinnati Milling Products Division)
Cincinnati Milling Machine Company8-9
(Grinding Machine Division)
Circular Tool Company 21
Clark Instrument Company167
Clausing Division
(Atlas Press Company)
Cleveland Crane & Engineering Company 72
Cleveland Punch & Shear Works Co 54
Clipper Diamond Tool Company225
Columbia Tool & Die Works236
Columbus Die-Tool & Machine Company 56
Commander Manufacturing Company176
Comtor Company239
Conway Clutch Company260
Cook's Lead Hammer Service238
Cooley Electric Manufacturing Corporation 178
Covel Manufacturing Company
Criterion Machine Works151
Crucible Steel Company of America80-81
Cullen Manufacturing Company258
Cunningham Company, M. E187

D

1

Fostern Mochine Core	w Corporation 95
Eclipse Counterbore C	
	Company22
	npany249
Electro-Mechano Comp	any25
Empire Tool Company	
Ex-Cell-O Corporation	25

.

Federal	Tool	& Manu	facturing	Company	166
Fellows	Gear	Shaper	Company	Company	38-39


Fenn Manufacturing Company	M
Flynn Manufacturing Company235	
Fullio Specialities Company 188	M. B. Products, Inc195
Fulmer Company, C. Allen 64	McGonegal Manufacturing Company163
	Machine Products Corporation 194
	Magna-Lock, Incorporated
G	Manhattan Supply Company219
	Meehanite Metal Corporation208
Gaertner Scientific Corporation232	Metco, Inc
Gallmeyer & Livingston Company254-255	Midwest Tool & Engineering Company229
Gisholt Machine Company	Minster Machine Company 51
Green Instrument Company 33	Minster Machine Company
Green Instrument Company	Modern Machine Tool Company 84
Grieder Industries, Inc 70	Moore Special Tool Company
Grobet File Company of America	Morse Twist Drill & Machine Company 77
Grobet File Company of America 41	Motch & Merryweather Machinery Co209 (Avey Division)
	(array paramon)
H	
	N
Hamilton Tool Company 79 Hammond Machinery Builders, Inc. 67 Hanchelt Magna-Lock Corporation 26 Harig Manufacturing Company 73-196 Havir Manufacturing Company 217 Heimann Manufacturing Company 176	
Hammond Machinery Builders, Inc 67	Navan Products, Inc
Haria Manufacturing Company 72.106	(Sub. North American Aviation, Inc.)
Havir Manufacturing Company 217	Nelso Tool Company Inc. 65
Heimann Manufacturing Company176	Neise, Karl A
Heller Tool Company 27 Himoff Machine Company 216	NewTools, Inc. 268 Nicholson File Company 146
Himoff Machine Company216	Nicholson File Company146
(Camm Services Division)	Nielsen, Inc252
Houston Grinding & Mig. Co., Inc	Nielsen, Inc. 252 Northwestern Tools, Inc. 222 Numberall Stamp & Tool Company 202
trappert company, as it.	Numberali Stamp & 1001 Company202
	0
Index Machine Company173	Oliver Instrument Company
J	
1.00.00	D
6 S Tool Company	
Torvie Corporation 94	Dannier Corneration 242
Johnson Gas Appliance Company	Pannier Corporation
Johnson Machine & Press Company231	Parker-Hannifin Corporation 96 Peaslee Metal Products Company 236
Johnson and Son, Inc., S. C	Penniman, Elisha 208 Pines Engineering Company 189 Pope Machinery Corporation 86 Portage Double-Quick, Inc. 66
Jones and Lamson Machine Company 53	Pines Engineering Company189
Junkin Safety Appliance Company235	Pope Machinery Corporation 86
	Powermatic Machine CompanyBack Cover
K	Prott & Whitney 96-A-B-C-D
N.	Practise Products Corporation96-A-B-C-D
Kenco Manufacturing Company	Precision Tool & Manufacturing Co187
Keo Cutters, Inc. 249	Procunier Safety Chuck Company175
Kec Cutters, Inc	Punch Products Corporation169
Krieg Inc., Victor J243	
	Q
L	and the second s
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Queen City Machine Tool Company226
L & J Press Corporation 88	
Landis Machine Company	
Lees-Bradner Company 43 Leland-Gifford Company 267	R
Levin and Son, Inc., Louis	
Linley Brothers Company247	R. B. Tool Company212
Lodge and Shipley CoInside Front Cover	R. B. Tool Company212 Reich_Manufacturing Co., J. R244
Logan Engineering Company100	Rice Pump & Machine Company
Lucifer Furnaces, Inc. 229	(Allied Products Corporation)
Levin and Son, Inc. Louis 75 Linley Brothers Company 247 Lodge and Shipley Co. Inside Front Cover Logan Engineering Company 100 Logansport Machine Company 36 Lucifer Furnaces, Inc. 228 Lund Manufacturing Company 259	(Allied Products Corporation) Richards Company, J. A

NBM

LELAND-GIFFORD

KNEE-TYPE GUN DRILL

- Does High Precision Work
- Handles Many Jobs
- Cuts Fixturing Costs



AVAILABLE WITH HYDRAULIC OR LEAD SCREW FEED

For gun drilling smooth, round, straight, deep holes up to ¾" diameter in ferrous or non-ferrous materials, consider the advantages of this Leland-Gifford Universal Gun Drill:

Coordinate elevating, traversing and swiveling of the table eliminates much expensive fixturing. You can handle a wide variety of jobs quickly and economically.

Available with hydraulic or lead screw feed. Choose the feed unit best for your range of hole diameters and depths.

There are few holes too deep, too small or too accurate to be drilled with this modern, capable gun drilling equipment.

For complete information, write for detailed bulletin — or ask to have an experienced sales engineer call.



LELAND-GIFFORD

WORCESTER 1, MASSACHUSETTS

DRILLING MACHINES

Rocheleau Tool & Die Company 83
Rockford Engineered Products Company213
Rockwell Manufacturing Company 46
(Delta Power Tool Division)
Rockwin Manufacturing Company219
Ross Equipment Company221
Rothfuss Tool Company218
Ruthman Machinery Company 97

5

S. P. Manufacturing Corporation	89
Sales Service Manufacturing Company2	21
Sanford Manufacturing Company64	
Scientific Lubricants Company2	
Service Machine Company	
Severance Tool Industries, Inc	
Sheffield Corporation	
Sheldon Machine Company	
Sid Tool Company 2 Simonds Saw & Steel Company 34	25
Simonds Saw & Steel Company34-	30
Skinner Precision Industries, Inc.	38
(Skinner-Horton Chuck Division)	
Somma Tool Company	32
South Bend Lathe Works, Inc.	
Speedlap Corporation2	15
Spellman Company, R. L2	53
Sperman Metal Specialties, Inc2	
Spitfire Tool & Machine Company	14
Standard Electrical Tool Company2	72
Star Cutter Company2	49
Stueck, W. Whitney1	99
Sunnen Products Company	
Supreme Products, Inc.	
Syntron Company	
-1	-

NEW HONING LAP

Laps Everything Better Than
Diamond Will Not Load Finer
Finish Laps overything from plastic
to hardest carbides without loading!
 Costs 70% Loss than diamond Use
wet or dry o Four grits—180-220-3806-500
 Easily resurfaced by ordinary sanding.



BUY DIRECT-MONEY- \$8.75 each, BACK GUARANTEE any grit WRITE FOR LARGE COLOR PHOTO

NEWTOOLS INC.

Use postpaid card. Circle No. 451

T

Taft-Peirce Manufacturing Company206
Tahlen Hammer Company 208
(Div. H. F. Soderling Co.)
Tamms Industries, Inc220
Thompson and Son Company, Henry G 87
Thriftmaster Products Corporation
Torit Manufacturing Company197
Torsion Balance Company201
Tracatorm Corperation234
Training for Industry270
Tree Tool & Die Works 10
Trico Fuse Manufacturing Company166

U

U. S. Tool	Company	44
	Engineering Company	
Universal	Vise and Tool Company 192-	193

V

Vacuum Research Corporation
Victor Machinery Exchange, Inc245
Victory Diamond Tool Company209
Viking Tool Company
Vogel Tool & Die Corporation230
Von Arnauld Company, W218

W

Wade Tool Company 2
Wales-Strippit Company 42
Walker Company, O. S 58
Wallace Supplies Manufacturing Co224
Wardwell Manufacturing Company187
Warner & Swasey Company16-17
Watts Brothers Tool Works238
Weldon Roberts Rubber Company 78
(Brightboy Industrial Division)
Weldon Tool Company
Wells Manufacturing Company207
Wetmore Tool & Engineering Company179
Whistler & Sons, Inc., S. B
Wiedemann Machine Company 48
Williams & Company, J. H
Woodson Tool Company268

Z

Zagar,	Inc.	*******************	.2	4
--------	------	---------------------	----	---



TRIED · PROVEN · GUARANTEED MICRO MINIATURE END MILLS

2 Flute 1/32 through 3/16 by 1/64s 3 & 4 Flute 3/32 through 3/16 by 1/32s ALL SIZES SINGLE AND DOUBLE END

2 and 3 Flute Flat or Ball End—4 Flute Flat End Only

DISTRIBUTORS STUB LENGTH IN ALL SIZES to principal cities

WOODSON TOOL CO. 4811 tennox Blvd Inglewood, Calif



WHY WAIT FOR SPECIAL TAPS?

Has them IN STOCK for IMMEDIATE DELIVERY!

HIGH SPEED

SPECIAL

RIGHT HAND TAPS

SIZE	THREAD	SIZE	THREAD	SIZE	THREAD
00	96	15/32	32	1-3/4	5-8-10-12-14-
0	70-72-76-80	1/2	12-13-14-16-18-20-24-27-		16-18-20-24
	48-56-64-72-80-90	.,-	28-32-36-40	1-13/16	8-10-12-14-
2	48-52-54-56-64-72-80	9/16	12-14-16-18-20-24-27-28-		16-18-20-24-32
3	40-44-46-48-56-60-64		32-36-40	1-7/8	5-8-10-12-14-16-
4	32-36-40-48-56-60-64	5/8	10-11-1214-16-18-20-24-		18-29-24
•	72-80	9/0	27-28-32-36-40	1-15/16	5-6-8-10-12-
5	30-32-36-40-44-48-56-	11/16	10-11-12-14-16-18-20-24-	1-10/10	14-16-18-20
9	64-80	11/10	27-28-32-40	2	8-10-12-14-16-18-20
R .	30-32-36-40-48-56-60-64	3/4	10-11-12-14-16-18-20-24-	2-1/16	12-14-16
9	72-80	3/4	27-28-30-32-36-40	2-1/8	8-10-12-14-
7	30-32-36-40-48-64	13/16	10-12-14-16-18-20-24-27-	4-1/0	16-18-20
8	24-30-36-40-44-48-56-60-	13/19	32	2-3/16	10-18-20
8	64-80	7/8	9-10-12-14-16-18-20-24-	2-3/10	10-12-14-
	24-28-32-36-40	1/8	27-28-32-40	2 1/4	10 0 10
9		15/16	8-9-10-12-14-16-18-20-	2-1/4	41/2-8-10-
10	28-30-36-40-48-56-60-64	15/10			12-14-16-18
12	20-22-24-28-30-32-36-40-		24-27-32-40	2-5/16	12-14-16-
	56-60	1	8-10-12-14-16-18-20-24-		18
14	20-24-28-32-40		27-32-36-40	2-3/8	10-12-14-16-18
1/16	60-64-72	1-1/16	10-12-14-16-18-20-24-27-	2-1/2	4-8-10-12-
5/64	72		32		14-16-18
3/32	36-48	1-1/8	7-8-10-12-14-16-18-20-	2-9/16	12-14
1/8	32-36-40-44-48		24-27-32-36	2-5/8	8-10-12-
5/32	32-36-38-40-44-48	1-3/16	8-10-12-14-16-18-20-24-		14-16-18
3/16	20-24-28-32-36-40-45		27-32	2-3/4	4-8-10-
7/32	20-24-28-32-36-40	1-1/4	7-8-10-12-14-16-18-20-		12-14-16
1/4	14-16-18-22-24-26-27-28-		24-27-32	2-7/8	8-10-12-
	30-32-36-40-48-56-64	1-5/16	6-8-10-12-14-16-18-20-	1	14-16
9/32	18-20-24-27-28-32-40-64	1	24-27-32	3	4-8-10-
5/16	16-18-20-22-24-26-27-28-	1-3/8	6-8-10-12-14-16-18-20-	-	12-14-16
	30-32-36-40-48-64	1	24-27-32	3-1/4	8-10-12-
11/32	20-28-32-40-48	1-7/16	8-10-12-14-16-18-20-24	1 1	14-16
3/8	12-13-14-18-20-22-27-28-	1-1/2	6-8-10-12-14-16-18-20-24	3-1/2	8-10-12-
0/0	30-32-36-40-48	1-9/16	12-14-16-18-29-24	0-1/2	14-16
13/32	16-20-24-32	1-5/8	51/2-6-8-10-12-14-	3-3/4	4-8-10-
7/16	12-14-16-18-20-24-27-28-	1-0/0	16-18-20-24	0-0/4	12-14
2/10	32-36-40	1-11/16	6-8-10-12-14-16-18-20-24	4	8-10-12
	32-30-40	1-11/19	0-0-10-17-14-10-10-20-24	1.4	0-10-12

HIGH SPEED LEFT HAND TAPS

SIZE	THREAD	SIZE	THREAD	SIZE	THREAD
0	80	3/8	16-24-32	1-3/8	6-8-10-12-16-18-20-24
1	56-64-72	7/16	14-20-28	1-7/16	8-10-12-14-16-18-20
2	06-64	1/2	12-13-20-28	1-1/2	6-8-10-12-16-18-20
3	56	9/16	12-18-20-24	1-9/16	8-10-12-16-18-20
4	32-36-40-48	5/8	11-12-18-20-24	1-5/8	8-10-12-14-16-18-20
5	40-44	11/16	11-16-24	1-11/16	8-10-12-14-16-18-26
6	32-36-40	3/4	10-16-18-20	1-3/4	8-10-12-14-16-18-20
8	32-36-40	13/16	16	1-13/16	8-10-12-14-16-18-20
10	24-30-32-40	7/B	9-12-14-18-20	1-7/8	8-10-12-14-16-18-20
12	24-28-32	1	8-12-14-16-18-20	1-15/16	8-10-12-14-16-18-20
1/4	20-28-32	1-1/8	7-12	2	41/2-10-12
E / LE	10 00 04 00 00	1 1/4	7 10 10 10	-	-14 -1 -1

. SPECIAL AND LEFT HAND DIES IN STOCK .

NOTE: Oversize, Undersize, Metric, 64th and 32nd Size Taps Available for Quick Delivery. We stock Special Sizes in High Speed Milling Cutters, Slitting Saws, End Mills and Reamers.

Dealer Inquiries Invited

If you are a user of cutting tools it will pay you to be on our mailing list.

SID TOOL COMPANY, INC.

Cutting Tool Specialists
158 LAFAYETTE ST., NEW YORK 13, N. Y.
Telephone: BEekman 3-4270

Don't Overlook These Features

- America's Amazing Abilities well describes the work of Henry Viscardi, Jr., president of Abilities, Inc. BLUE BOOK'S editor, Ed Altholz, interviews Viscardi to report on the latest thinking of this leader in the hiring of the disabled.

 Page 102
- Chipless Machining is the subject of a new regular column in BLUE BOOK. The series will be written by Charles H. Wick. This month's column outlines what chipless machining is and how it fits into today's production processes

 Page 128
- There's No Need To Postpone Numerical Control, says managing editor Jim Pond, if tape preparation is holding you back. The reason is simple; tape preparation services are now available to industry. This article describes one such service.

 Page 118

FLUID POWER

HOME STUDY COURSE

"installation, operation and maintenance" of F/P equipment

An up to date practical course of study covering Theory, Fundamentals of Operation, Application, Diagnosis and Repair, for all types of Hydraulic and Pneumatic equipment and controls.

"easy to understand"

LOW COST

Has impartial support of National Fluid Power Association



Mr. Manager: It's a sound investment to sponsor studies for your men who are interested enough to improve themselves in their jobs.

Send for: Descriptive Literature and enrollment blank.

TRAINING for INDUSTRY DIVISION

P.O. BOX 120 LOGANSPORT, INDIANA



One Last Word

B

Is the U.S. Losing the Race?

A nyone interested in America's economic future looks with horror on the implications of the January shipments of the American machine tool builders. These implications are shocking. How does anyone, having his country's welfare at heart, sleep soundly at night?

Shipments of all types of metal cuting machine tools totaled \$35.5 million. Of these \$14.5 million were foreign shipments, or a whopping 41%. The balance, or \$21 million, were domestic shipments. The implications which worry us lie in the ratio of foreign to domestic orders.

Why are foreign industries, especially European automotive, plunking down hard cash for American machine tools? Primarily, because the European machine tool industry, producing to capacity, cannot meet the demand. (By contrast, our own machine tool industry is below 50% of capacity.) The significant point is this: foreign industries are expanding and modernizing so rapidly that their own machine tool industry cannot meet the programs of their industries.

With the exception of the U.S., all industrial nations are arming for an assault on world markets, including our own domestic market.

With the exception of the U.S., all industrial nations are modernizing their facilities, replacing their equipment so that the world's needs for products of every kind and description will be satisfied.

The U.S. is not modernizing at the rate it should, it is not replacing obsolete clunkers, it is not reinvesting in productive equipment and facilities. The climate, tax-wise, for modernization and capital expenditures has not only been poor, it's been criminal.* Thus we see foreign customers buying our machine tools, in addition to their own, to increase productivity; at the same time we run around, spread gloom, complain, and let the old clunkers rattle around for another five years.

The goods and products which foreign nations will produce economically with our tools will haunt us. The import picture (and we have no fight with importers, believing, as we do in free trade) will be black for American business and for the American worker.

The U.S. must replace, must modernize, must grow up industrially and take advantage of new techniques, it must forge its weapons in a healthy fiscal and a sound depreciation climate. This is as urgent as finding a bucket for bailing out a water-filled boat.

*We are encouraged by President Kennedy's awareness of this problem and by his desire to do something about it. Report of this appears on page 164.

Wm. 7. Schleicher



Right Angle Attachmen



No. 4208M



No. 6026M Motorized, Liquid or Fan Cooled; with Feed



No. OOMY with Built-in Feed



Piggy-Back

pecify rugged, dependable Standard Super Precision Milling Spindles. The nation's widest line of conventional designs plus custom engineering service.

"endless versatile variations" WRITE FOR CATALOG TODAY!



No. 4250M2Y Infinitely Variable 100 to 1000 R. P.



PRECISION SPINDLE DIVISION

electrical tool co.

2486 RIVER ROAD, CINCINNATI 4, OHIO

Use postpoid cord, Circle No. 443








TALK ABOUT ABILITY!

This husky boasts a 100 hp main drive motor and spindle speed range of 6 to 750 rpm. Its massive $7\frac{1}{2}$ " tailstock spindle offers big load capacity. Pre-selective hydraulic powershift and push button control of cross and longitudinal feeds keep this giant under fingertip control. 48 spindle speeds provide any surface speed with a deviation of less than 6% from that actually required for the chosen diameter. The operator, after setting the correct surface speed, merely dials the work diameter. The computing dials then automatically produce the correct rpm for each diameter. Or . . . the operator may choose rpm directly if he wishes. Write for Bulletin 913-A.

100 HORSEPOWER

AMERICAN 40" STYLE J-100

PRE-SELECT ENGINE LATHE



This and all other AMERICAN machine tools are available on "Toolease", our own equipment leasing plan.

COMPETE COMPETENTLY WITH



LATHES . RADIAL DRILLS SPECIAL MACHINES



The American Tool Works Company

Pearl Street at Eggleston Avenue

Cincinnati 2, Ohio

NEW

COMBINATION



Choose your stock...plastic, metal or wood! Choose from 8 speeds . . . 40 to 3000 SFM, with two-speed transmission!

Check every unique heavy-duty feature of this newest Powermatic-engineered contour saw. Designed for safety, performance and micro-accuracy...priced right for your shop!

- CROSS-RIBBED, ONE-PIECE CAST IRON FRAME
- BIG 15" x 15" CAST IRON TILTING TABLE
- EASY-TO-SET ADJUSTMENTS
- ALL MOVING PARTS COMPLETELY GUARDED

Model 143 14" Band Saw POWERMATIC

MACHINE COMPANY Dept. 9

McMinnville, Tennessee
IN CANADA: 650 MAITLAND ST., LONDON, ONT.

Get Full Details Now!

Rush me details on the new Model 143 Band Saw

Name____

Address____

City & State _____

PRECISION

BAND SAWS DRILL PRESSES GRINDERS AND WOODWORKING MACHINES

